



nassli
LED LIGHTS

LED FLOOD LIGHT-T

Application:

Ideal for any large area with height ceiling. such as, warwhouse, factories, closed parks, commercial complexes, indoor playgrounds, hangars

Feuture:

High cooling aluminum, with zip technology and 3D cooling created air convection channel, make it ideal for hot area. High lumen output. High power saving fixture. Overload protection, short circuit protection, and no-load protection

SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	120 - 277 VAC
Frequency	50 / 60 Hz
Power Factor	>98%
CCT	GREEN, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	130 - 140Lm/W
Power supply	Tridonic / Philips/Nassli
LED Type	Osram / Philips
Materials	Aluminum, PC, & Friendly material
Beam Angle	143° x 67°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Wall Mounted / with Base
IP Rating	IP65
Dimmable	On Request
Emergency	N/A
Warranty	5 Years



Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-FLT-30W-XXK-SMD- NS-IP65	L290 W190 H55	30	3900
NSL-FLT-50W-XXK-SMD-NS-IP65	L290 W190 H55	50	6500
NSL-FLT-100W-XXK-SMD-TD-XX-IP65	L415 W235 H90	100	13000
NSL-FLT-100W-XXK-SMD-PH-XX-IP65	L415 W235 H90	100	13000
NSL-FLT-150W-XXK-SMD-TD-XX-IP65	L555 W310 H95	150	19500
NSL-FLT-150W-XXK-SMD-PH-XX-IP65	L555 W310 H95	150	19500
NSL-FLT-200W-XXK-SMD-TD-XX-IP65	L555 W310 H95	200	26000
NSL-FLT-200W-XXK-SMD-PH-XX-IP65	L555 W310 H95	200	26000