



nassli
LED LIGHTS

ISLAMIC LED PANEL

Application:

Ideal for any large area with height ceiling. such as, warwhouse, factories, closed parks, commercial complexes, indoor playgrounds, hangars, mosques.

Feature:

High cooling aluminum, with zip technology and 3D cooling created air convection channel, make it ideal for hot area. High lumen output. High power saving fixture. Overload protection, short circuit protection, and no-load protection



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	120 - 277 VAC
Frequency	50 / 60 Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	140Lm/W
Power supply	Inventronics / QP
LED Type	Osram / Philips
Materials	Aluminum, PC, & Friendly material
Beam Angle	70° x 130°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Surface Mounted
IP Rating	IP65
Dimmable	On Request
Emergency	N/A
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-ISLP-150W-XXK-SMD-PH-XX-IP65	L: 290, W: 270, H: 120	150	21000

INSTALLATION

