



nassli
LED LIGHTS

LED LIGHT UNDER CANOPY T



Application:

Ideal for Gas Station, Factory, Industrial Area, Shopping Center, Green House, Football field, Car Park, Warehouse, General Lighting etc.

Feature:

Fixture designed for Harsh and hot environments. High lumen output. Aluminum heat dissipation module has surface anodic oxidation process to make it very resistant and anti-aging fixture. Over temperature protection, Overload protection, Short-circuit protection, and No-load protection

WHITE FINISH



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	120 - 277 VAC
Frequency	50 / 60 Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120 - 130Lm/W
Power supply	Tridonic / Philips
LED Type	Osram / Philips
Materials	Aluminum, PC, & Friendly material
Beam Angle	90°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP65
Dimmable	On Request
Emergency	N/A
Warranty	5 Years

CUT OUT: 305X305MM

Clearance Height above fixture: 150mm

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-UCAN-V2-100W-XXK-SMD-TD-CN-IP65	L335 W335 H70	100	12500
NSL-UCAN-V2-100W-XXK-SMD-PH-CN-IP65	L335 W335 H70	100	12500