



nassli
LED LIGHTS

LED HIGH BAY A

Application:

Ideal for any large area with height ceiling. such as, warehouse, factories, closed parks, commercial complexes, indoor playgrounds, hangars

Feature:

High cooling aluminum, with zip technology and 3D cooling created air convection channel, make it ideal for hot area. High lumen output. High power saving fixture. Overload protection, short circuit protection, and no-load protection

reflector : Available upon request



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	85-305VAC
Frequency	50 / 60 Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120 - 130Lm/W
Power supply	Nassli
LED Type	Philips
Materials	Aluminum, PC, & Friendly material
Beam Angle	60° 90° 120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Suspended
IP Rating	IP65
Dimmable	As per customer's request
Emergency	As per customer's request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-HBT-VEG-L1-150W-XXK-SMD-NS-IP65	D 299.29 H 181.5	150	18000