



nassli
LED LIGHTS

LED TUBE

Application:

It can be used for Hotels, Government Buildings, offices, Residential Buildings (villas, palaces, apartment), School collage and University, Hospitals Super Market.

Feature:

The product is used as a pure light source, using LED technology, human and environment friendly, no Pb, Hg nor UV. It does not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 VAC / 85 - 305 VAC
Frequency	50 / 60 Hz
Power factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power supply	Nassli / LF / ZY
LED Type	Osram / Epistar
Materials	Aluminum, PC, & Friendly material
Beam Angle	120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Wall Mounting, Surface, Suspended
IP Rating	IP20
Dimmable	N/A
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-LTUV2-60T8-11W-XXK-SMD-ZY-IP20	L600 x D30	11	1210
NSL-LTUV2-120T8-14W-XXK-SMD-ZY-IP20	L1200 x D30	14	1540
NSL-LTUV2-120T8-18W-XXK-SMD-ZY-IP20	L1200 D30	18	1980
NSL-LTUV2-120T8-20W-XXK-SMD-LF-IP20	L1200 D30	20	2200
NSL-LTUV2-120T8-20W-XXK-SMD-ZY-IP20	L1200 D30	20	2200
NSL-LTUV1-120T8-22W-XXK-SMD-LF-IP20	L1200 D30	22	2420
NSL-LTUV2-150T8-30W-XXK-SMD-ZY-IP20	L1500 D30	30	3300



nassli
LED LIGHTS

WATERPROOF LED TUBE

Application:

It can be widely used for Trade Shows, Supermarkets, Schools, Hospitals, Factories, Car Parking, Airport, Corridor etc....

Feature:

LED ceiling light: The LED diffuser light is mounted directly on the ceiling for plaster ceiling mounting. The LED moisture-proof diffuser light is already completely wired for LED technology and does not have to be converted. Operating temperature -20°C to 65°C, low heat generation: Temperature heat sink >1h max. approx. 45°C Robust plastic housing and protection class IP65 prevent penetration of foreign bodies or dust as well as protection against water jets

SPECIFICATIONS

ITEM	DESCRIPTION
Materials	Aluminum, PC, & Friendly material
Raw material	Polycarbonate
Beam Angle	120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Mounting	Ceiling, Wall mounting
IP Rating	IP65
Mech. Impact Protection	IK07
Warranty	5 Years



Order code	Dimensions(mm)	LED SIZE	IP Rating
NSL-WP-LTU-2x150-IP65	L1567 x W125 x H85	T8-150	65
NSL-WP-LTU-1x150-IP65	L1567 x W95 x H85	T8-150	65
NSL-WP-LTU-2x120-IP65	L1267 x W125 x H85	T8-120	65
NSL-WP-LTU-1x120-IP65	L1267 x W95 x H85	T8-120	65
NSL-WP-LTU-2x60-IP65	L667 x W125 x H85	T8-60	65
NSL-WP-LTU-1x60-IP65	L667 x W95 x H85	T8-60	65



nassli
LED LIGHTS

WATER PROOF LED TUBE WITH PCB

Application:

It can be widely used for Trade Shows, Supermarkets, Schools, Hospitals, Factories, Car Parking, Airport, Corridor etc....

Feature:

LED ceiling light: The LED diffuser light is mounted directly on the ceiling for plaster ceiling mounting. The LED moisture-proof diffuser light is already completely wired for LED technology and does not have to be converted. Operating temperature -20°C to 65°C, low heat generation: Temperature heat sink >1h max. approx. 45°C Robust plastic housing and protection class IP65 prevent penetration of foreign bodies or dust as well as protection against water jets



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 VAC / 85 - 305 VAC
Frequency	50 / 60Hz
Power factor	>98%
CCT	3000K, 4000K, 5000K, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power supply	Tridonic / Nassli / LF / ZY / GL
LED Type	Osram / Epistar
Materials	Aluminum, PC, & Friendly material
Beam Angle	120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Wall mounting, Surface
IP Rating	IP65
Mech. Impact Protection	IK07
Dimmable	N/A
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-WP-PCB-2x120-40W-XXK-SMD-NS-IP65	L1267 x W125 x H85	40	4400
NSL-WP-PCB-2x120-40W-XXK-SMD-ZY-XX-IP65	L1267 x W125 x H85	40	4400
NSL-WP-PCB-2x120-40W-XXK-SMD-TD-XX-IP65	L1267 x W125 x H85	40	4400
NSL-WP-PCB-2x120-40W-XXK-SMD-PH-XX-IP65	L1267 x W125 x H85	40	4400
NSL-WP-PCB-2x120-50W-XXK-SMD-NS-IP65	L1267 x W125 x H85	50	5500



nassli
LED LIGHTS

WATER PROOF LED TUBE WITH PCB

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-WP-PCB-1x120-25W-XXK-SMD-NS-IP65	L1267 x W125 x H85	25	2750
NSL-WP-PCB-1x120-25W-XXK-SMD-ZY-XX-IP65	L1267 x W125 x H85	25	2750
NSL-WP-PCB-1x120-25W-XXK-SMD-TD-XX-IP65	L1267 x W125 x H85	25	2750
NSL-WP-PCB-1x120-18W-XXK-SMD-ZY-XX-IP65	L1267 x W125 x H85	18	1980
NSL-WP-PCB-1x120-20W-XXK-SMD-ZY-XX-IP65	L1267 x W125 x H85	20	2200
NSL-WP-PCB-1x120-20W-XXK-SMD-PH-XX-IP65	L1267 x W125 x H85	20	2200
NSL-WP-PCB-1x120-22W-XXK-SMD-LF-XX-IP65	L1267 x W125 x H85	22	2420

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-WP-PCB-2x60-22W-XXK-SMD-NS-IP65	L667 x W125 x H85	22	2420
NSL-WP-PCB-2x60-22W-XXK-SMD-ZY-XX-IP65	L667 x W125 x H85	22	2420
NSL-WP-PCB-2x60-22W-XXK-SMD-TD-XX-IP65	L667 x W125 x H85	22	2420
NSL-WP-PCB-2x60-22W-XXK-SMD-PH-XX-IP65	L667 x W125 x H85	22	2420
NSL-WP-PCB-1x60-11W-XXK-SMD-NS-IP65	L667 x W95 x H85	11	1210
NSL-WP-PCB-1x60-11W-XXK-SMD-ZY-XX-IP65	L667 x W95 x H85	11	1210
NSL-WP-PCB-1x60-11W-XXK-SMD-TD-XX-IP65	L667 x W95 x H85	11	1210
NSL-WP-PCB-1x60-11W-XXK-SMD-PH-XX-IP65	L667 x W95 x H85	11	1210
NSL-WP-PCB-2x150-60W-XXK-SMD-NS-IP65	L1567 x W125 x H85	60	6600
NSL-WP-PCB-2x150-60W-XXK-SMD-TD-XX-IP65	L1567 x W125 x H85	60	6600
NSL-WP-PCB-2x150-60W-XXK-SMD-PH-XX-IP65	L1567 x W125 x H85	60	6600
NSL-WP-PCB-2x150-60W-XXK-SMD-ZY-XX-IP65	L1567 x W125 x H85	60	6600
NSL-WP-PCB-1x150-30W-XXK-SMD-NS-IP65	L1567 x W95 x H85	30	3300
NSL-WP-PCB-1x150-30W-XXK-SMD-TD-XX-IP65	L1567 x W95 x H85	30	3300
NSL-WP-PCB-1x150-30W-XXK-SMD-PH-XX-IP65	L1567 x W95 x H85	30	3300
NSL-WP-PCB-1x150-30W-XXK-SMD-ZY-XX-IP65	L1567 x W95 x H85	30	3300