



nassli
LED LIGHTS


WATER PROOF LED TUBE WITH PCB

Application:

It can be widely used for Trade Shows, Supermarkets, Schools, Hospitals, Factories, Car Parking, Airport, Corridor etc....

Feature:

LED ceiling light: The LED diffuser light is mounted directly on the ceiling for plaster ceiling mounting. The LED moisture-proof diffuser light is already completely wired for LED technology and does not have to be converted. Operating temperature -20°C to 65°C, low heat generation: Temperature heat sink >1h max. approx. 45°C Robust plastic housing and protection class IP65 prevent penetration of foreign bodies or dust as well as protection against water jets



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 VAC / 85 - 305 VAC
Frequency	50 / 60Hz
Power factor	>98%
CCT	3000K, 4000K, 5000K, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power supply	Tridonic / Nassli / LF / ZY
LED Type	Osram / Epistar
Materials	Aluminum, PC, & Friendly material
Beam Angle	120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Wall mounting, Surface
IP Rating	IP65
Mech. Impact Protection	IK07
Dimmable	N/A
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-WP-PCB-2x120-50W-XXK-SMD-NS-IP65	L1267 x W125 x H85	50	5500LM

NASSLI FOR ELECTRICAL INDUSTRY C.R. 1010328884
www.nassli-led.com.sa, +966 (011) 247122
Riyadh, Kingdom of Saudi Arabia



nassli
LED LIGHTS

WATER PROOF LED TUBE WITH PCB

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-WP-PCB-1x120-25W-XXK-SMD-NS-IP65	L1267 x W125 x H85	25	2750
NSL-WP-PCB-1x120-25W-XXK-SMD-ZY-XX-IP65	L1267 x W125 x H85	25	2750
NSL-WP-PCB-1x120-25W-XXK-SMD-TD-XX-IP65	L1267 x W125 x H85	25	2750
NSL-WP-PCB-1x120-18W-XXK-SMD-ZY-XX-IP65	L1267 x W125 x H85	18	1980
NSL-WP-PCB-1x120-20W-XXK-SMD-ZY-XX-IP65	L1267 x W125 x H85	20	2200
NSL-WP-PCB-1x120-20W-XXK-SMD-PH-XX-IP65	L1267 x W125 x H85	20	2200
NSL-WP-PCB-1x120-22W-XXK-SMD-LF-XX-IP65	L1267 x W125 x H85	22	2420

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-WP-PCB-2x60-22W-XXK-SMD-NS-IP65	L667 x W125 x H85	22	2420
NSL-WP-PCB-2x60-22W-XXK-SMD-ZY-XX-IP65	L667 x W125 x H85	22	2420
NSL-WP-PCB-2x60-22W-XXK-SMD-TD-XX-IP65	L667 x W125 x H85	22	2420
NSL-WP-PCB-2x60-22W-XXK-SMD-PH-XX-IP65	L667 x W125 x H85	22	2420
NSL-WP-PCB-1x60-11W-XXK-SMD-NS-IP65	L667 x W95 x H85	11	1210
NSL-WP-PCB-1x60-11W-XXK-SMD-ZY-XX-IP65	L667 x W95 x H85	11	1210
NSL-WP-PCB-1x60-11W-XXK-SMD-TD-XX-IP65	L667 x W95 x H85	11	1210
NSL-WP-PCB-1x60-11W-XXK-SMD-PH-XX-IP65	L667 x W95 x H85	11	1210
NSL-WP-PCB-2x150-60W-XXK-SMD-NS-IP65	L1567 x W125 x H85	60	6600
NSL-WP-PCB-2x150-60W-XXK-SMD-TD-XX-IP65	L1567 x W125 x H85	60	6600
NSL-WP-PCB-2x150-60W-XXK-SMD-PH-XX-IP65	L1567 x W125 x H85	60	6600
NSL-WP-PCB-2x150-60W-XXK-SMD-ZY-XX-IP65	L1567 x W125 x H85	60	6600
NSL-WP-PCB-1x150-30W-XXK-SMD-NS-IP65	L1567 x W95 x H85	30	3300
NSL-WP-PCB-1x150-30W-XXK-SMD-TD-XX-IP65	L1567 x W95 x H85	30	3300
NSL-WP-PCB-1x150-30W-XXK-SMD-PH-XX-IP65	L1567 x W95 x H85	30	3300
NSL-WP-PCB-1x150-30W-XXK-SMD-ZY-XX-IP65	L1567 x W95 x H85	30	3300