



nassli
LED LIGHTS

LED LINEAR LIGHT S

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas, Kitchens and Corridor etc...

Feature:

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV. Do not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60 H z
Power factor	>98%
CCT	3000K, 4000K, 5000k, 6000K
CRI	>80%
LED Efficiency	110-120lm/W
Power supply	Nassli
LED Type	Osram, Bridgelux
Materials	Aluminum, PC, & Friendly material
Frame color	On Request
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	Suspended
IP Rating	IP20
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

IT CAN BE WITH ACYLIC DIFFUSER OR STRETCH FABRIC

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-DECORATIVE-PENDANT LIGHT-CIRC-FULL DIFF	H300 Ø(300:1000)	(20:60)W	(2200:6600)lm