



NASSLI
LED LAMP

NASSLI LED LINEAR LIGHT

Product .: LED Linear Light CIRCULAR RING
P.N: NSL-DECORATIVE-PENDANT LIGHT-CIRC-UP-DOWN

Application

It can be widely used for Decoration, shopping malls, Trade shows, Supermarkets,

Hotels, Schools, Hospitals, Factories, Conference Hall, Palces, Meeting room, Theater,

Cinemas, Kitchens and Corridor etc...

Technical Data:

Power Source: 220-240 VAC 50/60HZ

LED Type: Osram

Power Supply: Tridonic / Nassli / GL

Low tolerances for colour tempreature: Mac

Humidity Storage: 10-80%

IK Code: IK02.

Frame color: As per client requirements

Dimmable: DALI Power Supply on request.

Size:

1-Diameter: 5200mm

Width: 70mm

Height: 100mm

Light Source:

LIGHT SOURCE DIRECT AND INDIRECT DIRECTIONS, DIRECT (DOWN): 30W/M,
INDIRECT (UP): 10W/M, TOTAL 40W/M, TOTAL 653W/PCS



SPECIFICATIONS

MAIN SPECIFICATIONS (T=25C)

ITEM	DESCRIPTION
Input Voltage	220-240 VAC
Frequency	50/ 60 Hz
LED Type	Osram
Power	653W
Power supply	Tridonic / Nassli / Gruenes Licht
Flux	71830LM/pcs
Mounting	Suspended
LED Efficiency	110-120Lm/W
Materials	Aluminum, PC, & Friendly material
Power factor	>98%
CCT	3000K, 4000K, 6000K, RGB
CRI	>85
Life Time	>50,000 Hour
Operating Temperature	-20°C to +55°C
Storage Temperature	-40°C to +65°C
Certifications	CE, SELV, ISO and ROHS
Size	
IP Rating	IP20