



nassli
LED LIGHTS

LED SURFACE LIGHT

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas, Kitchens and Corridor etc...

Feature:

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV. Do not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.



LC6



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60 H z
Power factor	>98%
CCT	3000K, 4000K, 5000k, 6000K
CRI	90%
LED Efficiency	110-120Lm/W
Power supply	Tridonic / Nassli / GL / QP
LED Type	Osram, Bridgelux
Materials	Aluminum, PC, & Friendly material
Frame color	On Request
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Mounting	Surface
IP Rating	IP20
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-DECORATIVE-SURFACE MOUNTED LIGHT	H100 Ø600	55W	5500lm