



nassli
LED LIGHTS

LED LINEAR

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room, Theater, Cinemas, Kitchens and Corridor


Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV. Do not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.

W: 50mm, H: 50mm, L: Various, W: 30W/M, Lumen: 3300LM/M

SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 VAC
Frequency	50 / 60 Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120 - 130Lm/W
Power supply	Tridonic, Nassli, GL
LED Type	Osram
Materials	Aluminum, PC, & Friendly material
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP20
Length	Customized
Dimmable	DALI
Emergency	Yes
Warranty	5 Years



Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-LLR-CIRC-5X5-30WM-XXK-SMD-XX-IP20	W50 H50	30W/M	3300LM/M