



**nassli**  
LED LIGHTS

## LED LINEAR RS


### Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room, Theater, Cinemas, Kitchens and Corridor

### Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV. Do not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.

Mounting: Suspended, Recessed, Surface mounted.



## SPECIFICATIONS

| ITEM           | DESCRIPTION                       |
|----------------|-----------------------------------|
| Input Voltage  | 220 - 240 VAC                     |
| Frequency      | 50 / 60 Hz                        |
| Power Factor   | >95%                              |
| CCT            | 2700K, 3000K, 4000K, 6000K,       |
| CRI            | >80%                              |
| LED Efficiency | 120 - 130Lm/W                     |
| Power supply   | Tridonic / Nassli                 |
| LED Type       | Osram                             |
| Materials      | Aluminum, PC, & Friendly material |
| Beam Angle     | 120°                              |
| Life Time      | >50,000 Hour                      |
| Operating Temp | -20°C to +55°C                    |
| Storage Temp   | -40°C to +85°C                    |
| Certifications | CE, SELV and ISO                  |
| Mounting       | Recessed, Suspended               |
| IP Rating      | IP20 / IP40                       |
| Dimmable       | On Request                        |
| Emergency      | On Request                        |
| Warranty       | 5 Years                           |

| Order code                                       | Dimensions(mm) | Power(Watt) | Lumen |
|--------------------------------------------------|----------------|-------------|-------|
| NSL-LLS-10x13x1000-CV24-10W/M-XXK-SMD-NS-IP20    | W10 H13        | 10          | 1100  |
| NSL-LLS-10x13x1000-CV24-10W/M-XXK-SMD-TD-XX-IP20 | W10 H 13       | 10          | 1100  |
| NSL-LLS-10x13x1000-CV24-10W/M-XXK-SMD-NS-IP40    | W10 H13        | 10          | 1100  |
| NSL-LLS-10x13x1000-CV24-10W/M-XXK-SMD-TD-XX-IP40 | W10 H 13       | 10          | 1100  |