



nassli
LED LIGHTS

Linear floor lighting


Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room, Theater, Cinemas, Kitchens and Corridor

Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV. Do not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.

Installation: For stairs / park / supermarkets and other public place application.



HL-BAPL048



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	24 VDC
Frequency	0Hz
Power Factor	>95%
CCT	2700K, 3000K, 4000K, 6000K,
CRI	>80%
LED Efficiency	120 - 130Lm/W
Power supply	Tridonic / Nassli
LED Type	Osram
Materials	Aluminum, PC, & Friendly material
Beam Angle	120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP65
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code

Dimensions(mm)

Power(Watt)

Lumen

NSL-LLR-27x11x1000-CV24-10W/M-XXK-SMD-NS-IP20

W21.3 H11 /27

10

1100