



nassli
LED LIGHTS

Suspended linear lighting

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room, Theater, Cinemas, Kitchens and Corridor

Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV. Do not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.


Mounting: Suspended, Recessed, Surface mounted.

Body color: Available upon request

Hanging accessories : available upon request.

SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220-240 VAC
Frequency	50/60 Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120 - 130Lm/W
Power supply	Nassli
LED Type	Osram
Materials	Aluminum, PC, & Friendly material
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Suspended
IP Rating	IP20
Dimmable	On Request
Emergency	On Request
Warranty	5 Years



Order code	Dimensions(Cm)	Power(Watt)	Lumen
NSL-LLSL1-19x2.6x120-10W-XXK-NS-IP20	W19 H2.6 L120	10	1100
NSL-LLSL1-19x2.6x120-15W-XXK-NS-IP20	W19 H2.6 L120	15	1650



**5 Year
Warranty**

nassli
LED LIGHTS

Suspended linear lighting

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room, Theater, Cinemas, Kitchens and Corridor

Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV. Do not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.


Mounting: Suspended, Recessed, Surface mounted.

Body color: Available upon request

Hanging accessories : available upon request.

SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220-240 VAC
Frequency	50/60 Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120 - 130Lm/W
Power supply	Nassli
LED Type	Osram
Materials	Aluminum, PC, & Friendly material
Beam Angle	120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Suspended
IP Rating	IP20
Dimmable	On Request
Emergency	On Request
Warranty	5 Years



Order code	Dimensions(Cm)	Power(Watt)	Lumen
NSL-LLSL2-18.9x5.8x120-10W-XXK-NS-IP20	W18.9 H5.8 L120	10	1100
NSL-LLSL2-18.9x5.8x120-15W-XXK-NS-IP20	W18.9 H5.8 L120	15	1650
NSL-LLSL2-18.9x5.8x120-20W-XXK-NS-IP20	W18.9 H5.8 L120	20	2200

NASSLI LED Factory C.R. 1010328884
www.nassli-led.com.sa Kingdom of Saudi Arabia
Riyadh (Head Office), P.O. Box25320 Riyadh 11466, UN: 920004733



NASSLI
LED LIGHTS

Suspended linear lighting

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room, Theater, Cinemas, Kitchens and Corridor


Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV. Do not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.

Mounting: Suspended, Recessed, Surface mounted.

Body color: Available upon request

Hanging accessories : available upon request.



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220-240 VAC
Frequency	50/60 Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120 - 130Lm/W
Power supply	Nassli
LED Type	Osram
Materials	Aluminum, PC, & Friendly material
Beam Angle	90°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Suspended
IP Rating	IP20
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(Cm)	Power(Watt)	Lumen
NSL-LLSL3-9.9x7.8x120-10W-XXK-NS-IP20	W9.9 H7.9 L120	10	1100
NSL-LLSL3-9.9x7.8x120-15W-XXK-NS-IP20	W9.9 H7.9 L120	15	1650
NSL-LLSL3-9.9x7.8x120-20W-XXK-NS-IP20	W9.9 H7.9 L120	20	2200



NASSLI
LED LIGHTS

Suspended linear lighting

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room, Theater, Cinemas, Kitchens and Corridor

Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV. Do not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.

Mounting: Suspended, Recessed, Surface mounted.

Body color: Available upon request

Hanging accessories : available upon request.



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220-240 VAC
Frequency	50/60 Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120 - 130Lm/W
Power supply	Nassli
LED Type	Osram
Materials	Aluminum, PC, & Friendly material
Beam Angle	60°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Suspended
IP Rating	IP20
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(Cm)	Power(Watt)	Lumen
NSL-LLSL4-11.4x10.8x120-10W-XXK-NS-IP20	W11.4 H10.8 L120	10	1100
NSL-LLSL4-11.4x10.8x120-15W-XXK-NS-IP20	W11.4 H10.8 L120	15	1650
NSL-LLSL4-11.4x10.8x120-20W-XXK-NS-IP20	W11.4 H10.8 L120	20	2200



nassli
LED LIGHTS

Suspended linear lighting

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room, Theater, Cinemas, Kitchens and Corridor

Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV. Do not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.

Mounting: Suspended, Recessed, Surface mounted.

Body color: Available upon request

Hanging accessories : available upon request.



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220-240 VAC
Frequency	50/60 Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120 - 130Lm/W
Power supply	Nassli
LED Type	Osram
Materials	Aluminum, PC, & Friendly material
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Suspended
IP Rating	IP20
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(Cm)	Power(Watt)	Lumen
NSL-LLSL2-18.9x5.8x120-15W-XXK-NS-IP20	W18.9 H5.8 L120	15	1650
NSL-LLSL2-18.9x5.8x120-20W-XXK-NS-IP20	W18.9 H5.8 L120	20	2200