



NASSLI
LED LIGHTS

LED LINEAR 2.5

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room, Theater, Cinemas, Kitchens and Corridor

Feature:

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV. Do not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.

Mounting: Suspended, Recessed, Surface mounted



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 VAC
Frequency	50 / 60 Hz
Power Factor	>98%
CCT	RGB
CRI	>80%
LED Efficiency	120 - 130Lm/W
Power supply	Tridonic / Nassli / Philips / Osram
LED Type	Osram / Epistar
Materials	Aluminum, PC, & Friendly material
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP20/65
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-LLR-25x25x1000-CV24-10W/M-XXK-SMD-NS-IP65	W2.5 H2.5	10	1100
NSL-LLR-25x25x1000-CV24-10W/M-XXK-SMD-TD-XX-IP20	W2.5 H2.5	10	1100
NSL-LLR-25x25x1000-CV24-10W/M-XXK-SMD-PH-XX-IP20	W2.5 H2.5	10	1100
NSL-LLR-25x25x1000-CV24-15W/M-XXK-SMD-NS-IP20	W2.5 H2.5	15	1650
NSL-LLR-25x25x1000-CV24-15W/M-XXK-SMD-TD-XX-IP20	W2.5 H2.5	15	1650
NSL-LLR-25x25x1000-CV24-15W/M-XXK-SMD-PH-XX-IP20	W2.5 H2.5	15	1650