



Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room, Theater, Cinemas, Kitchens and Corridor

Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV. Do not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.

SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220-240 VAC
Frequency	50/60 Hz
Power Factor	>95%
CCT	, 3000K, 4000K, 6000K,
CRI	>80%
LED Efficiency	120 - 130Lm/W
Power supply	/ Nassli
LED Type	Osram
Materials	Aluminum, PC, & Friendly material
Beam Angle	120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP54
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-LLR-XXxXXx1000-CV24-30W/M-XXK-SMD-NS-IP54	100*3.5*5cm	30W/m	3300