



**nassli**  
LED LIGHTS

## LED LINEAR

### Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room, Theater, Cinemas, Kitchens and Corridor

### Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV. Do not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.



## SPECIFICATIONS

| ITEM           | DESCRIPTION                       |
|----------------|-----------------------------------|
| Input Voltage  | 220 - 240 VAC                     |
| Frequency      | 50 / 60 Hz                        |
| Power Factor   | >98%                              |
| CCT            | 2700K, 3000K, 4000K, 6000K        |
| CRI            | >80%                              |
| LED Efficiency | 120 - 130Lm/W                     |
| Power supply   | Tridonic                          |
| LED Type       | Osram                             |
| Materials      | Aluminum, PC, & Friendly material |
| Beam Angle     | 160°                              |
| Life Time      | >50,000 Hour                      |
| Operating Temp | -20°C to +55°C                    |
| Storage Temp   | -40°C to +85°C                    |
| Certifications | CE, SELV and ISO                  |
| Mounting       | Recessed                          |
| IP Rating      | IP20                              |
| Length         | 400 - 1000 mm                     |
| Dimmable       | No                                |
| Emergency      | On Request                        |
| Warranty       | 5 Years                           |

### Order code

NSL-LLR-70x50x1000-CC-20W/M-XXK-SMD0.2-TD-CN-IP20

### Dimensions(mm)

W70 H80

### Power(Watt)

20

### Lumen

2200