



nassli
LED LIGHTS

LED LINEAR LIGHT

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room, Theater, Cinemas, Kitchens and Corridor

Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV. Do not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 VAC
Frequency	50 / 60 Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120 - 130Lm/W
Power supply	Tridonic, Nassli, GL
LED Type	Osram
Materials	Aluminum, PC, & Friendly material
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Suspended, Surface
IP Rating	IP40
Length	Customized
Dimmable	DALI, 0-10V On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-LLS-70X80X1000-CV24-30WM-XXK-SMD-NS-IP40	W70 H80	30W/M	3300LM/M
NSL-LLS-70X80X1000-CC-30WM-XXK-SMD-TD-AT-XX-IP40	W70 H80	30W/M	3300LM/M

NASSLI FOR ELECTRICAL INDUSTRY C.R. 1010328884
www.nassli-led.com.sa, +966 (011) 247122
Riyadh, Kingdom of Saudi Arabia