



NASSLI LED LINEAR LIGHT

NSL-LLS-T-50x80x1000-CV24-20WM-XXK-SMD-NS-IP65

Application

It can be widely used for Decoration, shopping malls, Trade shows, Supermarkets, Hotels, Schools,

Hospitals, Factories, Conference Hall, Palces, Meeting room, Theater, Cinemas,

Kitchens and Corridor etc...

Technical Data:

Power Source:220-240 VAC 60/50HZ

LED Type: Osram

Low tolerances for colour tempereature: MacAdam 3

Humidity Storage: %80-10

Dimmable: no (can be dimmableor DALI on request)

Size: 1000x50x80 mm



SPECIFICATIONS

MAIN SPECIFICATIONS (T=25C)

ITEM	DESCRIPTION
Input Voltage	220- 240VAC
Frequency	50/ 60 H z
LED Type	Osram
Power	20 W/M
Power supply	Tridonic/ GL /Nassli
Flux	2200 Lm/M
Mounting	Suspended / Surface
LED Efficiency	120-130 Lm/W
Materials	Aluminum, PC, Iron & Friendly material
Power factor	>95%
CCT	3000K, 4000K, 5000K 6000K
CRI	>80%
Life Time	>50,000 Hour
Operating Temperature	°20-C to °55+C
Storage Temperature	°40-C to +°85C
Certifications	CE, SELV, ISO and ROHS
Warranty	5 Years
IP Rating	IP65