



nassli
LED LIGHTS

PANEL LIGHT 112x112

Application:

I deal for Schools, Offices, universities, Malls, supermarkets, and special design for hotels and palaces. etc...

Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV.

No glare and no heat under the the fixture. Available with all mounting options (recessed, suspended, surface mounted).



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60 H z
Power factor	>98%
CCT	2700K, 3000K, 4000K, 5000k, 6000K
CRI	>80%
LED Efficiency	80-100lm/W
Power supply	Tridonic / Nassli / Philips / GL
LED Type	Osram / Bridgelux
Materials	Aluminum, PC, & Friendly material
Beam Angle	110°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	Recessed / Suspended / Surface
IP Rating	IP54
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-PL-V2-11211210-115W-XXK-SMD-NS-IP54	1120x1120x150	115	9500