



**nassli**  
LED LIGHTS

## PANEL LIGHT 30120

### Application:

It can be widely used for Schools, Offices, universities, Malls, Supermarket, and special design for hotels and palaces. etc...

### Feature:

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.

No glare and no heat under the fixture. Available with all mounting options (recessed, suspended, surface mounted)

### SPECIFICATIONS

| ITEM           | DESCRIPTION                       |
|----------------|-----------------------------------|
| Input Voltage  | 220 - 240 V A C                   |
| Frequency      | 50 / 60 H z                       |
| Power factor   | >98%                              |
| CCT            | 2700K, 3000K, 4000K, 6000K        |
| CRI            | >80%                              |
| LED Efficiency | 120-130Lm/W                       |
| Power supply   | Tridonic / Nassli / Philips / GL  |
| LED Type       | Osram / Epistar                   |
| Materials      | Aluminum, PC, & Friendly material |
| Beam Angle     | 115°                              |
| Life Time      | >50,000 Hour                      |
| Operating Temp | -20°C to +55°C                    |
| Storage Temp   | -40°C to +85°C                    |
| Certifications | CE, SELV and ISO                  |
| Mounting       | Recessed / Suspended              |
| IP Rating      | IP20 / IP 40                      |
| Dimmable       | On Request                        |
| Emergency      | On Request                        |
| Warranty       | 5 Years                           |

| Order code                          | Dimensions(mm) | Power(Watt) | Lumen |
|-------------------------------------|----------------|-------------|-------|
| NSL-PL-30120-40W-XXK-SMD-NS-IP20    | 119x29.5x9     | 40          | 4400  |
| NSL-PL-30120-40W-XXK-SMD-NS-IP40    | 119x29.5x9     | 40          | 4400  |
| NSL-PL-30120-40W-XXK-SMD-TD-XX-IP20 | 119x29.5x9     | 40          | 4400  |
| NSL-PL-30120-40W-XXK-SMD-TD-XX-IP40 | 119x29.5x9     | 40          | 4400  |



**nassli**  
LED LIGHTS

## PANEL LIGHT 30120

### Application:

It can be widely used for Schools, Offices, universities, Malls, Supermarket, and special design for hotels and palaces. etc...

### Feature:

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.

No glare and no heat under the fixture. Available with all mounting options (recessed, suspended, surface mounted)

### SPECIFICATIONS

| ITEM           | DESCRIPTION                       |
|----------------|-----------------------------------|
| Input Voltage  | 220 - 240 V A C                   |
| Frequency      | 50 / 60 H z                       |
| Power factor   | >98%                              |
| CCT            | 2700K, 3000K, 4000K, 6000K        |
| CRI            | >80%                              |
| LED Efficiency | 120-130Lm/W                       |
| Power supply   | Tridonic / Nassli / Philips / GL  |
| LED Type       | Osram / Epistar                   |
| Materials      | Aluminum, PC, & Friendly material |
| Beam Angle     | 115°                              |
| Life Time      | >50,000 Hour                      |
| Operating Temp | -20°C to +55°C                    |
| Storage Temp   | -40°C to +85°C                    |
| Certifications | CE, SELV and ISO                  |
| Mounting       | Recessed / Suspended              |
| IP Rating      | IP20 / IP 40                      |
| Dimmable       | On Request                        |
| Emergency      | On Request                        |
| Warranty       | 5 Years                           |

| Order code                          | Dimensions(mm) | Power(Watt) | Lumen |
|-------------------------------------|----------------|-------------|-------|
| NSL-PL-30120-48W-XXK-SMD-NS-IP20    | 119x29.5x9     | 48          | 5280  |
| NSL-PL-30120-48W-XXK-SMD-NS-IP40    | 119x29.5x9     | 48          | 5280  |
| NSL-PL-30120-48W-XXK-SMD-TD-XX-IP20 | 119x29.5x9     | 48          | 5280  |
| NSL-PL-30120-48W-XXK-SMD-TD-XX-IP40 | 119x29.5x9     | 48          | 5280  |





**nassli**  
LED LIGHTS

## PANEL LIGHT 30120

### Application:

It can be widely used for Schools, Offices, universities, Malls, Supermarket, and special design for hotels and palaces. etc...

### Feature:

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.

No glare and no heat under the fixture. Available with all mounting options (recessed, suspended, surface mounted)

### SPECIFICATIONS

| ITEM           | DESCRIPTION                       |
|----------------|-----------------------------------|
| Input Voltage  | 220 - 240 V A C                   |
| Frequency      | 50 / 60 H z                       |
| Power factor   | >98%                              |
| CCT            | 2700K, 3000K, 4000K, 6000K        |
| CRI            | >80%                              |
| LED Efficiency | 120-130Lm/W                       |
| Power supply   | Tridonic / Nassli / Philips / GL  |
| LED Type       | Osram / Epistar                   |
| Materials      | Aluminum, PC, & Friendly material |
| Beam Angle     | 115°                              |
| Life Time      | >50,000 Hour                      |
| Operating Temp | -20°C to +55°C                    |
| Storage Temp   | -40°C to +85°C                    |
| Certifications | CE, SELV and ISO                  |
| Mounting       | Recessed / Suspended              |
| IP Rating      | IP20 / IP 40                      |
| Dimmable       | On Request                        |
| Emergency      | On Request                        |
| Warranty       | 5 Years                           |

| Order code                          | Dimensions(mm) | Power(Watt) | Lumen |
|-------------------------------------|----------------|-------------|-------|
| NSL-PL-30120-54W-XXK-SMD-NS-IP20    | 119x29.5x9     | 54          | 5940  |
| NSL-PL-30120-54W-XXK-SMD-NS-IP40    | 119x29.5x9     | 54          | 5940  |
| NSL-PL-30120-54W-XXK-SMD-TD-XX-IP20 | 119x29.5x9     | 54          | 5940  |
| NSL-PL-30120-54W-XXK-SMD-TD-XX-IP40 | 119x29.5x9     | 54          | 5940  |