



nassli
LED LIGHTS

ANTIBACTERIAL PANEL LIGHT 6060

Application:

I deal for Hospitals and laboratuvar etc...

Feature:

This LED panel with an antibacterial and air-purifying effect is available in a size of 59.5 x 59.5 cm This is done by circulating air in the room . Many types of bacteria , viruses or fungi to be reduced. For example, dangerous hospital germs (MRSA) , H1N1 or SARS germs.



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60 H z
Power factor	>98%
CCT	2700K, 3000K, 4000K, 5000k, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power supply	Tridonic / Nassli
LED Type	Osram / Epistar
Housing	Steel sheet with electrostatic powder coating
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	Recessed / Suspended / Surface
IP Rating	IP65
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-PL-ANB-6060-36W-XXK-SMD-NS-IP65	595x595x90	36	3600
NSL-PL-ANB-6060-36W-XXK-SMD-TD-XX-IP65	595x595x90	36	3600
NSL-PL-ANB-6060-40W-XXK-SMD-NS-IP65	595x595x90	40	4000
NSL-PL-ANB-6060-42W-XXK-SMD-TD-XX-IP65	595x595x90	42	4200
NSL-PL-ANB-6060-48W-XXK-SMD-NS-IP65	595x595x90	48	4800
NSL-PL-ANB-6060-48W-XXK-SMD-TD-XX-IP65	595x595x90	48	4800