



nassli
LED LIGHTS

LED INDIRECT PANEL LIGHT

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas, Kitchens and Corridor etc...

Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV.

No glare and no heat under the the fixture. Available with all mounting options (recessed)



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60 H z
Power factor	>98%
CCT	3000K, 4000K, 5000k, 6000K
CRI	>80%
LED Efficiency	100Lm/W
Power supply	Tridonic / Nassli
LED Type	Osram/Cree
Materials	Aluminum, PC, & Friendly material
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP20
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-PL-DIND-6060-40W-XXK-SMD-NS-IP20	W600xL600xD101	40	4000
NSL-PL-DIND-6060-47W-XXK-SMD-NS-IP20	W600xL600xD101	47	4700
NSL-PL-DIND-6060-47W-XXK-SMD-TD-XX-IP20	W600xL600xD101	47	4700