



nassli
LED LIGHTS

WATERPROOF PANEL LIGHT 6060

Application:

I deal for Schools, Offices, universities, Malls, supermarkets, and special design for hotels and palaces. etc...

Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV.

No glare and no heat under the the fixture. Available with all mounting options (recessed, suspended, surface mounted).



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60 H z
Power factor	>98%
CCT	2700K, 3000K, 4000K, 5000k, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power supply	Tridonic / Nassli / Philips / GL
LED Type	Osram / Bridgelux
Materials	Steel Galvanized, PC, & Friendly material
Beam Angle	110°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	Recessed / Suspended / Surface
IP Rating	IP65
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-PL-V2-6060-54W-XXK-SMD-TD-XX-IP65	595x595x90	54	4752
NSL-PL-V2-6060-54W-XXK-SMD-NS-IP65	595x595x90	54	4752
NSL-PL-V2-6060-54W-XXK-SMD-PH-XX-IP65	595x595x90	54	4752



nassli
LED LIGHTS

WATERPROOF PANEL LIGHT 6060

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-PL-V2-6060-48W-XXK-SMD-TD-XX-IP65	595x595x90	48	4224
NSL-PL-V2-6060-48W-XXK-SMD-NS-IP65	595x595x90	48	4224
NSL-PL-V2-6060-48W-XXK-SMD-PH-XX-IP65	595x595x90	48	4224

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-PL-V2-6060-40W-XXK-SMD-TD-XX-IP65	595x595x90	40	3520
NSL-PL-V2-6060-42W-XXK-SMD-NS-IP65	595x595x90	42	3696
NSL-PL-V2-6060-40W-XXK-SMD-NS-IP65	595x595x90	40	3520

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-PL-V2-6060-36W-XXK-SMD-TD-XX-IP65	595x595x90	36	3168
NSL-PL-V2-6060-36W-XXK-SMD-NS-IP65	595x595x90	36	3168
0NSL-PL-V2-6060-30W-XXK-SMD-NS-IP65	595x595x90	30	2640