



nassli
LED LIGHTS

PANEL LIGHT 6060

Application:

It can be widely used for Schools, Offices, universities, Malls, Supermarket, and special design for hotels and palaces. etc...

Feature:

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.

No glare and no heat under the fixture. Available with all mounting options (recessed, suspended, surface mounted)

FRAME HEIGHT: 50MM



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60 H z
Power factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power supply	Tridonic / Nassli / Gruenes Licht
LED Type	Osram / Epistar
Materials	Aluminum, PC, & Friendly material
Beam Angle	115°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	Recessed / Surface / Suspended
IP Rating	IP20 / IP 40
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-PL-6060-40W-XXK-SMD-TD-XX-IP20	59.5x59.5x9	40	4800
NSL-PL-6060-40W-XXK-SMD-NS-XX-IP20	59.5x59.5x9	40	4800
NSL-PL-6060-40W-XXK-SMD-PH-XX-IP20	59.5x59.5x9	40	4800
NSL-PL-6060-40W-XXK-SMD-TD-XX-IP40	59.5x59.5x9	40	4800
NSL-PL-6060-40W-XXK-SMD-NS-XX-IP40	59.5x59.5x9	40	4800
NSL-PL-6060-40W-XXK-SMD-PH-XX-IP40	59.5x59.5x9	40	4800