



# LED TWIN SPOT LIGHT 2X7WATT

**NASSLI**  
LED LAMP

Product .: LED Downlight 7w diffuser  
NSL-SPL-MR16-50-2X7W-XX-SMD-DIFF-TD-XX-IP20

## Application

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting Room, Factories, Theater, Cinemas, Kitchens and Corridor etc...

## Technical Data:

Power Source: 220-240 VAC 50/60HZ

LED Type: Osram 2835 SMD

Low tolerances for colour temperature: MacAdam 3

Humidity Storage: 10-80%

IK Code: IK01.

Dimmable: DALI

Dimensions:  
Cut Out: 100\*190mm  
Outer Size: 110\*200mm



## SPECIFICATIONS

### MAIN SPECIFICATIONS (T=25C)

| ITEM                  | DESCRIPTION                       |
|-----------------------|-----------------------------------|
| Input Voltage         | 220-240VAC                        |
| Frequency             | 50/60 Hz                          |
| LED Type              | Osram 2835 SMD                    |
| Power                 | 7W X 2                            |
| Power supply          | Tridonic                          |
| Flux                  | 770 X 2 Lm                        |
| CRI                   | > 83%                             |
| LED Efficiency        | 110-130 Lm/W                      |
| Materials             | Aluminum, PC, & Friendly material |
| Power factor          | > 98%                             |
| CCT                   | 3000K, 4000K, 5000K 6000K         |
| Beam Angle            | 160°                              |
| Life Time             | >50,000 Hour                      |
| Operating Temperature | -20°C to +55°C                    |
| Storage Temperature   | -40°C to +85°C                    |
| Certifications        | CE, SELV and ISO                  |
| Hole Size             |                                   |
| Mounting              | Recessed                          |
| IP Rating             | IP20                              |