



NASSLI
LED LIGHTS

LED STREET LIGHT T

Application:

Ideal for collector roads, local roads, commercial and industrial complexes, driveway, open areas, public squares, parks and playgrounds, factories, airports.

Feature:

Fixture designed for harsh and hot environments.

Each LED module can be replaced separately. Overload protection, short circuit protection, and no-load protection. Aluminum heat dissipation module has a surface anodic oxidation process to make it resistant and anti-aging fixture.



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	120 - 277 VAC
Frequency	50 / 60 Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120 - 130Lm/W
Power supply	Tridonic / Nassli / Philips
LED Type	Osram / Philips
Materials	Aluminum, PC, & Friendly material
Beam Angle	143° x 67°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	With Pole
IP Rating	IP65
Dimmable	On Request
Emergency	N/A
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-STLT-30W-XXK-SMD-NS-IP65	L290 W190 H55	30	3900
NSL-STLT-50W-XXK-SMD-PH-XX-IP65	L290 W190 H55	50	6500
NSL-STLT-100W-XXK-SMD-TD-XX-IP65	L415 W235 H90	100	13000
NSL-STLT-100W-XXK-SMD-PH-XX-IP65	L415 W235 H90	100	13000
NSL-STLT-150W-XXK-SMD-TD-XX-IP65	L555 W310 H95	150	19500
NSL-STLT-150W-XXK-SMD-PH-XX-IP65	L555 W310 H95	150	19500
NSL-STLT-200W-XXK-SMD-TD-XX-IP65	L555 W310 H95	200	26000
NSL-STLT-200W-XXK-SMD-PH-XX-IP65	L555 W310 H95	200	26000