



NASSLI
LED LIGHTS

Giant street lighting device

Application:

Ideal for collector roads, local roads, commercial and industrial complexes, driveway, open areas, public squares, parks and playgrounds, factories, airports.

Feature:

Fixture designed for harsh and hot environments.

Each LED module can be replaced separately. Overload protection, short circuit protection, and no-load protection. Aluminum heat dissipation module has a surface anodic oxidation process to make it resistant and anti-aging fixture.



SPECIFICATIONS

ITEM	DESCRIPTION
Input AC Voltage	120-277 VAC
Frequency	47-63 Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6500K
CRI	>70%
LED Efficiency	174 Lm/W
Power supply	INVENTRONICS
LED Type	Philips
Materials	Aluminum, PC, & Friendly material
Beam Angle	143° x 67°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	With Pole
IP Rating	IP66
Dimmable	1...10 V On Request
Emergency	N/A
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-STLM-150W-XXK-SMD-IN-IP66	L522 W320 H140	150	21300