



NASSLI
LED LAMP

Product .: LED stretched ceiling
Item No.:NSL-SCC-40W/M-XXK-SMD-NS-IP20

Application

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting Room, Factories, Theater, Cinemas, Kitchens and Corridor etc...

Technical Data:

Power Source: 220-240 VAC 50/60HZ

LED Type: SMD Osram

Low tolerances for colour temperature: MacAdam 3

Humidity Storage: 10-80%

IK Code: IK01.

Body of glare control

Dimmable: depends on the request

Emergency: no (can be Emergency on request)

Dali: no (can be DALI on request)

Against fire
anti humidity

very light
Ease of disassembly and installation
10 years guarantee for stretch body

SPECIFICATIONS

MAIN SPECIFICATIONS (T=25C)

ITEM	DESCRIPTION
Input Voltage	220 - 240VAC
Frequency	50/60 Hz
LED Type	SMD Osram
Power	1 strip line each 10cm or 15cm
Power supply	Tridonic / Nassli / Gruenes Licht
Light fixture output lumen	110 Lm/W
CRI	>80%
LED Efficacy (Light source)	120-130 Lm/W
Materials	Aluminum, PC, & Friendly material
Power factor	>94 %
CCT	2700K.....6500K
Beam Angle	120°
Life Time	>50,000 Hour
Operating Temperature	-20°C to +55°C
Storage Temperature	-40°C to +85°C
Certifications	CE, SELV and ISO
Dimension	As per request
Mounting	Surface
IP Rating	IP20

