



Features :


- 100~264VAC input
- Protection: Short circuit/overload/over voltage
- Working temperature with 60°C
- Cooling by free air convection
- 100% full load burn-in test
- IP67 waterproof

Specification


CE RoHS BIS SELV IP67

	Model	NSL-CV-100-24-4.2A-S-IP67	
Output	DC Voltage	24V	
	Voltage Tolerance	±0.5V	
	Rated Current	0 - 4.2A	
	Rated Power	100W	
	Ripple & Noise	200mVp-p	
Input	Voltage Range	100~264VAC	
	Frequency Range	50 – 60HZ	
	Full Load Efficiency(Typ.)	85%	
	AC Current (Max.)	1.2A	
	Leakage Current	<0.75mA/260VAC	
	Inrush Current	≤ 60A	
Protection	Short Circuit	Protection type: Hiccup mode, recovers automatically after fault condition is removed.	
	Over Load	Hiccup mode, recovers automatically after fault condition is removed	
	VIBRATION	10-500Hz 2G10min	
	BURNT-IN TEST	Input voltage: 220V 50Hz rated output current 25°C Bum-in 2h	
Environment	Over Temperature	100°C±10°C shut down o/p voltage, re-poweron to recover	
	Working TEMP.	-20 ~ + 50°C	
	Working Humidity	20~60%RH,non-condensing	
	Storage TEM.,Humidity	-20~+ 85%, 10~95%RH	
	START RISE HOLD TIME	500ms, 20ms, 50ms/230VAC at full load	
Safety & EMC	Vibration	10 ~500Hz, 5G 12min./1 cycle, period for 60min.each along X,Y,Z axes.	
	Safety Standards	CE Mark	
	Withstand Voltage	I/P-O/P:1.5KVAC I/P-GND:1.5KVAC	
	EMC Immunity	EN55015:2013;EN61547:2009; EN61000-3-2:2014; EN61000-3-3:2013	
Others	Weight	0.525kg	
	Dimension	215x58x25mm (LxWxH)	
	Packing	40pcs/CTN	
Notes	1. All parameters NOT specially mentioned are measured at 230VAC input , rated load and 25°C of ambient temperature. 2. Tolerance: includes set up tolerance, line regulation and load regulation . 3. The power supply is considered as a component that will be operated in combination with final Equipment. Since EMC performance will be affected by the complete installation, the final equipment manufactures must be-qualifyEMC Directive on the complete installation again.		

Mechanical Specification



Derating Curve



Package

DIMENSION	215x58x25 (mm) (L×W×H)
CARTON QUANTITY	40PCS/Cartron
CARTON SIZE	370x300x29.5 (mm)
WEIGHT	525g/PCS