



nassli
LED LIGHTS

PANEL LIGHT SRFT1

Application:

It can be used for Hotels, Government Buildings, offices, Meeting Rooms, Residential Buildings (villas, palaces, apartments), Schools and Universities, Hospitals, Supermarkets.

Feature:

The product is used as a pure light source, using LED technology, human and environment friendly, no Pb, Hg, nor UV. High power saving fixture, no decay and color temperature shift. Can be dimmable (through direct control or via network). A motion sensor can be added.



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 VAC
Frequency	50 / 60 Hz
Power factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power supply	Nassli
LED Type	Osram / Epistar
Materials	Aluminum, PC, & Friendly material
Beam Angle	120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	Surface Mounted
IP Rating	IP20
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-SRFT1-220-20W-XXK-SMD-NS-IP20	H66 D225	20	2200
NSL-SRFT1-220-20W-XXK-SMD-DON-IP20	H66 D225	20	2200
NSL-SRFT1-220-24W-XXK-SMD-TD-XX-IP20	H66 D225	24	2640
NSL-SRFT1-220-30W-XXK-SMD-NS-IP20	H66 D225	30	3300
NSL-SRFT1-220-30W-XXK-SMD-DON-IP20	H66 D225	30	3300
NSL-SRFT1-220-30W-XXK-SMD-TD-XX-IP20	H66 D225	30	3300