



**nassli**  
LED LIGHTS

## PANEL LIGHT SRFV2

### Application:

It can be used for Hotels, Government Building, offices, Meeting Room, Residential Building (villas, palaces, apartment), School collage and University, Hospitals Super Market.

### Feature:

The product is used as a pure light source, using LED technology, human and environment friendly, no Pb, Hg nor UV.  
High power saving fixture, no decay and color temperature shift.  
Can be dimmable (through direct control or via network). A motion sensor can be added.



### SPECIFICATIONS

| ITEM           | DESCRIPTION                       |
|----------------|-----------------------------------|
| Input Voltage  | 220 - 240 VAC                     |
| Frequency      | 50 / 60 Hz                        |
| Power factor   | >98%                              |
| CCT            | 2700K, 3000K, 4000K, 6000K        |
| CRI            | >80%                              |
| LED Efficiency | 120-130Lm/W                       |
| Power supply   | Nassli                            |
| LED Type       | Osram / Epistar                   |
| Materials      | Aluminum, PC, & Friendly material |
| Beam Angle     | 120°                              |
| Life Time      | >50,000 Hour                      |
| Operating Temp | -20°C to +55°C                    |
| Storage Temp   | -40°C to +65°C                    |
| Certifications | CE, SELV and ISO                  |
| Mounting       | Surface Mounted                   |
| IP Rating      | IP20                              |
| Dimmable       | On Request                        |
| Emergency      | On Request                        |
| Warranty       | 5 Years                           |

| Order code                        | DIAMETER(mm) | Power(Watt) | Lumen |
|-----------------------------------|--------------|-------------|-------|
| NSL-SRFV2-350-30W-XXK-SMD-LF-IP20 | 350          | 30          | 3300  |