



nassli
LED LIGHTS

LED TRACK LIGHT

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas and Corridor etc.

Feature:

The most common form of track lighting still consists of straight pieces of track that are attached directly to the surface of the wall or ceiling. They come with a piece that connects to a ceiling outlet, special 90-degree pieces for making turns, couplers to join two straight pieces together, and a "dead end" to safely cap the track at its end, but there are also curved or wave track fixtures as well as ones that are suspended below the ceiling



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60 Hz
Power factor	>95%
CCT	2700k,3000k,4000k,5000k,6000k
CRI	>80%
LED Efficiency	150Lm/W
Power supply	Tridonic / Nassli
LED Type	Bridgelux
Materials	Aluminum, PC, & Friendly material
Beam Angle	Adjustable / 15° / 60°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +80°C
Certifications	CE, SELV and ISO
Mounting	Wall Mounted, Suspended
IP Rating	IP20
Dimmable	Dali, DSI, ON/OFF
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-TL-134-T3-15W-XXK-TD-XX-IP20	ø95x165	15	1500
NSL-TL-134-T3-15W-XXK-NS-IP20	ø95x165	15	1500
NSL-TL-134-T3-20W-XXK-NS-IP20	ø95x165	20	2000
NSL-TL-134-T3-25W-XXK-TD-XX-IP20	ø95x165	25	2500
NSL-TL-134-T3-25W-XXK-NS-IP20	ø95x165	25	2500
NSL-TL-134-T3-25W-XXK-PH-XX-IP20	ø95x165	25	2500
NSL-TL-134-T3-30W-XXK-TD-XX-IP20	ø95x165	30	3000
NSL-TL-134-T3-30W-XXK-NS-IP20	ø95x165	30	3000