



nassli
LED LIGHTS

LED UP&DOWN LIGHT

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas and Corridor etc.

Feature:

High cooling aluminum, make it good even for hot areas.

High lumen with small size.

Power saving: as it replace the halogen so it save around 90%

of the consumed power.

We Have different option(Wide lens, Narrow lens)

frame colors (Black / Gray / White)



SMALL : DIA:65 MM , H:260MM
LARGE : DIA:108MM, H:300 MM

SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60 H z
Power factor	>90%
CCT	3000K, 4000k, 6000k
CRI	>80%
LED Efficiency	85-95Lm/W
Power supply	Tridonic / Nassli
LED Type	Citizen / Philips
Materials	Aluminum, PC, & Friendly material
Beam Angle	30°, 45°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +80°C
Certifications	CE, SELV and ISO
Mounting	Wall Mounted
IP Rating	IP65
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-UDL-2x7W-XXK-COB-ZY-IP65	W65 L260	2x7	2x910
NSL-UDL-2x7W-XXK-SPOT-ZY-IP65	W65 L260	2x7	2x910
NSL-UDL-2x7W-XXK-SPOT-ZY-IP65	W108 L300	2x7	2x910
NSL-UDL-2x9W-XXK-SPOT-ZY-IP65	W108 L300	2x9	2x1170
NSL-UDL-2x10W-XXK-SPOT-ZY-IP65	W108 L300	2x10	2x1300
NSL-UDL-2x12W-XXK-SPOT-ZY-IP65	W108 L300	2x12	2x1560