



nassli
LED LIGHTS

LINEAR UP LIGHT

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas and Corridor etc...

Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV. Do not cause any flickering and electromagnetic interference. High power saving fixture, no decay and color temperature shift.



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60Hz
Power factor	>95%
CCT	3000K, 4000K, 5000K, 6000k,RGB
CRI	>80%
LED Efficiency	120-130Lm/W
Power supply	Nassli
LED Type	Osram / Cree
Materials	Aluminum, PC, & Friendly material
Color Fram	Silver
Beam Angle	10°, 30°, 120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE
Mounting	Ground Recessed
IP Rating	IP67
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-UPL-1000-120D-20W-XXK-SMD-NS-IP67	W65 H60 D85 L1000	20	2600
NSL-UPL-1000-120D-20W-XXK-SMD-NS-IP67	W65 H60 D85 L1000	20	2600
NSL-UPL-1000-120D-30W-XXK-SMD-NS-IP67	W65 H60 D85 L1000	30	3900
NSL-UPL-1000-120D-30W-XXK-SMD-NS-IP67	W65 H60 D85 L1000	30	3900

