



nassli
LED LIGHTS

LED WALL MOUNTED LIGHT

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas and Corridor etc...

Feature:

LED Wall Mounted Light is designed for Whether for a new building or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Wall-mounted range of LED products can be used to replace traditional wall-mounted luminaires incorporating compact fluorescent lamps. The Process of selecting, installing and maintaining is so easy it's a simple switch.



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60Hz
Power factor	>98%
CCT	3000K, 4000K, 5000K, 6000k
CRI	>80%
LED Efficiency	120-130Lm/W
Power supply	Tridonic / Philips
LED Type	Osram
Materials	Aluminum, PC, & Friendly material
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE,SELV&ISO
Mounting	Wall Mounted / Surface Mounted
IP Rating	IP65
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-WML-320-30W-XXK-SMD-TD-XX-IP65	320X230X190	30	3900
NSL-WML-320-30W-XXK-SMD-PH-XX-IP65	320X230X190	30	3900
NSL-WML-320-50W-XXK-SMD-TD-XX-IP65	320X230X190	50	6500
NSL-WML-320-50W-XXK-SMD-PH-XX-IP65	320X230X190	50	6500