



nassli
LED LIGHTS

LED LINEAR LIGHT

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas and Corridor etc...

Feature:

LED Linear Light designed for Harsh and hot environments, High lumen output. Power saving as it replace the sodium metal halide so it it save between 5% to 75%of the consumed power.Unlimited numberof on/off switching cycles, Aluminum heat dissipation module has surface anodic oxidation process to make it very resistant and ant-aging fixture.Over temperature protection, overload protection short circuit protection and no load protection



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60Hz
Power factor	>90%
CCT	3000K, 4000K, 5000K, 6000k, RGB
CRI	>80%
LED Efficiency	120-130Lm/W
Power supply	Tridonic / Nassli
LED Type	Osram
Materials	Aluminum, PC, & Friendly material
Beam Angle	155°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV, SASO
Mounting	Suspended, Surface Mounted
IP Rating	IP65
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-LWP-84-74-1274-CV-18W-XXK-SMD-TD-IP65	L100 W7.5	18	1800
NSL-LWP-84-74-1274-CV-18W-XXK-SMD-NS-IP65	L120 W7.5	18	1800
NSL-LWP-84-74-1274-CV-36W-XXK-SMD-TD-IP65	L100 W7.5	18	3600
NSL-LWP-84-74-1274-CV-36W-XXK-SMD-NS-IP65	L120 W7.5	36	3600