

CFGs OF LOOP AND CONDITIONAL STATEMENT:

<loop> -> iter(<initialize_statement> ;<condition>;<counter>) { <body> }

<initialize_statement> -> DT ID = <expression>

<condition> -> digit <cond_operator> ID | ID <cond_operator> digit | ID <cond_operator> ID

<counter> -> ID=ID+1 | ID=ID-1

<cond_operator> -> == | '<' | '<=' | '>' | '>=' | not | and | or

<conditional_statement> -> if (<condition>) { <body>} | elif (<condition>) { <body>}
| else { <body>}

<body> -> <statement> | <body> <statement>

<statement> -> <initialize_statement> <statement> | <counter> <statement> | <loop> <statement> |
<conditional_statement> <statement> | <print_statement> <statement> | <input_statement> <statement> |
null

<input_statement> -> input (ID)

<print_statement> -> print(ID) | print(digit)

<expression> -> ID <new> | digit<new>

<new> -> <arithmetic_operator> ID <new> | <arithmetic_operator> digit <new> | null

<arithmetic_operator> -> '+' | '-' | '*' | '/'

Example:

Define an iterative loop with initialization, condition, and counter

```
iter(num #i = 0; #i < 5; #i = #i + 1) {  
    # Inside the loop body  
    # Initialize a variable j  
    DT #j = #i * 2  
    # Check a condition  
    if (#j >= 5) {  
        print(#j)  
    }  
}
```

LEFT MOST DERIVATION :

<loop> -> iter(<initialize_statement> ; <condition>; <counter>) { <body> }

<initialize_statement> -> iter(num #i = <expression> ; <condition>; <counter>) { <body> }

<expression> -> iter(num #i = 0 <new> ; <condition>; <counter>) { <body> }

```

<new> -> iter( num #i = 0; <condition>; <counter> ) { <body> }
<condition> -> iter( num #i = 0; #i <cond_operator> digit ; <counter> ) { <body> }
<cond_operator> -> iter( num #i = 0; #i < digit ; <counter> ) { <body> }
<condition> -> iter( num #i = 0; #i < 5; <counter> ) { <body> }
<counter> -> iter( num #i = 0; #i < 5; #i = #i + 1){<body> }
<body> -> iter( num #i = 0; #i < 5; #i = #i + 1){<statement> }
<statement> -> iter( num #i = 0; #i < 5; #i = #i + 1){ <initialize_statement> <statement> }
<initialize_statement> -> iter( num #i = 0; #i < 5; #i = #i + 1){ num #j = <expression> <statement> }
<expression> -> iter( num #i = 0; #i < 5; #i = #i + 1){ num #j = #i <new> <statement> }
<new> -> iter( num #i = 0; #i < 5; #i = #i + 1){ num #j = #i <arithmetic_operator> digit <new> <statement> }
<arithmetic_operator> -> iter( num #i = 0; #i < 5; #i = #i + 1){ num #j = #i * 2 <statement> }
<statement>-> iter( num #i = 0; #i < 5; #i = #i + 1){ num #j = #i * 2 <conditional_statement> <statement> }
<conditional_statement> -> iter( num #i = 0; #i < 5; #i = #i + 1){ num #j = #i * 2 if ( <condition> ) { <body> }
<statement> }
<condition> -> iter( num #i = 0; #i < 5; #i = #i + 1){ num #j = #i * 2 if ( #j <cond_operator> digit ) { <body> }
<statement> }
<cond_operator> -> iter( num #i = 0; #i < 5; #i = #i + 1){ num #j = #i * 2 if ( #j >= 5 ) { <body> } <statement> }
<body> -> <cond_operator> == iter( num #i = 0; #i < 5; #i = #i + 1){ num #j = #i * 2 if ( #j >= 5 ) { <statement> }
<statement> }
<statement> -> iter( num #i = 0; #i < 5; #i = #i + 1){ num #j = #i * 2 if ( #j >= 5 ) { <print_statement>
<statement> } <statement> }
<print_statement> -> iter( num #i = 0; #i < 5; #i = #i + 1){ num #j = #i * 2 if ( #j >= 5 ) { print(#j) } }

```

RIGHT MOST DERIVATION:

```

<loop> -> iter( <initialize_statement> ; <condition>; <counter> ) { <body> }
<body> -> iter( <initialize_statement> ; <condition>; <counter> ) { <statement> }
<statement> -> iter( <initialize_statement> ; <condition>; <counter> ) { <initialize_statement> <statement> }
<statement> -> iter( <initialize_statement> ; <condition>; <counter> ) { <initialize_statement>
<conditional_statement> }
<conditional_statement> -> iter( <initialize_statement> ; <condition>; <counter> ) { <initialize_statement> if (
<condition> ) { <body> } }
<body> -> iter( <initialize_statement> ; <condition>; <counter> ) { <initialize_statement> if ( <condition> ) {
<statement> } }
<statement> -> iter( <initialize_statement> ; <condition>; <counter> ) { <initialize_statement> if (
<condition> ) { <print_statement> } }
<print_statement> -> iter( <initialize_statement> ; <condition>; <counter> ) { <initialize_statement> if (
<condition> ) { print(#j) } }
<condition> -> iter( <initialize_statement> ; <condition>; <counter> ) { <initialize_statement> if (ID
<cond_operator> 5 ) { print(#j) } }
<cond_operator> -> iter( <initialize_statement> ; <condition>; <counter> ) { <initialize_statement> if ( #j >= 5 )
{ print(#j) } }
<initialize_statement> -> iter( <initialize_statement> ; <condition>; <counter> ) { DT ID = <expression> if ( #j
>= 5 ) { print(#j) } }
<expression> -> iter( <initialize_statement> ; <condition>; <counter> ) { DT ID = ID <new> if ( #j >= 5 )
{ print(#j) } }
<new> -> iter( <initialize_statement> ; <condition>; <counter> ) { DT ID = ID <arithmetic_operator> 2 if ( #j >=
5 ) { print(#j) } }
<arithmetic_operator> -> iter( <initialize_statement> ; <condition>; <counter> ) { num #j = #i * 2 if ( #j >= 5 )
{ print(#j) } }

```

```

<counter> -> iter( <initialize_statement> ; <condition>; #i=#i+1 ) { num #j = #i * 2 if (#j >= 5 ) {print(#j)}}
<condition> -> iter( <initialize_statement> ; ID <cond_operator> 5 ; #i = #i +1 ) { num #j = #i * 2 if (#j >= 5 )
{print(#j)}}
<cond_operator> -> iter( <initialize_statement> ; #i < 5 ; #i = #i +1 ) { num #j = #i * 2 if (#j >= 5 ) {print(#j)}}
<initialize_statement> -> iter( DT ID = <expression> ; #i < 5 ; #i = #i +1 ) { num #j = #i * 2 if (#j >= 5 ) {print(#j)}}
<expression> -> iter( DT ID = 0 ; #i < 5 ; #i = #i +1 ) { num #j = #i * 2 if (#j >= 5 ) {print(#j)}}

```

Final->iter(num #i = 0 ; #i < 5 ; #i = #i +1) { num #j = #i * 2 if (#j >= 5) {print(#j)}}

CFG OF INPUT STATEMENT:

<input_statement> -> input (ID)

Example:

input(#d)

<input_statement> -> input (#d)

CFGs OF EXPRESSION:

```

<initialize_statement> -> DT ID = <expression>
<expression> -> ID <new> | digit<new>
<new> -> <arithmetic_operator> ID <new> | <arithmetic_operator> digit <new> | null
<arithmetic_operator> -> '+' | '-' | '*' | '/'

```

Example:

num #a = 4+5

LEFT DERIVATION:

```

<initialize_statement> -> DT ID = <expression>
<expression> -> num #a = digit <new>
<new> -> num #a =4 <arithmetic_operator> digit <new>
<arithmetic_operator> -> num #a =4 + 5

```

RIGHT DERIVATION:

```

<initialize_statement> -> DT ID = <expression>
<expression> -> DT ID = digit<new>
<new> -> DT ID = digit <arithmetic_operator> digit <new>
<new> -> DT ID = digit <arithmetic_operator> digit
<arithmetic_operator> -> DT ID = digit + 5

```

Final-> num #a = 4 +5

CFGs OF VARIABLE DECLARATION:

<variable_decl> -> DT # letter <letter> <digit> <underscore> | DT # letter <letter> <digit> | DT # letter <letter>
<letter> -> letter<letter> | <digit> | null
<digit> -> digit<digit> | <letter> | null
<underscore> -> _ <letter> <digit> | _ <digit> <letter>

Example:

num #abc_1d

LEFT DERIVATION:

<variable_decl> -> DT # letter <letter> <digit> <underscore>
<letter> -> num #a letter<letter> <digit> <underscore>
<letter> -> num #ab letter<letter> <digit> <underscore>
<underscore> -> num #abc _ <digit> <letter>
<digit> -> num #abc_digit<digit><letter>
<letter> -> num #abc_1 letter<letter>
<letter> -> num #abc_1d

RIGHT DERIVATION:

<variable_decl> -> DT # letter <letter> <digit> <underscore>
<underscore> -> DT # letter <letter> <digit> _ <digit> <letter>
<letter> -> D T # letter <letter> <digit> _ <digit> letter<letter>
<letter> -> D T # letter <letter> <digit> _ <digit> d
<digit> -> D T # letter <letter> <digit> _ digit<digit> d
<digit> -> D T # letter <letter> <digit> _1d
<digit> -> D T # letter <letter> _1d
<letter> -> DT # letter letter <letter>_1d
<letter> -> DT # letter letter letter <letter>_1d
<letter> -> DT #letter letter letter _1d

Final -> num #abc_1d

CFGs OF VARIABLE INITIALIZATION:

<variable_initial> -> <variable_decl> = <variable_decl> | <variable_decl> = <value>
<value> -> <sign> digit <digit> <decimal> <exponent>
<exponent> -> e <value> | E <value> | null
<sign> -> + | - | null
<decimal> -> . digit <digit> | null
<variable_decl> -> DT # letter <letter> <digit> <underscore> | DT # letter <letter> <digit> | DT # letter <letter>
<letter> -> letter<letter> | <digit> | null
<digit> -> digit<digit> | <letter> | null
<underscore> -> _ <letter> <digit> | _ <digit> <letter>

Example:

num #ab = 9.5 e -10

LEFT DERIVATION:

<variable_initial> -> <variable_decl> = <value>
 <variable_decl> -> DT # letter <letter> = <value>
 <letter> -> num # a letter<letter> = <value>
 <letter> -> num # ab = <value>
 <value> -> num # ab = 9 <decimal> <exponent>
 <decimal> -> num # ab = 9. digit <digit> <exponent>
 <decimal> -> num # ab = 9.5<exponent>
 <exponent> -> num # ab = 9.5 e <value>
 <value> -> num # ab = 9.5 e <sign> digit <digit> <decimal> <exponent>
 <sign> -> num # ab = 9.5 e – 1 <digit> <decimal> <exponent>
 <digit>-> num # ab = 9.5 e – 1 digit<digit> <decimal> <exponent>
 <digit>-> num # ab = 9.5 e – 10

RIGHT DERIVATION:

<variable_initial> -> <variable_decl> = <value>
 <value> -> <variable_decl> = <sign> digit <digit> <decimal> <exponent>
 <exponent> -> <variable_decl> = <sign> digit <digit> <decimal> e <value>
 <value> -> <variable_decl> = <sign> digit <digit> <decimal> e <sign> digit <digit>
 <digit> -> <variable_decl> = <sign> digit <digit> <decimal> e <sign>10
 <sign> -> <variable_decl> = <sign> digit <digit> <decimal> e-10
 <decimal> -> <variable_decl> = <sign> digit <digit>. digit e-10
 <digit> -> <variable_decl> = 9.5 e-10
 <variable_decl> -> DT # letter <letter> = 9.5 e-10
 <letter> -> DT # letter<letter> = 9.5 e-10
 <letter> -> DT # letter letter= 9.5 e-10

Final -> num #ab = 9.5e-10