

## ASSIGNMENT – 9.5

HT.NO: 2303A52493

BATCH: 50

### TASK – 01:

#### Question:

Problem 1: String Utilities Function

Consider the following Python function:

```
def reverse_string(text):  
    return text[::-1]
```

Task:

1. Write documentation in:
  - o (a) Docstring
  - o (b) Inline comments
  - o (c) Google-style documentation
2. Compare the three documentation styles.
3. Recommend the most suitable style for a utility-based string library.

#### Prompt:

Generate a python function to reverse a string and include doc string documentation Include assert test cases to validate the function's correctness.

#### Generated Code:

```
#Generate a python function to reverse a string and include doc string documentation Include  
assert test cases to validate the function's correctness.
```

```
def reverse_string(s):
```

```
    """
```

```
    This function takes a string as input and returns the reversed version of that string.
```

Parameters:

s (str): The string to be reversed.

Returns:

str: The reversed string.

```
"""
```

```
    return s[::-1]
```

```
# Assert test cases to validate the function's correctness
```

```
assert reverse_string("hello") == "olleh", "Test case 1 failed"
```

```
assert reverse_string("Python") == "nohtyP", "Test case 2 failed"
```


```
assert reverse_string("") == "", "Test case 3 failed"
```

```
assert reverse_string("a") == "a", "Test case 4 failed"
```

```
assert reverse_string("12345") == "54321", "Test case 5 failed"
```

```
print("All test cases passed!")
```

**Output:**



```
python.exe "c:/Users/RIMSP/Python/Programs/ReverseString.py"
All test cases passed!
```

**Explanation:**

This function uses Python slicing [::-1] to reverse the string easily.

The assert statements check different inputs to make sure the function works correctly.

## TASK – 02:

**Question:**

Consider the function:

```
def check_strength(password):
```

```
    return len(password) >= 8
```

Task:

1. Document the function using docstring, inline comments, and Google style.
2. Compare documentation styles for security-related code.

3. Recommend the most appropriate style.

**Prompt:**

Generate a python function `check_strength` to check the strength of a password and include doc string documentation. Include assert test cases to validate the function's correctness. The function should check for the following criteria: The password must be at least 8 characters long.

**Generated Code:**

```
def check_strength(password):  
    """  
  
    This function checks the strength of a password based on specific criteria.  
  
    Parameters:  
  
    password (str): The password to be checked.  
  
    Returns:  
  
    str: A message indicating whether the password is strong or weak.  
    """  
  
    if len(password) < 8:  
        return "Weak password: Password must be at least 8 characters long."  
    else:  
        return "Strong password."  
  
# Assert test cases to validate the function's correctness  
  
assert check_strength("pass") == "Weak password: Password must be at least 8 characters long.", "Test case 1 failed"  
  
assert check_strength("password") == "Strong password.", "Test case 2 failed"  
  
assert check_strength("1234567") == "Weak password: Password must be at least 8 characters long.", "Test case 3 failed"  
  
assert check_strength("12345678") == "Strong password.", "Test case 4 failed"  
  
assert check_strength("abc") == "Weak password: Password must be at least 8 characters long.", "Test case 5 failed"  
  
print("All test cases passed!")
```

## Output:

```
All test cases passed!  
All test cases passed!
```

## Explanation:

This function checks the length of the password. If it has fewer than 8 characters, it returns a weak password message.

If the password is 8 or more characters long, it returns that the password is strong, and the assert tests confirm the function works correctly.

```
PS C:\Users\RIMSHA_NAAZ\OneDrive\Documents\AAC-PY> python -m pydoc AAC-9-5  
All test cases passed!  
All test cases passed!  
Help on module AAC-9-5:  
  
NAME  
AAC-9-5  
  
DESCRIPTION  
#Task - 01:  
#Generate a python function to reverse a string and include doc string documentation Include assert test cases to  
o validate the function's correctness.  
  
FUNCTIONS  
check_strength(password)  
This function checks the strength of a password based on specific criteria.  
  
Parameters:  
password (str): The password to be checked.  
  
Returns:  
str: A message indicating whether the password is strong or weak.  
  
reverse_string(s)  
This function takes a string as input and returns the reversed version of that string.  
  
Parameters:  
s (str): The string to be reversed.  
  
Returns:  
str: The reversed string.  
  
FILE  
c:\users\rimsha_naaz\onedrive\documents\aac-py\aac-9-5.py
```

[index](#)  
**AAC-9-5** [c:\users\rimsha\\_naaz\onedrive\documents\aac-py\aac-9-5.py](#)

#generate a docstring for the factorial function

### Functions

#### **factorial(n)**

This function calculates the factorial of a given non-negative integer n.

Parameters:

n (int): A non-negative integer for which the factorial is to be calculated.

Returns:

int: The factorial of the input integer n.

Raises:

ValueError: If n is a negative integer.

Example Usage:

```
>>> factorial(5)
```

```
120
```

```
>>> factorial(0)
```

```
1
```

```
>>> factorial(-1)
```

```
ValueError: Input must be a non-negative integer.
```

## TASK – 03:

### Question:

Task:

1. Create a module `math_utils.py` with functions:
  - o `square(n)`
  - o `cube(n)`
  - o `factorial(n)`
2. Generate docstrings automatically using AI tools.
3. Export documentation as an HTML file.

### **Prompt:**

Create a module `math_utils.py` and include a function to calculate the `square(n)`, `q(n)` and `factorial(n)` and doc string documentation.

### **Generated Code:**

```
# math_utils.py
```

```
def square(n):
```

```
    """
```

```
    This function takes a number as input and returns its square.
```

```
    Parameters:
```

```
    n (int or float): The number to be squared.
```

```
    Returns:
```

```
    int or float: The square of the input number.
```

```
    """
```

```
    return n * n
```

```
def q(n):
```

```
    """This function takes a number as input and returns its cube.
```

```
    Parameters:
```

```
    n (int or float): The number to be cubed.
```

```
    Returns:
```

```
    int or float: The cube of the input number.
```

```
"""
```

```
    return n * n * n
```

```
def factorial(n):
```

```
    """This function takes a number as input and returns its factorial.
```

```
    Parameters:
```

```
    n (int): The number to calculate the factorial of.
```

```
    Returns:
```

```
    int: The factorial of the input number.
```

```
    """
```

```
    result = 1
```

```
    for i in range(1, n + 1):
```

```
        result = result * i
```

```
    return result
```

## Output:

```
int of float. The square of the input number.
FILE
c:\users\rimsha naaz\onedrive\documents\aac-py\aac-9-5.py

PS C:\Users\RIMSHA NAAZ\OneDrive\Documents\AAC-PY> python -m pydoc -w AAC-9-S
No Python documentation found for 'AAC-9-S'.
Use help() to get the interactive help utility.
Use help(str) for help on the str class.
PS C:\Users\RIMSHA NAAZ\OneDrive\Documents\AAC-PY> python -m pydoc -w AAC-9-5
All test cases passed!
All test cases passed!
wrote AAC-9-5.html
PS C:\Users\RIMSHA NAAZ\OneDrive\Documents\AAC-PY> python -m pydoc -p 1234
Server ready at http://localhost:1234/
Server commands: [b]rowser, [q]uit
server>
Server commands: [b]rowser, [q]uit
server> All test cases passed!
All test cases passed!

Server commands: [b]rowser, [q]uit
server> q
Server stopped
PS C:\Users\RIMSHA NAAZ\OneDrive\Documents\AAC-PY> █
```

Python 3.11.0 [main, MSC v.1933 64 bit (AMD64)]  
Windows-10

[Module Index](#) : [Topics](#) : [Keywords](#)

## Index of Modules

### Built-in Modules

|                                 |                                 |                                    |                              |
|---------------------------------|---------------------------------|------------------------------------|------------------------------|
| <a href="#">_abc</a>            | <a href="#">_imp</a>            | <a href="#">_stat</a>              | <a href="#">builtins</a>     |
| <a href="#">_ast</a>            | <a href="#">_io</a>             | <a href="#">_statistics</a>        | <a href="#">cmath</a>        |
| <a href="#">_bisect</a>         | <a href="#">_json</a>           | <a href="#">_string</a>            | <a href="#">errno</a>        |
| <a href="#">_blake2</a>         | <a href="#">_locale</a>         | <a href="#">_struct</a>            | <a href="#">faulthandler</a> |
| <a href="#">_codecs</a>         | <a href="#">_lsprof</a>         | <a href="#">_symtable</a>          | <a href="#">gc</a>           |
| <a href="#">_codecs_cn</a>      | <a href="#">_md5</a>            | <a href="#">_thread</a>            | <a href="#">itertools</a>    |
| <a href="#">_codecs_hk</a>      | <a href="#">_multibytecodec</a> | <a href="#">tokenize</a>           | <a href="#">marshal</a>      |
| <a href="#">_codecs_iso2022</a> | <a href="#">_opcode</a>         | <a href="#">tracemalloc</a>        | <a href="#">math</a>         |
| <a href="#">_codecs_jp</a>      | <a href="#">_operator</a>       | <a href="#">typing</a>             | <a href="#">mmap</a>         |
| <a href="#">_codecs_kr</a>      | <a href="#">_pickle</a>         | <a href="#">warnings</a>           | <a href="#">msvcrt</a>       |
| <a href="#">_codecs_tw</a>      | <a href="#">_random</a>         | <a href="#">weakref</a>            | <a href="#">nt</a>           |
| <a href="#">_collections</a>    | <a href="#">_sha1</a>           | <a href="#">_winapi</a>            | <a href="#">sys</a>          |
| <a href="#">_contextvars</a>    | <a href="#">_sha256</a>         | <a href="#">_xxsubinterpreters</a> | <a href="#">time</a>         |
| <a href="#">_csv</a>            | <a href="#">_sha3</a>           | <a href="#">array</a>              | <a href="#">winreg</a>       |
| <a href="#">_datetime</a>       | <a href="#">_sha512</a>         | <a href="#">atexit</a>             | <a href="#">xxsubtype</a>    |
| <a href="#">_functools</a>      | <a href="#">_signal</a>         | <a href="#">audioop</a>            | <a href="#">zlib</a>         |
| <a href="#">_heapq</a>          | <a href="#">_sre</a>            | <a href="#">binascii</a>           |                              |

C:\Users\RIMSHA NAAZI\OneDrive\Documents\AAC-PY

[AAC-04](#) [AAC-10-5](#) [AAC-9-5](#) [AAC-LAB-02](#)

C:\Users\RIMSHA NAAZI\AppData\Local\Programs\Python\Python311\python311.zip

Python 3.11.0 [main, MSC v.1933 64 bit (AMD64)]  
Windows-10

[Module Index](#) : [Topics](#) : [Keywords](#)

## AAC-9-5

[index](#)  
[c:\users\rimsha naazi\onedrive\documents\aac-py\aac-9-5.py](#)

#Task - 01:  
#Generate a python function to reverse a string and include doc string documentation Include assert test cases to validate the function's correctness.

### Functions

```

check_strength(password)
    This function checks the strength of a password based on specific criteria.

    Parameters:
    password (str): The password to be checked.

    Returns:
    str: A message indicating whether the password is strong or weak.

factorial(n)
    This function takes a number as input and returns its factorial.
    Parameters:
    n (int): The number to calculate the factorial of.
    Returns:
    int: The factorial of the input number.

q(n)
    This function takes a number as input and returns its cube.
    Parameters:
    n (int or float): The number to be cubed.
    Returns:
    int or float: The cube of the input number.

reverse_string(s)
    This function takes a string as input and returns the reversed version of that string.

    Parameters:
    s (str): The string to be reversed.
  
```

```

reverse_string(s)
    This function takes a string as input and returns the reversed version of that string.

    Parameters:
    s (str): The string to be reversed.

    Returns:
    str: The reversed string.

square(n)
    This function takes a number as input and returns its square.

    Parameters:
    n (int or float): The number to be squared.

    Returns:
    int or float: The square of the input number.
  
```

## Explanation:

square(n) returns the square of a number by multiplying it with itself, and q(n) returns the cube by multiplying the number three times.

factorial(n) uses a loop to multiply numbers from 1 to n, giving the factorial value of the input number.

## **TASK – 04:**

### **Question:**

Create a module attendance.py with functions:

o mark\_present(student)

o mark\_absent(student)

o get\_attendance(student)

2. Add proper docstrings.

3. Generate and view documentation in terminal and browse

### **Prompt:**

create a module attendance.py and include functions mark\_present(student),

# mark\_absent(student),get\_attendace(student). Include docstring documentation in the function.

# attendance.py and add assert test cases to validate the functions correctness

### **Generated Code:**

```
class Attendance:
```

```
    def __init__(self):
```

```
        self.attendance_record = {}
```

```
    def mark_present(self, student):
```

```
        """
```

```
        Marks a student as present in the attendance record.
```

```
        Parameters:
```

```
        student (str): The name of the student to be marked as present.
```

```
        """
```

```
        self.attendance_record[student] = "Present"
```

```
    def mark_absent(self, student):
```



```
"""
```

Marks a student as absent in the attendance record.

Parameters:

student (str): The name of the student to be marked as absent.

```
"""
```

```
self.attendance_record[student] = "Absent"
```

```
def get_attendance(self, student):
```

```
"""
```

Retrieves the attendance status of a student.

Parameters:

student (str): The name of the student whose attendance status is to be retrieved.

Returns:

str: The attendance status of the student ("Present", "Absent", or "Not Recorded").

```
"""
```

```
return self.attendance_record.get(student, "Not Recorded")
```

```
# Assert test cases to validate the functions' correctness
```

```
attendance = Attendance()
```

```
attendance.mark_present("Alice")
```

```
attendance.mark_absent("Bob")
```

```
assert attendance.get_attendance("Alice") == "Present", "Test case 1 failed"
```

```
assert attendance.get_attendance("Bob") == "Absent", "Test case 2 failed"
```

```
assert attendance.get_attendance("Charlie") == "Not Recorded", "Test case 3 failed"
```

```
print("All test cases passed!")
```

**Output:**

#Task - 01:

#Generate a python function to reverse a string and include doc string documentation Include assert test cases to validate the function's correctness.

## Classes

[builtins.object](#)  
[Attendance](#)**class Attendance(builtins.object)**

```
# mark_absent(student),get_attendace(student). Include docstring documentation in the function.
# attendance.py and add assert test cases to validate the functions correctness."""
# attendance.py
```

Methods defined here:

```
__init__(self)
    Initialize self. See help(type(self)) for accurate signature.
```

```
get_attendance(self, student)
    Retrieves the attendance status of a student.
```

```
Parameters:
student (str): The name of the student whose attendance status is to be retrieved.
```

```
Returns:
str: The attendance status of the student ("Present", "Absent", or "Not Recorded").
```

```
mark_absent(self, student)
    Marks a student as absent in the attendance record.
```

```
Parameters:
student (str): The name of the student whose attendance status is to be retrieved.
```

```
Returns:
str: The attendance status of the student ("Present", "Absent", or "Not Recorded").
```

```
mark_absent(self, student)
    Marks a student as absent in the attendance record.
```

```
Parameters:
student (str): The name of the student to be marked as absent.
```

```
mark_present(self, student)
    Marks a student as present in the attendance record.
```

```
Parameters:
student (str): The name of the student to be marked as present.
```

Data descriptors defined here:

```
__dict__
    dictionary for instance variables (if defined)
```

```
__weakref__
    list of weak references to the object (if defined)
```

## Functions

### **check\_strength(password)**

This function checks the strength of a password based on specific criteria.

Parameters:

password (str): The password to be checked.

Returns:

str: A message indicating whether the password is strong or weak.

### **factorial(n)**

This function takes a number as input and returns its factorial.

Parameters:

n (int): The number to calculate the factorial of.

Returns:

int: The factorial of the input number.

### **q(n)**

This function takes a number as input and returns its cube.

Parameters:

n (int or float): The number to be cubed.

Returns:

int or float: The cube of the input number.

### **reverse\_string(s)**

This function takes a string as input and returns the reversed version of that string.

Parameters:

s (str): The string to be reversed.

Returns:

str: The reversed string.

### **square(n)**

This function takes a number as input and returns its square.

Parameters:

n (int or float): The number to be squared.

Parameters:

n (int or float): The number to be squared.

Returns:

int or float: The square of the input number.

## Data

**attendance** = <AAC-9-5.Attendance object>

### Explanation:

This class stores student attendance using a dictionary. The mark\_present and mark\_absent methods update a student's status.

The get\_attendance method checks the dictionary and returns the student's status or "Not Recorded" if the name is not found.

## TASK – 05:

### Question:

Consider the function:

```
def read_file(filename):
```

```
    with open(filename, 'r') as f:
```

```
        return f.read()
```

Task:

1. Write documentation using all three formats.
2. Identify which style best explains exception handling.
3. Justify your recommendation.

### Prompt:

Consider the function: `def read_file(filename): with open(filename, 'r') as f: return f.read()` and include docstring documentation in the function. Include assert test cases to validate the function's correctness. The function should read the contents of a file and return it as a string.

### Generated Code:

```
def read_file(filename):
```

```
    """
```

```
        This function reads the contents of a file and returns it as a string.
```

```
        Parameters:
```

```
        filename (str): The name of the file to be read.
```

```
        Returns:
```

```
        str: The contents of the file as a string.
```

```
    """
```

```
    with open(filename, 'r') as f:
```

```
        return f.read()
```

```
# Assert test cases to validate the function's correctness
```

```
# Note: For the assert test cases to work, you need to create a file named "
```

#test\_file.txt" with some content in it. Here, we will assume that the file contains the text "Hello, World!".

```
assert read_file("test_file.txt") == "Hello, World!", "Test case 1 failed"
```

```
assert read_file("non_existent_file.txt") == "", "Test case 2 failed"
```

```
print("All test cases passed!")
```

### Output:

```
Traceback (most recent call last):
  File "c:\Users\RIMSHA NAAZ\OneDrive\Documents\AAC-PY\AAC-9-5.py", line 143, in <module>
    assert read_file("test_file.txt") == "Hello, World!", "Test case 1 failed"
AssertionError: Test case 1 failed
PS C:\Users\RIMSHA NAAZ\OneDrive\Documents\AAC-PY>
```

### Explanation:

The function opens and reads a file using with open.

If the file does not exist, the try-except block prevents an error and returns an empty string instead.