




Item	Model	Ref.Pic	Description	Above 20million UGX	Installer price (USD)	Warranty
1	EOT05S		All in one system(battery&inverter) 51.2V/5KW Rated Output Power 230V Rated Output Voltage 100A Max. DC Charge Current 5.12kWh Battery Max. PV Output Power 5500W MPPT controller+ off-grid inverter + liFePO4 battery Plug and play	4,577,000	1,280	inverter 3years battery 5years
2	EOV05B		EOT05S Battery Pack: Expand Capacity via Parallel Connection 51.2V 100Ah, 5.12kWh battery Stackable design for quick installation Standard USB interface for connecting the battery to a host computer via USB cable High-current terminals Supports up to 4 battery banks in parallel	3,082,000	860	5years
3	EOS02B-12		Wall Mount LiFePO4 12.8V/200Ah 2.56kWh Cycle life: 6000cycles at 80%DOD Max. charging voltage: 14.4V Standard charge/discharge current: 100A Max. charge/discharge current: 120A Support BMS Communication and parallel Support wifi monitoring Max. Parallel Capacity: 4pcs	1,794,000	505	5 Years
4	EOS02B-24		Wall Mount LiFePO4 25.6V/100Ah 2.56kWh Cycle life: 6000cycles at 80%DOD Max. charging voltage: 28.8V Standard charge/discharge current: 50A Max. charge/discharge current: 100A Support BMS Communication and parallel Support wifi monitoring Max. Parallel Capacity: 4pcs	1,932,000	545	5 Years
5	EOC05B-UL		Rack Mount LiFePO4 51.2V/100Ah 5.12kWh Cycle life: 6000cycles at 80%DOD Max. charging voltage: 57.6V Standard charge/discharge current: 50A Max. charge/discharge current: 100A Support BMS Communication and parallel Support wifi/BT monitoring Max. Parallel Capacity: 16pcs	3,059,000	855	5 Years
6	SE05B		Wall Mount LiFePO4 51.2V/100Ah 5.12kWh Cycle life: 6000cycles at 80%DOD Max. charging voltage: 58.4V Standard charge/discharge current: 50A Max. charge/discharge current: 100A Support BMS Communication and parallel Support wifi/BT monitoring Max. Parallel Capacity: 16pcs	3,059,000	855	5 Years
7	SE10B		Wall Mount LiFePO4 51.2V 205Ah 10.49kWh Cycle life: 6000cycles at 80%DOD Max. charging voltage: 58.4V Standard charge/discharge current: 100A Max. charge/discharge current: 200A Support BMS Communication and parallel Support wifi/BT monitoring Max. Parallel Capacity: 16pcs	5,382,000	1,495	5 Years
8	SE16B-Pro		Wall Mount LiFePO4 51.2V/314Ah 16.07kWh Cycle life: 8000cycles at 80%DOD Max. charging voltage: 58.4V Standard charge/discharge current: 150A Max. charge/discharge current: 200A Support BMS Communication, built-in breaker(240A) Support wifi/BT monitoring Max. Parallel Capacity: 16pcs	7,820,000	2,175	5 Years
9	HF1215S60-108		1.5kW/12V Single phase Solar inverter Max. Battery Charging Current 60A Max. Open Circuit Voltage: 108Vdc Max. PV array power 1000W MPPT inbuilt, voltage range: 15~90Vdc	667,000	190	2 Years
10	HF2430S60-108		3kW/24V Single phase Solar inverter Max. Battery Charging Current 60A Max. Open Circuit Voltage: 108Vdc Max. PV array power 1600W MPPT inbuilt, voltage range: 30~90Vdc	863,000	245	2 Years
11	HF2430S80-H		3.3kW/24V Single phase Solar inverter Max. Battery Charging Current 80A Max. Open Circuit Voltage: 500Vdc Max. PV array power 4000W MPPT inbuilt, voltage range: 120~500Vdc	989,000	280	2 Years

Item	Model	Ref.Pic	Description	Above 20million UGX	Installer price (USD)	Warranty
12	AFP4850S100 -H		5kW/48V Single phase, three phase inverter (Parallel) outputs Max. Battery Charging Current 100A Max. Open Circuit Voltage: 500Vdc Max. PV array power 7500W MPPT inbuilt, voltage range:60~450Vdc Parallel Capacity : 1-6pcs	1,380,000	390	2 Years
13	AEP4860S135-H		6kW/48V Solar inverter 230Vac Rated output voltage Single phase, three phase(Parallel) outputs Max. PV Charging Current: 135Ade Max. Input Short-Circuit Current: 33Ade + 33Ade Max. Input Voltage: 500Vdc+500vdc NO. of MPPT: 2 MPPT operating voltage range: 65Vdc ~ 450Vdc /65Vdc ~ 450Vdc Max. PV array power 6000W+6000W Parallel Capacity : 1-6pcs	1,920,000	515	5years
14	HYP4860S100-H		6kW/48V Single phase, three phase inverter (Parallel) outputs Max. Battery Charging Current 100A Max. Open Circuit Voltage: 550Vdc+550vdc 2 MPPT inbuilt, voltage range: 120~480Vdc Max. PV array power 4500W+4500W Parallel Capacity : 1-6pcs External Module(Standard)-WiFi	1,840,000	515	2 Years
15	ASP48100S200-H		10kW/48V Single phase, three phase inverter (Parallel) outputs Max. Battery Charging Current 200A Max. Open Circuit Voltage: 500Vdc+500Vdc 2 MPPT inbuilt, voltage range: 125~425Vdc Max. PV array power 5,500W+5,500W Parallel Capacity : 1-6pcs	3,450,000	965	2 Years
16	ASP48120S200 -H		12kW/48V Single phase, three phase inverter (Parallel) outputs Max. Battery Charging Current 200A Max. Open Circuit Voltage: 500Vdc+500Vdc 2 MPPT inbuilt, voltage range: 125~425Vdc Max. PV array power 6600W+6600W Parallel Capacity : 1-6pcs	3,680,000	1,025	2 Years
17	ASP48200SH3		20KW/48V Three phase Solar inverter 230/400Vac Battery Voltage Range: 40-60V Max. Charging/Discharging Current: 360A Max. PV Input Voltage 1000V 2 MPPT inbuilt, voltage range: 160~800Vdc Max. PV Input Power 15kW+15kW PV Input Current 36A/36A Parallel Capacity: 1-6pcs	6,670,000	1,860	2 Years
18	HESP4860S100-H		Max parallel up to 6units Grid & off-grid hybrid 6KW 48V /100A MPPT charge inverter Maximum PV open circuit voltage 500Vdc Waterproof 5years warranty	3,059,000	855	5 Years
19	太阳能板 GS600N-144M		Power:600W Cell range: 6*24(182*91mm) Size: 2278mm*1134*30mm Packing: 36pcs/pallet Pallet size: 2300*1130*1300mm Material: 2.0mm anti-reflection coating for front glass+2.0mm heat strengthened for back glass+High efficiency solar cells+EVA+Aluminium frame Junction box+MC4 cable Weight: 31.5kg	320,250	90	1 Year
20	Shiner2420		12V/24V MPPT Solar Controller 20A MaxPV voltage : 60vdc Heat sink cooling	133,000	45	3 Years
21	Shiner2430		12V/24V MPPT Solar Controller 30A MaxPV voltage : 100vdc Heat sink cooling	190,000	60	3 Years
22	BFB600		Light control+remote control Lithium iron phosphate battery: 3.2V30000mAh solar panel: 6V30W size 530 * 350 * 18MM lamp body: die cast aluminum+glass size 394 * 330 * 55MM LED light source: crystal chip 528LED (6500K)	230,000	70	2 Years
23	BS800		Light control+remote control+radar sensing Material: ABS+optical reflector solar panel: 6V 26W monocrystalline silicon solar panel Size: 510 * 335mm Lamp body size: 615 * 350 * 72mm Battery: 20AH lithium iron phosphate battery Lamp beads: 220 beads	207,000	60	2 Years
24	108306		Solarman wifi kit	128,000	45	1 Year

Item	Model	Ref.Pic	Description	Above 20million UGX	Installer price (USD)	Warranty
SRNE Promotional Model						
Item	Model	Ref.Pic	Description	Above 20million UGX	Installer price (USD)	Warranty
1	ASP48120H3		12kW/48V Solar inverter charger 230/400Vac three phase Max. Battery Charging Current 260A Num. of MPPT: 2 Max. PV Input Power: 9,000W+9,000W Max. PV Input Voltage: 800Vdc+800Vdc Parallel Capacity : 1-6 MPPT Voltage Range: 200-650Vdc	3,500,000	935	2 Years
2	HESP48120H3		12kW/48V Solar inverter charger 230/400Vac three phase 260A DC charging current Solar input volatge 800Vdc+800Vdc (two string MPPT) Max. PV array power 9,000W+9,000W Supports AC coupling Parallel Capacity : 1-6 Waterproof degree IP65 MPPT Voltage Range: 200-650Vdc	5,600,000	1,500	5 Years
3	HESP48120S200		12kW/48V Solar inverter charger 230Vac Single Phase / three phase (Parallel) 200A DC charging current Solar input volatge 500V+500v (two string MPPT) Max. PV array power 6,600W+6,600W Supports AC coupling Parallel Capacity : 1-6 Waterproof degree IP65	5,800,000	1,550	5 Years
4	Shiner2460		12V/24V MPPT Solar Controller 60A MaxPV voltage : 100V Heat sink cooling	350,000	95	3 Years
5	MF4860N15		12V/24V/36V/48V MPPT Solar Controller 60A Maximum input voltage : 145Vdc Fan cooling	480,000	128	3 Years
6	MC48100N25		12V/24V/36V/48V MPPT Solar Controller 100A MaxPV voltage : 250V Heat sink cooling	1,050,000	280	3 Years
7	MP48100N50		12V/24V/36V/48V MPPT Solar Controller 100A Maximum input voltage : 500Vdc Fan cooling	1,380,000	370	3 Years
8	DM200-W (G4) -B0		12V/24V MPPT Solar Street Light Controller 20A Max Solar input power: 260W/12V, 520W/24V	160,000	45	3 Year
9	BS200		Light control+remote control+radar sensing Material: ABS+optical reflector solar panel: 3.2V 20W monocrystalline silicon solar panel Size: 905 * 398mm Lamp body size: 910*400*91MM Battery: 60AH lithium iron phosphate battery Lamp beads: 220 beads	350,000	95	2 Years
10	BS300		Light control+remote control+radar sensing Material: ABS+optical reflector solar panel: 3.2V 30W monocrystalline silicon solar panel Size: 1165 * 398mm Lamp body size: 1170*400*91MM Battery: 75AH lithium iron phosphate battery Lamp beads: 300 beads	450,000	120	2 Years