

Kernel Pwn Cheat Sheet

- [Kernel version](#)
- [Kernel config](#)
- [Process management](#)
 - [task_struct](#)
 - [current](#)
- [Syscall](#)
- [Memory allocator](#)
 - [kmem_cache](#)
 - [__kmem_cache_create](#)
 - [kmalloc](#)
 - [kfree](#)
- [Phymem](#)
- [Paging](#)
- [Copy from/to user](#)
- [Symbol](#)
- [Snippet](#)
- [Structures](#)
 - [ldt_struct](#)
 - [shm_file_data](#)
 - [seq_operations](#)
 - [msg_msg, msg_msgseg](#)
 - [subprocess_info](#)
 - [timerfd_ctx](#)
 - [pipe_buffer](#)
 - [tty_struct](#)
 - [setxattr](#)
 - [sk_buff](#)
- [Variables](#)
 - [modprobe_path](#)
 - [core_pattern](#)
 - [poweroff_cmd](#)
 - [n_tty_ops](#)

Kernel version

```
commit 09688c0166e76ce2fb85e86b9d99be8b0084cdf9 (HEAD -> master, tag: v5.17-rc8,
origin/master, origin/HEAD)
Author: Linus Torvalds <torvalds@linux-foundation.org>
Date:   Sun Mar 13 13:23:37 2022 -0700
```

Linux 5.17-rc8

Kernel config

config	memo
CONFIG_KALLSYMS	/proc/sys/kernel/kptr_restrict

CONFIG_USERFAULTFD	/proc/sys/vm/unprivileged_userfaultfd
CONFIG_STATIC_USERMODEHELPER	
CONFIG_SLUB	default allocator
CONFIG_SLAB	
CONFIG_SLAB_FREELIST_RANDOM	
CONFIG_SLAB_FREELIST_HARDENED	
CONFIG_FG_KASLR	
CONFIG_BPF	/proc/sys/kernel/unprivileged_bpf_disabled
CONFIG_SMP	multi-processor
CONFIG_HAVE_STACKPROTECTOR	cannary
CONFIG_RANDOMIZE_BASE	kaslr
CONFIG_HARDENED_USERCOPY	prevent copying over object size

Process management

task_struct

- [task_struct](#)
 - [thread info](#)
 - syscall_work
 - [cred](#)
 - tasks
 - [init task](#)
 - [init_cred](#)
 - comm
 - prctl(PR_SET_NAME, name);

current

- [current](#)
 - [get_current](#)
 - [current task](#)
 - [DECLARE_PER_CPU](#)
 - [DECLARE_PER_CPU_SECTION](#)
 - [PCPU_ATTRS](#)
 - case CONFIG_SMP
 - [PER_CPU_BASE_SECTION](#)
 - [this_cpu_read_stable](#)
 - [__pcpu_size_call_return](#)
 - [this_cpu_read_stable_8](#)
 - [percpu_stable_op](#)

- *case CONFIG_SMP*
 - `movq %%gs:%P[var], %[val]` where
`var = ¤t_task`
- [start_kernel](#)
 - [setup_per_cpu_areas](#)
 - *case CONFIG_SMP*
 - [per_cpu_offset](#)
 - `__per_cpu_offset[cpu] = pcpu_base_addr - __per_cpu_start + pcpu_unit_offsets[cpu]`
 - [switch_to_new_gdt](#)
 - [load_percpu_segment](#)
 - [cpu_kernelmode_gs_base](#)
 - [fixed_percpu_data](#)
 - [DECLARE_PER_CPU_FIRST](#)
 - [fixed_percpu_data](#)
 - [per_cpu](#)
 - *case CONFIG_SMP*
 - [per_cpu_ptr](#)
 - [SHIFT_PERCPU_PTR](#)
 - [RELOC_HIDE](#)
 - *case CONFIG_SMP*
 - `gs = &fixed_percpu_data.gs_base + __per_cpu_offset[cpu]`

Syscall

- [entry_SYSCALL_64](#)
 - [pt_regs](#)
 - `pt_regs` may be use for stack pivoting
 - [do_syscall_64](#)
 - `add_random_kstack_offset();`
 - [syscall_enter_from_user_mode](#)
 - [__syscall_enter_from_user_work](#)
 - [syscall_trace_enter](#)
 - `SYSCALL_WORK_SECCOMP`
 - [do_syscall_x64](#)
 - [swaps_restore_regs_and_return_to_usermode](#)

Memory allocator

kmem_cache

- *case CONFIG_SLUB*
 - [kmem_cache](#)

- [kmem_cache_cpu](#)
 - freelist
 - [slab](#)
 - slab_cache
 - freelist
- offset
- random
- [kmem_cache_node](#)
- case *CONFIG_SLAB*
 - [kmem_cache](#)
 - [array_cache](#)
 - entry
 - [kmem_cache_node](#)
 - shared

__kmem_cache_create

- case *CONFIG_SLUB*
 - [__kmem_cache_create](#)
 - [kmem_cache_open](#)
 - [calculate_order](#)
 - [calculate_sizes](#)
 - [oo_make](#)
 - [order_objects](#)
- case *CONFIG_SLAB*
 - [__kmem_cache_create](#)
 - [set_objfreelist_slab_cache](#)
 - [calculate_slab_order](#)

kmalloc

- [kmalloc](#)
 - [kmalloc_index](#)
 - [__kmalloc_index](#)
 - case *CONFIG_SLUB*
 - `#define KMALLOC_MIN_SIZE 8`
 - case *CONFIG_SLAB*
 - `#define KMALLOC_MIN_SIZE 32`
 - [kmalloc_caches](#)
 - [kmalloc_type](#)
 - `#define GFP_KERNEL_ACCOUNT (GFP_KERNEL | __GFP_ACCOUNT)`
 - `GFP_KERNEL → KMALLOC_NORMAL`
 - `GFP_KERNEL_ACCOUNT → KMALLOC_CGROUP`
 - case *CONFIG_SLUB*
 - [kmem_cache_alloc_trace](#)

- [slab_alloc](#)
 - [slab_alloc_node](#)
 - [__slab_alloc](#)
 - `slab = c->slab =`
`slub_percpu_partial(c);`
 - [new_slab](#)
 - [allocate_slab](#)
 - [alloc_slab_page](#)
 - [shuffle_freelist](#)
 - [get_freepointer_safe](#)
 - [freelist_ptr](#)
- *case CONFIG_SLAB*
 - [kmem_cache_alloc_trace](#)
 - [slab_alloc](#)
 - [do_cache_alloc](#)
 - [__cache_alloc](#)
 - [cache_alloc_refill](#)
 - [__cache_alloc_node](#)
 - [cache_grow_begin](#)
 - [kmem_getpages](#)
 - [__alloc_pages_node](#)
 - [cache_init_objs](#)
 - [shuffle_freelist](#)

kfree

- *case CONFIG_SLUB*
 - [kfree](#)
 - [virt_to_folio](#)
 - [virt_to_page](#)
 - [__pa](#)
 - [__phys_addr](#)
 - [__phys_addr_nodebug](#)
 - `x - __START_KERNEL_map +`
`__START_KERNEL_map - PAGE_OFFSET`
 - `#define __PAGE_OFFSET`
`page_offset_base`
 - [pfn_to_page](#)
 - [__pfn_to_page](#)
 - [vmemmap](#)
 - [VMEMMAP_START](#)
 - `vmemmap_base`

- [page folio](#)
 - [_compound_head](#)
 - [pageflags](#)
- [folio_slab](#)
- [slab_free](#)
 - [do_slab_free](#)
 - `likely(slab == c->slab) → likely(slab == slab->slab_cache->cpu_slab->slab)`
 - [set_freepointer](#)
 - `BUG_ON(object == fp);`
 - [slab_free](#)
 - `put_cpu_partial(s, slab, 1);`
- *case CONFIG_SLAB*
 - [kfree](#)
 - [__cache_free](#)
 - [cache_flusharray](#)
 - [free_one](#)
 - `WARN_ON_ONCE(ac->avail > 0 && ac->entry[ac->avail - 1] == objp)`

Physem

- [page tables](#)
 - `page_offset_base`
 - heap base address (by `kmallocc`) and it is mapped to `/dev/mem`
 - `secondary_startup_64` can be found at `page_offset_base + offset`
 - `vmalloc_base`
 - `vmemmap_base`
 - base address of [pages](#)

Paging

- `CR3` , `Page Global Directory` , `Page Upper Directory` , `Page Middle Directory` , `Page Table Entry` are used
- each register or variable holds an encoded pointer, not a raw pointer
- the 12~51 bits of each register or variable indicates the base address of the next directory
- see [5.3.3 4-Kbyte Page Translation / AMD64 Architecture Programmer's Manual, Volume 2](#) for details
- last byte of `Page Global Directory(PML4E)` often be `0x67(0b01100111)`

Copy from/to user

- [copy from user](#)
 - [check_copy_size](#)
 - *case CONFIG_HARDENED_USERCOPY*
 - [check_object_size](#)

- [__check_object_size](#)
 - [__check_heap_object](#)
 - *case CONFIG_HARDENED_USERCOPY*
 - *case CONFIG_SLUB*
 - [__check_heap_object](#)
 - *case CONFIG_SLAB*
 - [__check_heap_object](#)
 - *otherwise*
 - [__check_heap_object](#)
 - [check_page_span](#)
 - *otherwise*
 - [check_object_size](#)
- [copy_to_user](#)

Symbol

- [EXPORT_SYMBOL](#)
 - [__EXPORT_SYMBOL](#)
 - [__EXPORT_SYMBOL](#)
 - [__cond_export_sym](#)
 - [__cond_export_sym](#)
 - [__cond_export_sym_1](#)
 - [__EXPORT_SYMBOL](#)
 - [KSYMTAB_ENTRY](#)
 - [RO_DATA](#)
- [kernel symbol value](#)
 - [offset to ptr](#)

Snippet

- gain root privileges
 - (kernel) `commit_creds(prepare_kernel_cred(NULL));`
- break out of namespaces
 - (kernel) `switch_task_namespaces(find_task_by_vpid(1), init_nsproxy);`
 - (user) `setns(open("/proc/1/ns/mnt", O_RDONLY), 0);`
 - (user) `setns(open("/proc/1/ns/pid", O_RDONLY), 0);`
 - (user) `setns(open("/proc/1/ns/net", O_RDONLY), 0);`

Structures

structure	size	flag (v5.14+)	memo
ldt_struct	16	GFP_KERNEL_ACCOUNT	
shm_file_data	32	GFP_KERNEL	

seq_operations	32	GFP_KERNEL_ACCOUNT	/proc/self/stat
msg_msg	48 ~ 4096	GFP_KERNEL_ACCOUNT	
msg_msgseg	8 ~ 4096	GFP_KERNEL_ACCOUNT	
subprocess_info	96	GFP_KERNEL	socket(22, AF_INET, 0);
timerfd_ctx	216	GFP_KERNEL	
pipe_buffer	640 = 40 x 16	GFP_KERNEL_ACCOUNT	
tty_struct	696	GFP_KERNEL	/dev/ptmx
setxattr	0 ~	GFP_KERNEL	
sk_buff	320 ~	GFP_KERNEL_ACCOUNT	

ldt_struct

- [modify_ldt](#)
 - [write_ldt](#)
 - `#define LDT_ENTRIES 8192`
 - `#define LDT_ENTRY_SIZE 8`
 - [alloc_ldt_struct](#)
 - [read_ldt](#)
 - [desc_struct](#)
 - `copy_to_user`
 - `copy_to_user` won't panic the kernel when accessing wrong address

shm_file_data

- [shmat](#)
 - [do_shmat](#)

seq_operations

- [proc_stat_init](#)
 - [stat_proc_ops](#)
- [stat_open](#)
 - [single_open_size](#)
 - [single_open](#)
- [seq_read_iter](#)
 - `m->op->start`

msg_msg, msg_msgseg

- [msg_queue](#)
 - `q_messages` → `msg_msg`
- [msgsnd](#)
 - [ksys_msgsnd](#)
 - [do_msgsnd](#)
 - [load_msg](#)

- [alloc_msg](#)
- [msgrcv](#)
 - [ksys_msgrcv](#)
 - [do_msgrcv](#)
 - `#define MSG_COPY 040000`
 - [copy_msg](#)

subprocess_info

- [socket](#)
 - [__sys_socket](#)
 - [sock_create](#)
 - [__sock_create](#)
 - [__request_module](#)
 - [call_modprobe](#)
 - [call_usermodehelper_setup](#)

timerfd_ctx

- [timerfd_create](#)
- [timerfd_release](#)
 - `kfree_rcu`

pipe_buffer

- [pipe](#), [pipe2](#)
 - [do_pipe2](#)
 - [do_pipe_flags](#)
 - [create_pipe_files](#)
 - [get_pipe_inode](#)
 - [alloc_pipe_info](#)
 - `#define PIPE_DEF_BUFFERS 16`
 - [pipefifo_fops](#)
- [pipe_write](#)
 - `buf->ops = &anon_pipe_buf_ops;`
- [pipe_release](#)
 - [put_pipe_info](#)
 - [free_pipe_info](#)
 - [pipe_buf_release](#)
 - `ops->release`

tty_struct

- [unix98_pty_init](#)
 - [tty_default_fops](#)
 - [tty_fops](#)

- [ptmx_open](#)
 - [tty_init_dev](#)
 - [alloc_tty_struct](#)
- [tty_ioctl](#)
 - [tty_paranoia_check](#)
 - `#define TTY_MAGIC 0x5401`
 - [tty_pair_get_tty](#)
 - `tty->ops->ioctl`

setxattr

- [setxattr](#)
 - [path_setxattr](#)
 - [setxattr](#)
 - `vfs_setxattr` may fail, but `kmalloc` and `kfree` complete successfully

sk_buff

- [socketpair](#)
 - [__sys_socketpair](#)
 - [sock_create](#)
 - [__sock_create](#)
 - `case PF_UNIX`
 - [unix_family_ops](#)
 - [unix_create](#)
 - `case SOCK_DGRAM`
 - [unix_dgram_ops](#)
 - [unix_create1](#)
 - `sk->sk_allocation = GFP_KERNEL_ACCOUNT;`
- [unix_dgram_sendmsg](#)
 - [sock_alloc_send_skb](#)
 - [alloc_skb_with_frags](#)
 - [alloc_skb](#)
 - [__alloc_skb](#)
 - `struct skb_shared_info` is at the end of `data`

Variables

variable	memo
<code>modprobe_path</code>	<code>/proc/sys/kernel/modprobe</code>
<code>core_pattern</code>	<code>/proc/sys/kernel/core_pattern</code>
<code>n_tty_ops</code>	(read) <code>scanf</code> , (ioctl) <code>fgets</code>

modprobe_path

- [execve](#)
 - [do_execve](#)
 - [do_execveat_common](#)
 - [bprm_execve](#)
 - [exec_binprm](#)
 - [search_binary_handler](#)
 - [__request_module](#)
 - [call_modprobe](#)
 - [call_usermodehelper_setup](#)
 - [call_usermodehelper_exec](#)

core_pattern

- [do_coredump](#)
 - [format_corename](#)
 - [call_usermodehelper_setup](#)
 - [call_usermodehelper_exec](#)

poweroff_cmd

- [orderly_poweroff](#)
 - [poweroff_work_func](#)
 - [__orderly_poweroff](#)
 - [run_cmd](#)
 - [call_usermodehelper](#)
 - [call_usermodehelper_setup](#)
 - [call_usermodehelper_exec](#)

n_tty_ops

- [tty_struct](#)
 - [tty_ldisc](#)
- [n_tty_init](#)
 - [tty_register_ldisc](#)