V8 Pwn Cheat Sheet

V8 version

```
commit d8914f7033295aa02fa72a73344e84edff87c70a (HEAD, tag: 10.5.118,
    origin/chromium/5159, origin/chromium/5158, origin/chromium/5157, origin/canary,
    origin/10.5.118)
Author: v8-ci-autoroll-builder <v8-ci-autoroll-builder@chops-service-
    accounts.iam.gserviceaccount.com>
Date: Fri Jul 1 11:01:06 2022 -0700

    Version 10.5.118

    Change-Id: I7d0574b460ea4c42ede4227d2ad3cd27f461b23b
    Reviewed-on: https://chromium-review.googlesource.com/c/v8/v8/+/3740713
    Bot-Commit: v8-ci-autoroll-builder <v8-ci-autoroll-builder@chops-service-
accounts.iam.gserviceaccount.com>
    Cr-Commit-Position: refs/heads/10.5.118@{#1}
    Cr-Branched-From: db3e14d3a231a1cf9eec888cf0a950aecf4a6d0b-
refs/heads/main@{#81497}
```

Map

- map.h, map.tq
 - descriptor-array.tq
 - PropertyDetails
 - If object has fast mode properties, PropertyDetails contains a property index
 - AccessInfoFactory::ComputeDataFieldAccessInfo
 - PropertyValue may contains Weak<Map>

Objects

- · objects.h
 - HeapObject
 - JSReceiver
 - JSObject
 - JSArray
 - JSArrayBuffer

Inline Cache and Map Transition

- IC
- FeedbackNexus
 - FeedbackVector
 - feedback-vector.tg
- GetNamedProperty

- <u>AccessorAssembler::LoadIC_BytecodeHandler</u>
 - Runtime LoadIC Miss
- <u>SetNamedProperty</u>
 - InterpreterSetNamedPropertyAssembler::SetNamedProperty
 - AccessorAssembler::StoreIC
 - Runtime StoreIC Miss
 - StorelC::Store
 - MigrateDeprecated
 - JSObject::MigrateInstance
 - JSObject::MigrateToMap
 - JSObject::MigrateFastToSlow
 - Object::SetProperty
 - Object::SetPropertyInternal
 - Object::AddDataProperty
 - Object::PrepareTransitionToDataProperty