POWERPOD

Product Catalogue

Complete range of AC EV Charging solutions from RIOD

PRODUCT CATALOGUE

Document No.	**RD027**
Date	**December 2025**
Drafted by	**RIOD India**
Website	**riod.energy**

The POWERPOD Range

POWERPOD is RIOD's range of AC EV charging stations designed for the Indian market. From affordable home chargers to commercial dual-connector stations, POWERPOD covers every AC charging need from 3.3 kW to 22 kW.

The range consists of three model families (Lite, Go, City) available in three power variants (3.3 kW, 7.4 kW, 22 kW), giving a total of nine products to cover every use case.

Which Model to Choose

POWERPOD Lite - Private Charging

Designed for home and private use. Simple, affordable, and reliable. No cloud connectivity needed. Best for homeowners, villas, and private parking where billing is not required.

POWERPOD Go - Commercial Charging

Built for commercial deployments. Features Wi-Fi connectivity, optional 4G LTE, OCPP 1.6J protocol support, and RFID authentication. Ideal for workplaces, hotels, hospitals, restaurants, malls, fleet depots, and any location that needs remote monitoring or billing.

POWERPOD City - High-Traffic Commercial

Dual-connector pedestal station for high-demand locations. Two independent charging points in one unit. Best for public parking, apartment complexes, shopping malls, and commercial parking lots where maximum throughput is needed.

Which Power Variant to Choose

Variant	Power	Charging Time (40 kWh)	Best For
3.3 kW	Single Phase, 16A	~12 hours (full charge)	Overnight home charging, low-usage private parking
7.4 kW	Single Phase, 32A	~5.5 hours (full charge)	Workplace daytime charging, hotels, hospitals, restaurants, large campuses
22 kW	Three Phase, 32A	~1.5 hours (full charge)	High-turnover parking, commercial hubs, fleet fast turnaround

Where to Deploy

Location	Recommended Model	Recommended Variant
Home / Villa	Lite	3.3 kW or 7.4 kW
Apartment (Individual)	Lite	3.3 kW or 7.4 kW
Apartment (Shared)	Go or City	7.4 kW or 22 kW
Office / Workplace	Go	7.4 kW or 22 kW
Large Campus	Go	7.4 kW
Hotel / Resort	Go	7.4 kW or 22 kW
Hospital	Go	7.4 kW
Restaurant / Cafe	Go	7.4 kW
Shopping Mall	Go or City	7.4 kW or 22 kW
Fleet Depot	Go	7.4 kW or 22 kW
Public Parking	City	7.4 kW or 22 kW
Fuel Station (City)	City	22 kW

POWERPOD Lite 3.3 kW

Compact wall-mounted AC charger for home and private use. Simple plug-and-play with RFID access control.

Specifications	
Charging Type	AC Level 1
Rating	Single Phase 3.3 kW / 16A
Voltage	230V 50Hz
Connector	16A 3-PIN Socket (with Shutter)
Protection	OV UV OC Short Circuit Surge OT Ground Fault Residual Current (IGPC5)
Energy Meter	In-built Class 1 Accuracy
Auth	RFID / Plug-and-Play
LED	Green(Charging) Yellow(Idle) Red(Error)
IP	IP65
Temp	-30 to 55C
Mounting	Wall Mount
Dims	350x230x170mm
Weight	1.64 Kg
Warranty	24 Months

POWERPOD Lite 7.4 kW

Mid-power wall-mounted AC charger for home use with Type 2 connector and 5m cable.

Specifications	
Charging Type	AC Level 2
Rating	Single Phase 7.4 kW / 32A
Voltage	230V 50Hz
Connector	Type 2 (IEC 62196) with 5m Cable
Protection	OV UV OC Short Circuit Surge OT Ground Fault Residual Current (IGPC5)
Energy Meter	In-built Class 1 Accuracy
Auth	RFID / Plug-and-Play
LED	Green(Charging) Yellow(Idle) Red(Error)
IP	IP65
Temp	-30 to 55C
Mounting	Wall Mount
Dims	350x230x170mm
Weight	3.5 Kg
Warranty	24 Months

POWERPOD Lite 22 kW

High-power three-phase AC charger for home use. Fastest home charging option with Type 2 connector.

Specifications	
Charging Type	AC Level 2
Rating	Three Phase 22 kW / 32A
Voltage	415V 50Hz
Connector	Type 2 (IEC 62196) with 5m Cable
Protection	OV UV OC Short Circuit Surge OT Ground Fault Residual Current (IGPC5)
Energy Meter	In-built Class 1 Accuracy
Auth	RFID / Plug-and-Play
LED	Green(Charging) Yellow(Idle) Red(Error)
IP	IP65
Temp	-30 to 55C
Mounting	Wall Mount
Dims	350x230x170mm
Weight	4.2 Kg
Warranty	24 Months

POWERPOD Go 3.3 kW

Entry-level commercial charger with Wi-Fi, optional 4G, and OCPP 1.6J support.

Specifications	
Charging Type	AC Level 1
Rating	Single Phase 3.3 kW / 16A
Voltage	230V 50Hz
Connector	16A 3-PIN Socket (with Shutter)
Protection	OV UV OC Short Circuit Surge OT Ground Fault Residual Current (IGPC5)
Energy Meter	In-built Class 1 Accuracy
Connectivity	Wi-Fi (Standard)
4G LTE	Optional
OCPP	OCPP 1.6J
Auth	RFID / Plug-and-Play
LED	Green(Charging) Yellow(Idle) Red(Error)
IP	IP65
Temp	-30 to 55C
Mounting	Wall Mount
Dims	350x220x110mm
Weight	1.8 Kg
Warranty	24 Months

POWERPOD Go 7.4 kW

The workhorse of commercial EV charging. Wi-Fi, OCPP 1.6J, and RFID for managed deployments.

Specifications	
Charging Type	AC Level 2
Rating	Single Phase 7.4 kW / 32A
Voltage	230V 50Hz
Connector	Type 2 (IEC 62196) with 5m Cable
Protection	OV UV OC Short Circuit Surge OT Ground Fault Residual Current (IGPC5)
Energy Meter	In-built Class 1 Accuracy
Connectivity	Wi-Fi (Standard)
4G LTE	Optional
OCPP	OCPP 1.6J
Auth	RFID / Plug-and-Play
LED	Green(Charging) Yellow(Idle) Red(Error)
IP	IP65
Temp	-30 to 55C
Mounting	Wall Mount
Dims	350x230x170mm
Weight	3.7 Kg
Warranty	24 Months

POWERPOD Go 22 kW

High-power commercial charger with three-phase support and full connectivity suite.

Specifications	
Charging Type	AC Level 2
Rating	Three Phase 22 kW / 32A
Voltage	415V 50Hz
Connector	Type 2 (IEC 62196) with 5m Cable
Protection	OV UV OC Short Circuit Surge OT Ground Fault Residual Current (IGPC5)
Energy Meter	In-built Class 1 Accuracy
Connectivity	Wi-Fi (Standard)
4G LTE	Optional
OCPP	OCPP 1.6J
Auth	RFID / Plug-and-Play
LED	Green(Charging) Yellow(Idle) Red(Error)
IP	IP65
Temp	-30 to 55C
Mounting	Wall Mount
Dims	350x230x170mm
Weight	4.5 Kg
Warranty	24 Months

POWERPOD City 3.3 kW

Dual-connector pedestal station with two 3.3 kW charging points for public/commercial use.

Specifications	
Charging Type	AC Level 1 x2
Rating	3.3 kW / 16A per connector (dual)
Voltage	230V 50Hz
Connector	16A 3-PIN x2
Protection	OV UV OC Short Circuit Surge OT Ground Fault Residual Current (IGPC5)
Energy Meter	In-built Class 1 Accuracy
Connectivity	Wi-Fi (Standard)
4G LTE	Optional
OCPP	OCPP 1.6J
Auth	RFID / Plug-and-Play
LED	Green(Charging) Yellow(Idle) Red(Error)
IP	IP65
Temp	-30 to 55C
Mounting	Standalone Pedestal
Dims	1000x250x220mm
Weight	6.5 Kg
Warranty	24 Months

POWERPOD City 7.4 kW

Dual-connector pedestal station with two 7.4 kW Type 2 charging points.

Specifications	
Charging Type	AC Level 2 x2
Rating	Single Phase 7.4 kW / 32A per connector (dual)
Voltage	230V 50Hz
Connector	Type 2 x2 with 5m Cable each
Protection	OV UV OC Short Circuit Surge OT Ground Fault Residual Current (IGPC5)
Energy Meter	In-built Class 1 Accuracy
Connectivity	Wi-Fi (Standard)
4G LTE	Optional
OCPP	OCPP 1.6J
Auth	RFID / Plug-and-Play
LED	Green(Charging) Yellow(Idle) Red(Error)
IP	IP65
Temp	-30 to 55C
Mounting	Standalone Pedestal
Dims	1000x250x220mm
Weight	8.5 Kg
Warranty	24 Months

POWERPOD City 22 kW

Dual 22 kW three-phase charging station. Maximum throughput for commercial and public parking.

Specifications	
Charging Type	AC Level 2 x2
Rating	Three Phase 22 kW / 32A per connector (dual)
Voltage	415V 50Hz
Connector	Type 2 x2 with 5m Cable each
Protection	OV UV OC Short Circuit Surge OT Ground Fault Residual Current (IGPC5)
Energy Meter	In-built Class 1 Accuracy
Connectivity	Wi-Fi (Standard)
4G LTE	Optional
OCPP	OCPP 1.6J
Auth	RFID / Plug-and-Play
LED	Green(Charging) Yellow(Idle) Red(Error)
IP	IP65
Temp	-30 to 55C
Mounting	Standalone Pedestal
Dims	1000x250x220mm
Weight	9.5 Kg
Warranty	24 Months

Contact Information	
Website	riod.energy
Email	hello@riod.in
Support	support@riodlogic.com
Phone	+91 974 600 6455

riod.energy | hello@riod.in | +91 974 600 6455