POWERPOD CITY

22 kW + 22 kW

Dual AC Fast Charger

Dual charging. Double the revenue.

COMMERCIAL CHARGING

Document No.	**RD018**
Date	**December 2025**
Drafted by	**RIOD India**
Website	**riod.energy**

POWERPOD City 22 kW is a high-power dual-connector station for high-demand deployments. Two 22 kW three-phase connectors with RFID/Plug-and-Play auth and OCPP 1.6J.

Key Features

Dual 22 kW Charging
Charge two vehicles simultaneously

Wi-Fi Connectivity
Standard Wi-Fi with optional 4G LTE

OCPP 1.6J Compliant
Industry-standard protocol support

LED Status per Connector
Independent LED strip for each connector

RFID / Plug-and-Play
Controlled or open authentication modes

Full Protection Suite
OV, UV, OC, surge, ground fault, residual current (IGPC5)

Applications

- Commercial Spaces
- Building Associations
- Restaurants
- Parking Lots

Compatible Vehicles in India

Supports all EVs with Type 2 (IEC 62196) AC charging:

Brand	Models
TATA	Nexon EV, Nexon EV Max, Tiago EV, Tigor EV, Punch EV, Curvv EV, Harrier EV
MAHINDRA	XEV 9e, BE 6, XUV400
MG MOTOR	Windsor EV, ZS EV, Comet EV
HYUNDAI	Creta Electric, Ioniq 5, Kona Electric
MARUTI SUZUKI	e-Vitara
KIA	EV6, EV9
BMW	i4, iX1
MERCEDES-BENZ	EQC, EQE, G580 EQ
AUDI	Q4 e-tron, e-tron
VOLVO	EX40, XC40 Recharge, C40 Recharge
PORSCHE	Taycan
CITROEN	eC3
BYD	Atto 3, Seal, e6
VINFAST	Limo Green
LEXUS	RZ 450e

Technical Specifications

Product Information	
Charging Type	AC Level 2 ‖ AC Level 2
Input/Output Rating	Three Phase: 22 kW / 32A ‖ 22 kW / 32A
Input/Output Voltage	Three Phase: 415 V, 50 Hz
Socket Outlet	Type 2 (IEC 62196) ‖ Type 2 (IEC 62196) with 5m Cable each
Protection	OV, UV, OC, Short Circuit, Surge, OT, Ground Fault, Residual Current (IGPC5)
Energy Meter	In-built, Class 1 Accuracy

Connectivity & Interface	
Connectivity	Wi-Fi (Standard)
4G LTE	Optional
OCPP	OCPP 1.6J
User Authentication	RFID / Plug-and-Play
Status Indications	LED Strip per connector

General Characteristics	
IP Rating	IP65
Operating Temperature	–30 °C to 55 °C
Storage Temperature	–40 °C to 70 °C
Humidity	< 95%, non-condensing
Mounting	Floor Mount / Pedestal
Dimensions (H × W × D)	1000 × 250 × 220 mm

Warranty	
Warranty Period	24 Months

For More Information

- EV Charger Selection Guide: https://riod.energy/ev-charger-selection-guide
- All Product Documents: https://riod.energy/resources
- Contact Us: hello@riod.in | +91 974 600 6455

riod.energy | hello@riod.in | +91 974 600 6455