POWERPOD EV Charger

Product Comparison Guide

Lite vs Go vs City | 3.3 kW vs 7.4 kW vs 22 kW | All 9 Variants

Complete comparison across models, power ratings, and the full product matrix.

PRODUCT COMPARISON

Document No.: **RD020**
Date: **December 2025**
Drafted by: **RIOD India**
Website: **riod.energy**

1. Model Comparison: Lite vs Go vs City

Specification	POWERPOD LITE	POWERPOD GO	POWERPOD CITY
Overview			
Segment	Private	Commercial	Commercial
Configuration	Single Connector	Single Connector	Dual Connector
Target Use	Homes, Apartments, Villas	Parking Lots, Restaurants	High-traffic Commercial
Power Options	3.3 kW / 7.4 kW / 22 kW	3.3 kW / 7.4 kW / 22 kW	2×3.3 / 2×7.4 / 2×22 kW
Connectivity & Management			
Wi-Fi	—	Standard	Standard
4G LTE	—	Optional	Optional
OCPP	—	OCPP 1.6J	OCPP 1.6J
User Interface			
Authentication	RFID / Plug-and-Play	RFID / Plug-and-Play	RFID / Plug-and-Play
Display	—	—	—
Status Indication	LED Strip	LED Strip	LED Strip per connector
Protection & Build			
Protection	Full Suite (IGPC5)	Full Suite (IGPC5)	Full Suite (IGPC5)
IP Rating	IP65	IP65	IP65
Energy Meter	In-built, Class 1	In-built, Class 1	In-built, Class 1
Physical			
Mounting	Wall Mount	Wall Mount / Pedestal	Floor Mount / Pedestal
Dimensions	350 × 230 × 170 mm	350 × 230 × 170 mm*	1000 × 250 × 220 mm
Warranty	24 Months	24 Months	24 Months
Best For			
Ideal Customer	**Homeowners wanting simple, affordable EV charging**	**Businesses deploying revenue-generating charge points**	**High-demand locations needing dual simultaneous charging**

** Go 3.3 kW dimensions: 350 × 220 × 110 mm*

2. Variant Comparison: 3.3 kW vs 7.4 kW vs 22 kW

Specification	3.3 kW	7.4 kW	22 kW
Power & Charging			
Charging Type	AC Level 1	AC Level 2	AC Level 2
Phase	Single Phase	Single Phase	Three Phase
Current	16A	32A	32A
Voltage	230 V, 50 Hz	230 V, 50 Hz	415 V, 50 Hz
Connector			
Type	16A 3-PIN Power Socket	Type 2 (IEC 62196) with 5m Cable	Type 2 (IEC 62196) with 5m Cable
Standard	Indian 3-PIN	IEC 62196	IEC 62196
Charging Time Estimate (40 kWh battery)			
0–80%	~10 hours	~4.5 hours	~1.5 hours
Overnight (8 hrs)	~26 kWh added	~59 kWh added	Full charge
Available In			
Lite (Private)	✓	✓	✓
Go (Commercial)	✓	✓	✓
City (Dual)	✓ (Dual 3.3 kW)	✓ (Dual 7.4 kW)	✓ (Dual 22 kW)
Infrastructure Requirements			
Electrical Supply	Standard 16A socket	32A dedicated circuit	Three-phase 32A supply
Wiring	Standard household	Dedicated cable run	Three-phase cabling
Installation Complexity	Low — Plug-and-play	Medium — Electrician needed	High — Professional install
Best For			
Ideal Use Case	**Overnight home charging, low daily km**	**Daily commuters, faster home/office charging**	**Fleet ops, commercial stations, rapid turnaround**

3. Complete Product Matrix: All 9 Variants

	Lite 3.3kW	Lite 7.4kW	Lite 22kW	Go 3.3kW	Go 7.4kW	Go 22kW	City 3.3kW	City 7.4kW	City 22kW
Segment & Configuration									
Segment	Private	Private	Private	Commercial	Commercial	Commercial	Commercial	Commercial	Commercial
Connectors	1	1	1	1	1	1	2	2	2
Doc No.	RD010	RD011	RD012	RD013	RD014	RD015	RD016	RD017	RD018
Power & Electrical									
Charging Type	AC Level 1	AC Level 2	AC Level 2	AC Level 1	AC Level 2	AC Level 2	AC L1‖L1	AC L2‖L2	AC L2‖L2
Rating	3.3kW/16A	7.4kW/32A	22kW/32A	3.3kW/16A	7.4kW/32A	22kW/32A	2×3.3kW	2×7.4kW	2×22kW
Voltage	1φ 230V	1φ 230V	3φ 415V	1φ 230V	1φ 230V	3φ 415V	1φ 230V	1φ 230V	3φ 415V
Connector	3-PIN	Type 2	Type 2	3-PIN	Type 2	Type 2	2×3-PIN	2×Type 2	2×Type 2
Connectivity									
Wi-Fi	—	—	—	Standard	Standard	Standard	Standard	Standard	Standard
4G LTE	—	—	—	Optional	Optional	Optional	Optional	Optional	Optional
OCPP	—	—	—	1.6J	1.6J	1.6J	1.6J	1.6J	1.6J
User Interface									
Auth	RFID/P&P	RFID/P&P	RFID/P&P	RFID/P&P	RFID/P&P	RFID/P&P	RFID/P&P	RFID/P&P	RFID/P&P
Status	LED Strip	LED Strip	LED Strip	LED Strip	LED Strip	LED Strip	LED/conn	LED/conn	LED/conn
Protection & Build									
Protection	IGPC5	IGPC5	IGPC5	IGPC5	IGPC5	IGPC5	IGPC5	IGPC5	IGPC5
IP Rating	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65
Energy Meter	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1
Physical									
Mounting	Wall	Wall	Wall	Wall/Ped	Wall	Wall	Floor/Ped	Pedestal	Floor/Ped
Dimensions	350×230×170	350×230×170	350×230×170	350×220×110	350×230×170	350×230×170	1000×250×220	1000×250×220	1000×250×220
Warranty	24 Mo	24 Mo	24 Mo	24 Mo	24 Mo	24 Mo	24 Mo	24 Mo	24 Mo