

Partner: AVPro Edge  
Models: MXNet  
Device Type: AVPro Edge MXNet



## GENERAL INFORMATION

<b>SIMPLWINDOWS NAME:</b>	AVPro Edge MXNet IRPort v2.0
<b>CATEGORY:</b>	AVPro Edge MXNet
<b>VERSION:</b>	2.0
<b>SUMMARY:</b>	<p>This module works in conjunction with the AVPro MXNet CommandProcessor v2.0 module for IR control of one Edge MXNet encoder or decoder. The full suite of AVPro MXNet modules includes:</p> <ul style="list-style-type: none"><li>• AVPro MXNet CommandProcessor v2.0</li><li>• AVPro MXNet Encoder v2.0</li><li>• AVPro MXNet Decoder v2.0</li><li>• AVPro MXNet SerialPort v2.0</li><li>• AVPro MXNet IRPort v2.0</li><li>• AVPro MXNet CEC v2.0</li><li>• AVPro MXNet DestinationRouter v2.0</li><li>• AVPro MXNet MultiDestinationRouter v2.0</li><li>• AVPro MXNet VW DecoderAssign v2.0</li><li>• AVPro MXNet VW Layout v2.0</li><li>• AVPro MXNet VW LayoutRecall v2.0</li></ul>
<b>GENERAL NOTES:</b>	<p>This module requires one instance of the AVPro MXNet CommandProcessor v2.0 module to register with and a matching instance of the AVPro MXNet Decoder v2.0 or AVPro MXNet Encoder v2.0</p>
<b>CRESTRON HARDWARE REQUIRED:</b>	4-Series processor, 3-Series processor
<b>SETUP OF CRESTRON HARDWARE:</b>	N/A
<b>VENDOR FIRMWARE:</b>	MXNet Control Box v2.28 MXNet Encoder v3.39 MXNet Decoder v4.21
<b>VENDOR SETUP:</b>	N/A

Partner: AVPro Edge  
Models: MXNet  
Device Type: AVPro Edge MXNet



## PARAMETERS:

<b>Command_Processor_ID</b>	The unique identifier of the command processor module that this module registers with.
<b>Endpoint_Type</b>	Select if this module will be associated with an encoder or decoder.
<b>Matrix_Index</b>	Specifies the unique index of the <b>Endpoint_Type</b> this module is associated with.
<b>Command_1_String..</b> <b>Command_10_String</b>	Text value of each property specifies the command to be sent by the corresponding <b>Command_X_Send</b> digital signal. IR formats Pronto and Global Cache are supported.

Partner: AVPro Edge  
Models: MXNet  
Device Type: AVPro Edge MXNet



## CONTROL:

<b>IR_TX</b>	S	Text value indicates a manual command to be sent.
<b>IR_Send</b>	D	Pulse to send the command specified by the <b>IR_TX</b> serial signal.
<b>Command_1_Send..</b> <b>Command_10_Send</b>	D	Pulse signal 1 through 10 to send the command of the corresponding <b>Command_X_String</b> property. IR formats Pronto and Global Cache are supported.



## Certified Module

Partner: AVPro Edge  
Models: MXNet  
Device Type: AVPro Edge MXNet



### FEEDBACK:

Is\_Online\_Fb

- D High to indicate that the matching endpoint is online and available for control. If the device is offline, no control will work.

Partner: AVPro Edge  
Models: MXNet  
Device Type: AVPro Edge MXNet



## TESTING:

**OPS USED FOR TESTING:** VC4 v4.0000.00007  
CP4 v2.8001.00086.01  
CP3 v1.8001.0214.01

**SIMPL WINDOWS USED FOR TESTING:** 4.2500.04

**CRES DB USED FOR TESTING:** 219.0500.001.00

**DEVICE DATABASE:** 200.27500.001.00

**SYMBOL LIBRARY USED FOR TESTING:** 1189

**SAMPLE PROGRAM:** AVPro Edge MXNet v2.0 Demo.smw

**REVISION HISTORY:**

- v1.0 – Initial Release
- v1.1 – Fixed SerialPort transmitted and received data.
  - Made updates to allow a Wallplate Encoder to initialize with this suite.
- v1.2 – Isolated serial communication queue to provide device control responsiveness.
  - Corrected unsolicited data parsing impacting hotplug detected and resolution.
- v2.0 – Added “Offline” functionality.
  - Polling will happen more frequently but will only poll for one component’s states at a time. This prevents serial control from getting backed up behind a global system poll.