

Given that

A is any language and

$$DROP\_OUT(A) = \{xz \mid xyz \in A \text{ where } x, z \in \Sigma^*, y \in \Sigma\}$$

We have to prove that class of regular languages closed under **DROP\_OUT** operation.

i.e. if A is a regular language then  $DROP\_OUT(A)$  is also regular.

We have to take that A is regular and we have to prove that  $DROP\_OUT(A)$  is regular.

Since A is a regular language, it must be recognized by a DFA.


Let  $M = (Q, \Sigma, \delta, q_0, F)$  be the DFA recognizes A.

Now we will construct an NFA  $N = (Q', \Sigma \cup \{\epsilon\}, \delta', q'_0, F')$  that we recognize  $DROP\_OUT(A)$ .

There are two copies of Machine M.

- Copy\_1: Copy 1 corresponds to the state of having 'not yet skipped a symbol'
- Copy\_2: Copy 2 corresponds to the state of having "already skipped a symbol".

(i) Proof by picture:-



$$N = (Q', \Sigma \cup \{\epsilon\}, \delta', q'_0, F')$$

•  $Q' = \{(q, b) \mid q \in Q, b \in \{0, 1\}\}$  = set of states

•  $q'_0$  = start state

$$= (q_0, 0)$$

•  $F'$  = set of final states

$$= \{(q, 1) \mid q \in F\}$$

•  $\delta'$  is given as follows:

$$\rightarrow \delta'((q, b), a) = \{\delta(q, a), b\} \forall q \in Q, b \in \{0, 1\}, a \in \Sigma$$

This means that both the copy1 and copy2 of the machine  $M$  do exactly as the original machine does on every symbol  $a$  of the alphabet

$$\rightarrow \delta'((q, 0), \epsilon) = \{(\hat{q}, 1) \mid \exists a \in \Sigma, \delta(q, a) = \hat{q}\}$$

Also at every stage, the machine has the option to skip a character. The only accepting states are in copy 2. This means, the machine cannot accept a string without skipping a character.

(ii) Formal proof:

→ The formal proof is given by induction on the length of the string.

→ An appropriate inductive hypothesis is to assume that, for any string  $w$  of length  $k$ ,

• The machine  $M$  stays in the copy -1 iff it has not yet skipped a symbol.

$$\text{i.e. } \delta'^*(q_0, 0, w) = (q_1, 0) \text{ iff } \delta^*(q_0, w) = q_1$$

• The machine  $M$  jumps to the copy-2 iff there is some symbol  $a$  that is skipped.

$$\text{i.e. } \delta'^*(q_0, 0, w) = (q_1, 1) \text{ iff } \delta^*(q_0, w_1 a w_2) = q_1.$$

So in both (i) and (ii) we constructed an NFA  $N$  that recognizes the language  $DROP\_OUT(A)$ .

Thus  $DROP\_OUT(A)$  is regular.

Hence class of regular languages closed under **DROP\_OUT** operation.