获得的答案

Rice's theorem: Let P be any nontrivial property of the language of a Turing machine.

In more formal terms, Let P be a Language consisting of Turing machine descriptions where P fulfills two conditions.

- First, P is nontrivial It contains some, but not all, TM descriptions.
- Second, P is a property of the TM's language- whenever $L(M_1) = L(M_2)$, we have $\langle M_1 \rangle \in P$ iff $\langle M_2 \rangle \in P$. Here M_1 and M_2 are any TMs.

Then we have to prove that P is an undecidable Language.

Assume that *P* is a decidable Language satisfying the Properties of Rice theorem.

Let the Turing machine T decides the language P. According to the first condition of Rice theorem, P contains some, but not all, TM descriptions.

From above properties we assume $TM_1 \& TM_2$ be the Turing machines and $\langle TM_1 \rangle \in P$ and $\langle TM_2 \rangle \not\in P$.

Now construct the Turing machine TM_3 using $TM_1 & TM_2$.

 TM_3 " on input w:

- 1. By using recursion theorem, construct our own description for $\langle TM_3 \rangle$
- 2. Run T on Turing machine $\langle TM_3 \rangle$
- 3. If T accepts $\langle TM_3 \rangle$, simulate $\langle TM_2 \rangle$ on w.

If T rejects $\langle TM_3 \rangle$, simulate $\langle TM_1 \rangle$ on w.

• Suppose $\langle TM_3 \rangle \in P$

Then T accepts $\langle TM_3 \rangle$ and $L(TM_3) = L(TM_2)$

According to second condition of Rice's theorem $\langle TM_2 \rangle \in P$ but our condition is $\langle TM_2 \rangle \not \in P$. It is a contradiction here.

• So, we will get similar contradiction if $\langle TM_3 \rangle \not\in P$.

As a result of that our assumption is wrong for P is a decidable language. Hence every property satisfying the conditions of Rice's theorem is undecidable.