From Pixels to Pronunciation: A Deep Learning System for Image Description and Speech Generation

Mehek Wagle*[1] , Rishita Mantri[2] , Prof. Avani Bhuva[3]
[1-2-3] Department of Computer Engineering, Mukesh Patel School of Technology Management and Engineering, SVKM's NMIMS University, Mumbai, Maharashtra, India
Email: mehek.wagle91@nmims.in, rishita.mantri75@nmims.in, avani.bhuva@nmims.edu

***Abstract*—This paper presents a deep learning-based image-to-speech system designed to enhance accessibility for visually impaired and elderly users. The system employs an Encoder-Decoder architecture with an integrated attention mechanism, converting visual content into spoken descriptions to allow users to "hear" visual information in real-time. InceptionV3 serves as the feature extractor, while a GRU-based decoder, guided by the attention mechanism, generates contextually relevant captions. With an accuracy of 91.4% and robust performance across evaluation metrics such as CIDEr and METEOR, the model shows high effectiveness, especially with simple images, though complex scenes and longer captions still present challenges. This project underscores the promise of assistive AI in promoting independence for visually impaired users and highlights future directions, such as multilingual support and integration across various devices, to increase its practical applications in everyday environments.**

Keywords— Image to speech, Encoder-Decoder, CIDEr, METEOR, Visually Impaired.

I. Introduction

Many older adults with visual impairments face difficulties in interacting with various forms of visual content. Lack of ability to independently read or interpret images invariably diminishes their quality of life [1]. Essentially, image-to-speech technology aims to provide considerable relief in that by translating visual information to spoken descriptions, it allows older and visually impaired people access to information with higher independence. In this research, we develop an image-to-speech production system based on deep-learning methods that improve older adults' audio-visual interaction .

Machine learning is adopted within this project in using Recurrent Neural Networks (RNNs) such as Gated Recurrent Units (GRUs) for generating a sequence of text and CNNs for feature extraction. This model has shown success in captioning the image by generating descriptive text from visual data, which is then turned into synthesized speech. Such contextually aware description generation was facilitated by attention mechanisms which allowed the model to attend to relevant parts of the input image [2].

This gives more autonomy to elderly people in providing major social benefits by reducing the dependency of such persons on others and improving their quality of life. The system can assist with daily chores, promote inclusivity, and alleviate the social divide relating to digital content which often challenges the visually impaired members in society by providing timely and accurate spoken feedback. Additionally, attention mechanisms ensure that descriptions in audio are accurate and context-sensitive, leaving the user complete with an experience when interpreting increasingly complex visual scenes.

II. Literature Review

"Image Orator-Image to Speech Using CNN, LSTM, and GTTS" relies on an image-to-speech converter for people with impaired vision. This technology combines CNNs in feature extraction with LSTMs for text captioning. The probability that the network goes through 74% after running over epochs of more than 30 values is very promising and thus it is a good form of assistive technology. However, the challenges regarding real-time captions and integration of multilingual dialects remain [3].

"Image2speech: Automatic Generation of Audio Descriptions of Images" presents a sequence-to-sequence model with attention that generates spoken descriptions directly from images, bypassing text generation. The production of audio outputs in this approach is coherent, reiterating the importance of the attention mechanism; this was precisely what was adopted in the design of our project, employing attention mechanisms for more precise outcomes [4].

"Image Text to Speech Conversion in Desired Language" gives an Android application that is intended to convert text from images to speech in languages selected by the user with OCR technologies like Tesseract and Microsoft Azure. It aligns with our objective of having a multilingual user interface for enhanced accessibility [6].

"An Efficient Approach for Text-to-Speech Conversion Using Machine Learning and Image Processing Techniques" uses MSER methods that provide 100% accuracy on text recognition.. Therefore, this study focuses on determining appropriate extraction, which will guide future research to strengthen the system's resilience for handling low contrast images [7].

"Image to Speech Conversion Using Digital Image Processing" emphasizes the usage of OCR and text-to-speech conversion to help visually impaired people with a very good accuracy across all image

formats. It validates our emphasis on the provision for various characteristics of text [5].

"Image Recognition and Voice Translation for Visually Impaired" integrates VGG16 for feature extraction and LSTM networks for caption generation. It highlights the need for optimizing caption generation accuracy, a goal shared by our project, especially in real-world settings [8].

III. Proposed Methodology

This section elaborates the process through which the deep learning-based image-to-speech system is built emphasizing more on encoding and decoding for captioning images by use of encoder-decoder architecture with support for attention mechanisms. The four major steps have been data preprocessing, the model architecture, training, and then evaluation. Data preprocessing makes sure pictures with captions are ready for efficient training. Pretrained models are applied in architecture to generate sequences and extract features. Evaluation step evaluates the capability of the model to develop an accurate as well as contextually relevant description whereas the training phase aims to optimize its performance by using techniques of supervised learning. The sections below describe each of these stages in greater detail.

A. Data Preprocessing

The dataset used for this experiment contains 8,000 images with approximately 40,000 captions. There is a corresponding number of captions for each image that describe its content, hence becoming a rich source of training data that could allow the model to learn visual features and their descriptive language. Diversification is at the core of developing a powerful image-to-speech system. Images are fed into a pre-processing pipeline made available by TensorFlow's InceptionV3 network, which is applied to resize the input to 299x299 pixels and normalize pixel values according to model-specific input standards. Then features are acquired from these images by using a pre-trained InceptionV3 model and stored for later use during training.

Caption pre-processing includes tokenization of captions and limiting the vocabulary size to 5,000 words with infrequent words replaced by an <unk> token. Each caption is enclosed by <start> and <end> tags to indicate the start and end of the sequence. To make the sequence uniform length, post-padding was added to the tokenized captions. These preprocessed image features and captions will act as train data for the model.




***Figure 1**: Top 30 Occurring Words before Tokenization*




***Figure 2**: Top 30 Occurring Words after Tokenization*

The encoder part of our architecture consists of a structure called InceptionV3 to extract features from images. It is indeed a highly capable CNN pre-trained on the ImageNet dataset. This CNN has captured rich visual details, and therefore the access to its hidden layers has yielded high-dimensional feature vectors representing the content of the image. These vectors now feed into the attention mechanism as well as the decoder to build captions for images.

To enhance the model's ability to concentrate on focused regions of the image while captioning, we incorporated an attention mechanism into the model. This enables the model to focus on the various parts of an image, thereby guiding the decoding process of the model toward the most relevant features of the context. The inclusion of an attention layer helps with the precision and relevance of generated captions, ensuring that the resultant audio output is contextually appropriate in regard to being full of detail [9].

The decoder consists of a Gated Recurrent Unit coupled with embedding layers, which jointly create text based on the features of an encoded image. GRUs are quite effective in handling sequential data compared to LSTM and are therefore suitable for modeling long-term dependencies in language [10]. Along the decoding process, the model uses image features in order to predict one word at a time for a caption, with the help of an attention context vector to maintain the focus relevant in each word. Figure 3 shows a simple architecture of the model.




Figure 3: Simple Architectural Design

B. Training Process

The training process uses preprocessed image features and their corresponding captions in a supervised learning setup to train the model. The InceptionV3 network first extracts features from the images, which then flow into the encoder to create high-dimensional feature vectors that accurately account for the visual content of each image. An GRU layer comprises the decoder and generates the entire captions one word at a time. At each

step of the caption generation, the embedded attention mechanism in the decoder is responsible for fixing the attention to the most relevant regions of the image. In doing this, the model emphasizes the most relevant visual features while predicting each word, thus making associated descriptions more accurate and context-sensitive. On the other hand, during the training phase, a process called teacher forcing is employed, whereby the decoder at each step receives the actual next word from the target caption at every time step [11]. In its core, this process trains the model on longer dependencies, especially initial training on better sentence structures. However, teacher forcing creates a gap between training and testing since the model becomes very reliant on having the correct input rather than predicting on its own from its prior outputs. Thus, during testing, this process is not used, and the decoder, instead, generates at every time step based on the outputs it has produced earlier. This allows it to realistically simulate world conditions where the reference sequence is not available.

The loss function chosen is sparse categorical cross-entropy, which measures the difference between the predicted and actual words in the captions. Attention masking is implemented to exclude the padding tokens used to hold places in the loss calculus, allowing the model to focus only on those parts of the caption that contained valid data. We adapt the use of the Adam optimizer for adaptive learning rate tuning, which accelerates the process and contributes to better convergence properties. The model was trained on 30 epochs, implying that in every epoch, it scans all images from the dataset.To safeguard model progress, checkpoints are saved periodically, enabling model restoration at optimal performance based on validation metrics.

C. Evaluation Metrics

To assess the model's effectiveness in generating accurate and contextually relevant captions, we utilize CIDEr and METEOR as our primary evaluation metrics. CIDEr (Consensus-based Image Description Evaluation) measures the similarity between generated captions and reference captions, considering consensus among multiple human references. A high CIDEr score indicates that the model-generated captions align closely with human descriptions, making it a valuable indicator of caption quality. METEOR (Metric for Evaluation of Translation with Explicit ORdering), on the other hand, evaluates caption quality based on precision, recall, and alignment with reference captions, factoring in synonymy and word ordering. This metric provides a balanced evaluation, focusing on both the fluency and adequacy of the generated captions.

The model's performance on these metrics was recorded across training epochs, revealing steady improvements as the model learned to produce more accurate and descriptive captions. The CIDEr score showed consistent growth, indicating that the captions generated by the model increasingly mirrored human annotations.

Similarly, the METEOR score demonstrated a positive trend, reflecting the model's enhanced ability to generate coherent, relevant captions that accurately describe the visual content. These results highlight the model's progressive learning during training and its effectiveness in generating descriptive audio output for visually impaired users, aligning with the research's objectives to provide accessible, high-quality spoken feedback.

D. Flowchart

The flowchart provides a high-level overview of the image-to-speech system workflow, detailing each step from image input to audio output.




Figure 4: Flowchart Image to Speech

This seamless sequence transforms visual data into accessible spoken descriptions, enhancing user independence and interaction with their environment.

IV. EXPERIMENTAL RESULTS

This section explores experimental results derivable from the image-to-speech system and is taken by its output, performance/accuracy, and evaluation metrics. It focuses on caption definition and analysis, system accuracy, and the contextual audio output effectiveness. The next few subsections articulate these results in conjunction with actual output examples, accuracy assessments compared in tabulated form, and evaluation scores using the CIDEr and METEOR metrics.

A. Output and Caption Generation

The system succeeds in generating descriptive captions for every input image, followed by its realization in an automatic speech generator as text-to-speech. The expected output for the system is contextually correct, representing salient objects in the image, and generates clear audio descriptions.






Figure 5: Output Images with Caption and Audio

Sample outputs present a system that accurately describes simpler scenes with a fair degree of accuracy by identifying pertinent information about objects and the context in which they are located. This is critical for accessibility, as it enables interpreters to have meaningful audio feedback on visual data.

B. Accuracy Assessment

Paper	COMPARISON			
	Dataset	***Sample size***	***Model Used***	***Accuracy***
[3]	Flickr 8k	8,000 images	InceptionV3	62.12%
[4]	Flick r8k, MSCOCO	8000 and 324,000	VGG16	78.8%
[5]	No predefined dataset was used	Not specified	OCR, MSER, SWT	83.61%
OUR MODEL	Flickr 8k	8000 Images	InceptionV3	91.4%

Table 1 : Model Comparison & Accuracies

The system obtains 91.4% accuracy in recognizing content in images and describing them. The above accuracy marks it out for such real-world applications as descriptive feedback for the visually impaired. Table 1 presents a comparative analysis against the existing models:

Our model outperforms prior models, largely due to the attention mechanism, which enables more precise focus on essential elements within the images, contributing to higher accuracy.

C. Evaluation Using CIDEr and METEOR Metrics

To further quantify the quality of generated captions, we evaluated the model using the CIDEr and METEOR metrics. The CIDEr metric measures how much the captions correlate with human descriptions, while METEOR aims strictly at evaluating linguistic accuracy and semantic alignment.

- **CIDEr Score:** The model had a consistent increase in CIDEr score over training epochs, reflecting greater and greater accuracy in generating captions aligned to human reference captions.
- **METEOR Score:** Same steady increase was seen with METEOR, showing better linguistic accuracy, which included appropriate word choices and syntactic structures.




Figure 5: Output Images with Caption and Audio

The graph above (Figure X) shows the progression of CIDEr and METEOR scores over the training epochs. The upward trend in both scores signifies the model's ability to enhance both contextual accuracy and linguistic quality in generated captions.

D. Loss Plot Analysis

The loss plot gives insights into the efficiency and optimization of model training across different epochs. As seen in Figure Y, the training and validation losses have been decreasing gradually, suggesting the effective learning and convergence of the model. Therefore, the gradual decline in training loss indicates that the model is honing in on the right learning pace from the data and hence minimizing errors throughout the training phase. The validation loss invariably follows the trend exhibited by the training loss, although it is slightly higher on the

baseline; this is due to the fact that there was no teacher forcing in effect during the evaluation process, thus relying on the predictions made by the model rather than at every time point being supervised by ground truth.




Figure 6: Loss Plot

The close alignment of the validation loss with that of training loss as development progressed signifies little overfitting and ensures adequate generalization of the model in unseen data. One could infer, given this trend, that the model is indeed robust, capable of generating sound captions for images outside the training testing. In conclusion, the loss plot gives the comfort that indeed the training process was a success as the model reduces errors in the training data and still retains reliability and consistency when faced with new data.

V. Limitations And Future Scope

Limitations: One major limitation of the model is that it cannot generate high-quality captions for those images which are poorly resolved or blurry. The quality of the generated caption primarily depends on the clarity of the extracted visual features, irrespective of their prominence. If the images are not clear, then the model may not be able to identify the important objects and scenes correctly. This could result in inaccurate or vague descriptions and hence reduce the usefulness of the system when applied to real-world problems. Additionally, the model is not very flexible if exposed to dissimilar images from the ones the model has experienced during training since its performance significantly depends on the diversity in the training data. While the attention mechanism allows this model to pay attention to the most informative parts of the image, its ability to handle a complex scene comprising many objects or multiple fine details is limited.

Future Scope: There are a variety of promising avenues for further growth. This might be taken further with the help of multilingual support, wherein models can provide spoken descriptions in multiple languages, making multitudes around the globe capable of accessing information. Furthermore, a simple, user-friendly interface can be developed in order to make the system easier to interact with, especially for elderly citizens who have very little or no technological background. With this interface, voice commands and easy touch-based navigation could be enabled, hence enhancing usability. For wide applicability in various contexts, such as at home and in public spaces, ensuring that people with visual impairments are consistently assisted, deployment should be extended with respect to a variety of devices: smartphones, tablets, smart glasses, and smart home assistants. Thus, such adaptability would enable real-time image-to-speech conversion, giving users more freedom, mobility, and a higher standard of living.

VI. Broader Impact and Ethical Considerations

An image-to-speech system for senior citizens and the blind or of low vision increases social benefits. Such technology provides spoken descriptions-in real time-of images, strongly enhancing the independence and quality of life of its users. More support for inclusiveness is attained because the technology enables users to better interact with their environment and reduces disability support in conducting visual tasks.

However, ethical concerns also exist in using this technology. Because it captures real-time images, which in most cases can contain sensitive information, data privacy is one of its major concerns. This data needs to be encrypted and data storage minimized to protect user privacy and unauthorized access to it. Besides, openness towards data usage maintains the knowledge of users regarding how their information is being handled. What's more, the system should be accessible to communities that don't have any access to higher technological means; for this functionality to be of any benefit to the local community, it should be accessible but quite inexpensive for the common person from different backgrounds. This may be because of low-cost hardware or by partnering up with some nonprofit organizations to reach out to those most in need of the technology. More importantly, the diversity of the training dataset is crucial since this will severely affect the accuracy of the model. By utilizing a wide variety of images, ones that represent different cultural contexts, the biases can be reduced and the accuracy of the descriptions can be increased for a wide audience of users.

The project, therefore, advances technology with moral issues addressed; hence, it avails the benefits of assistive AI equitably and makes the environment more welcoming for visually impaired people.

VII. Conclusion

This study proposes an image-to-speech system based on deep learning to provide greater accessibility for elderly and visually impaired individuals. Combining InceptionV3 with an encoder-decoder technique and attention mechanism, the model can output an audio description of an image that is both accurate and relevant. The results demonstrated that the model could grasp quite significant visual detail, although lengthening the descriptions smoothly is still difficult. Future development will further improve the usability and functionality of the system, such as multilinguality and the capability to support various device types. This paper defines the critical role that assistive technology could play in promoting visually impaired users' independence.

References

1. Cimarolli, Verena & Boerner, Kathrin & Brennan-Ing, Mark & Reinhardt, Joann & Horowitz, Amy. (2011). Challenges faced by older adults with vision loss: A qualitative study with implications for rehabilitation. Clinical rehabilitation. 26. 748-57. 10.1177/0269215511429162.
2. Ding, Songtao & Qu, Shiru & Xi, Yuling & Sangaiah, Arun & Wan, Shaohua. (2019). Image Caption Generation with High-Level Image Features. Pattern Recognition Letters. 123. 10.1016/j.patrec.2019.03.021.
3. Ayesha Jahan, Sanobar Shadan, Yasmeen Fatima, Naheed Sultana (2023) “Image Orator - Image to Speech Using CNN, LSTM and GTTS”, doi.org/10.22214/ijraset.2023.54470
4. Hasegawa-Johnson, Mark, Alan Black, Lucas Ondel, Odette Scharenborg, and Francesco Ciannella. "Image2speech: Automatically generating audio descriptions of images." Casablanca 2017 (2017)
5. Rozelle Jain and Shantanu Das, Image to Speech Conversion Using Digital Image Processing, International Journal of Advanced Research in Engineering and Technology, 9(5), 2018, pp160–169. http://iaeme.com/Home/issue/IJARET?Volume=9&Issue=5
6. P. H. S., A. Akash, B. Jaidev, G. Girish, and J. Dileep, "Image Text to Speech Conversion in Desired Language," International Journal of Creative Research Thoughts (IJCRT), vol. 11, no. 12, Available: http://www.ijcrt.org
7. Shastri, Swaroopa & Vishwakarma, Shashank. (2023). An Efficient Approach for Text-to-Speech Conversion Using Machine Learning and Image Processing Technique. International Journal of Engineering and Manufacturing. 13. 44-49. 10.5815/ijem.2023.04.05.
8. S. Pasupuleti, L. Dadi, M. Gadi, and R. Krishnaveni, "Image Recognition and Voice Translation for Visually Impaired," International Journal of Research in Engineering, Science and Management (IJRESM), vol. 4, no. 5, pp. 18, May 2021. Available: https://www.ijresm.com
9. Ahatesham Bhuiyan, Eftekhar Hossain, Mohammed Moshiul Hoque, M. Ali Akber Dewan, Enhancing image caption generation through context-aware attention mechanism, Heliyon, Volume 10, Issue 17, 2024, e36272, ISSN 2405-8440, https://doi.org/10.1016/j.heliyon.2024.e36272.
10. Nosouhian, Shiva & Nosouhian, Fereshteh & Khoshouei, Abbas. (2021). A Review of Recurrent Neural Network Architecture for Sequence Learning: Comparison between LSTM and GRU. 10.20944/preprints202107.0252.v1.
11. Tjandra, Andros & Sakti, Sakriani & Nakamura, Satoshi. (2019). End-to-End Speech Recognition Sequence Training With Reinforcement Learning. IEEE Access. PP. 1-1. 10.1109/ACCESS.2019.2922617.
12. Tiwary, T., Mahapatra, R.P. An accurate generation of image captions for blind people using extended convolutional atom neural network. Multimed Tools Appl 82, 3801–3830 (2023).
13. SS, Roshan & M, Priyadharshini & Kalinathan, Lekshmi. (2023). Image Caption Generation For Blind Users Of Social Media Websites. 10.21203/rs.3.rs-2893615/v1.
14. Srinivasagan, G., Deisher, M., & Georges, M. (2023). Compression of end-to-end non-autoregressive image-to-speech system for low-resourced devices. ArXiv.
15. N. K. Bakhsh, S. Alshomrani, and I. Khan, "A Comparative Study of Arabic Text-to-Speech Synthesis Systems," I.J. Information Engineering and Electronic Business, vol. 2014, no. 4, pp. 27-31, Aug. 2014.
16. Makav, Burak & Kilic, Volkan. (2019). A New Image Captioning Approach for Visually Impaired People. 945-949. 10.23919/ELECO47770.2019.8990630.
17. Ahatesham Bhuiyan, Eftekhar Hossain, Mohammed Moshiul Hoque, M. Ali Akber Dewan, Enhancing image caption generation through context-aware attention mechanism, Heliyon, Volume 10, Issue 17, 2024, e36272, ISSN 2405-8440,
18. Ahatesham Bhuiyan, Eftekhar Hossain, Mohammed Moshiul Hoque, M. Ali Akber Dewan, Enhancing image caption generation through context-aware attention mechanism, Heliyon, Volume 10, Issue 17, 2024, e36272, ISSN 2405-8440, https://doi.org/10.1016/j.heliyon.2024.e36272.
19. Nosouhian, Shiva & Nosouhian, Fereshteh & Khoshouei, Abbas. (2021). A Review of Recurrent Neural Network Architecture for Sequence Learning: Comparison between LSTM and GRU. 10.20944/preprints202107.0252.v1.
20. Tjandra, Andros & Sakti, Sakriani & Nakamura, Satoshi. (2019). End-to-End Speech Recognition Sequence Training With Reinforcement Learning. IEEE Access. PP. 1-1. 10.1109/ACCESS.2019.2922617.
21. Effendi, J., Sakti, S., & Nakamura, S. (2021). End-to-End Image-to-Speech Generation for Untranscribed Unknown Languages. IEEE Access, 9, 55144-55154.
22. Lahiff, N., Slocombe, K., Taglialatela, J., Dellwo, V., & Townsend, S. (2022). Degraded and computer-generated speech processing in a bonobo.
23. Guravaiah, K., Sai Bhavadeesh, Y., Shwejan, P., Vardhan, A. H., & Lavanya, S. (2023). Third Eye: Object Recognition and Speech Generation for Visually Impaired. Procedia Computer Science.