FRESCO: Fault-Tolerant, Anytime-Valid Distributed Estimation of Counterfactual Security Margins for LLM Agents

[AUTHOR NAMES AND AFFILIATIONS — INSERT AND VERIFY BEFORE SUBMISSION]

Working manuscript, 18 October 2026 — simulation results only; real-agent results pending

Abstract

Purpose. Counterfactual security margins summarise how much adversarial intervention an LLM agent tolerates before it commits an unauthorized action. Estimating them requires many stochastic, adaptively chosen agent episodes, so evaluations are run on distributed harnesses with retries, at-least-once queues and elastic workers. We study whether such execution preserves the statistical guarantees of the estimate. **Methods.** We formulate margin confirmation as anytime-valid sequential testing with betting e-processes and per-candidate error spending (LEXIS), and design FRESCO, a ledger-based distributed protocol whose six rules (seed-committed slots, prefix-predictable bets, exactly-once in-order commit, direction-aware crash imputation, a global leased error budget, and verifiable confirmation) make validity independent of scheduling. We prove validity under adaptive generation, arbitrary stopping, message loss, duplication, reordering, crashes and partitions, and show by construction that removing any single rule admits executions whose false-confirmation probability approaches one. We evaluate an implementation in a deterministic fault-injection simulator with known ground truth. **Results.** In simulation, FRESCO kept the false-confirmation probability at or below 0.018 (nominal 0.05) in every configuration, including combined faults; removing deduplication, the fresh-retry ban or in-order commit raised it to 0.083–0.133. FRESCO reached the true margin 25.4× faster with 32 workers (efficiency 0.79) at about 3.5 messages per oracle call. Two preregistered hypotheses failed: cooperation gave no detectable speed-up over independent runs with a split error budget, and LEXIS was less sample-efficient than a repaired fixed-design procedure. The fixed-design procedure as originally specified in MARGIN-Bench exceeded its nominal error (0.257). **Conclusion.** Distributed execution semantics are part of the statistics of security evaluation. FRESCO provides fault-tolerant validity at negligible coordination cost; it does not provide a cooperative or sample-efficiency advantage. Real-agent validation is specified but not yet executed.

Keywords: LLM agents; adversarial robustness; security evaluation; anytime-valid inference; e-values; distributed systems; fault tolerance; reproducibility

1 Introduction

Tool-using language-model agents read untrusted content, call services and delegate to other agents, and their security failures are *actions*: an unauthorized ledger update, a forwarded secret, a privilege change [1–3]. MARGIN-Bench [4] proposes to report not only whether an agent can be compromised but the smallest identified intervention cost at which a violation becomes reproducible—a counterfactual safety margin per attack surface. Its estimand is

$$R_{s,\alpha}(M,E) = \inf\{\, c_s(\delta) \;:\; \delta \in A_s(E),\; p_M(E,\delta) \geq \alpha \,\}, \tag{1}$$

where $p_M(E,\delta)$ is the probability that intervention δ on surface s yields a committed violation, and α a reproducibility threshold.

Estimating (1) is computationally heavy. Each candidate intervention must be executed repeatedly because agents are stochastic; candidates are generated adaptively; and a benchmark multiplies this over hundreds of scenario bundles, four attack surfaces, several budgets and models, yielding on the order of 10^7–10^8 agent episodes. Such workloads run on distributed harnesses, and the default semantics of those harnesses—at-least-once delivery, retry-on-failure with fresh randomness, results consumed as they arrive, worker-local configuration—are designed for throughput, not for statistical validity.

This paper's central observation is that *these execution semantics are part of the statistics.* A sequential test that consumes a duplicated result, a retried episode whose first attempt crashed because it was long, or results ordered by latency is no longer testing the hypothesis it reports. We show that each such default can drive the probability of falsely confirming a vulnerability far above its nominal level, and we design a protocol under which it cannot.

Contributions.

C1 **Schedule-oblivious validity.** We formulate margin confirmation as anytime-valid testing with betting e-processes and registration-time error spending (LEXIS) and prove that the reported margin is a $(1-\varepsilon)$ upper confidence bound on (1) for any generator, allocation, stopping rule and execution order, provided evidence is consumed by slot index (Theorem 1). Validity is thereby decoupled from scheduling: any scheduler is safe.

C2 **FRESCO protocol.** A ledger-based protocol with six rules that realises the conditions of C1 under message loss, duplication, reordering, crash-stop failures and partitions (Theorem 5), with a necessity result: removing any single rule admits executions whose false-confirmation probability approaches one (Theorem 6).

C3 **Two-sided reporting.** Anytime-valid cost-level certificates that bound the attack generator's violating mass at searched budgets without claiming a lower bound on the margin itself (Propositions 2–3).

C4 **Implementation and evaluation.** A tested implementation, a deterministic fault-injection simulator, and a preregistered synthetic evaluation including two negative results (no cooperative speed-up; lower sample efficiency than a repaired fixed design).

C5 **Audit of the baseline estimator.** The confirmation procedure specified in MARGIN-Bench lacks a correction across budget levels and exceeds its nominal error by a factor of five; we give and evaluate a repair.

Non-claims. We do not claim a certified lower bound on the margin, a speed-up from cooperation, better sample efficiency than well-designed fixed procedures, validity when episodes share hidden state, or any finding about real agents: all empirical results are synthetic, with real-agent experiments specified in Section 9.5 and not yet executed.

2 Research problem

Let a scenario E, surface s and defender M be fixed. An adaptive generator proposes candidates $\delta_1, \delta_2, \ldots$ with integer costs $c(\delta_j) \in \{1, \ldots, K\}$. Executing candidate j with randomness key u yields $Y(\delta_j, u) \in \{0, 1\}$, the committed-violation label of a permission-grounded oracle. The evaluator wants to report $\hat{b}$, the smallest cost at which some candidate is *confirmed* to satisfy $p(\delta) \geq \alpha$, such that

$$\Pr(R_{s,\alpha} > \hat{b}) \leq \varepsilon, \tag{2}$$

while executing episodes on W unreliable workers. The research question, posed as a falsifiable hypothesis rather than assumed, is: *Can distributed workers discover and confirm low-cost violations faster than a single process while preserving* (2) *under realistic faults, and does cooperation among them yield an advantage beyond parallelism?*

3 Related work and novelty analysis

Anytime-valid inference. Test supermartingales, Ville's inequality and e-values provide inference valid under optional stopping [5–7]; betting confidence sequences [8, 9] and always-valid A/B testing [10] are mature, as are e-value multiple testing and online variants [11–13]. Group-sequential designs handle delayed responses [14]. These methods assume a well-defined observation sequence; they do not address how a fault-prone distributed executor produces that sequence. Our contribution is not a new test but the identification of executor semantics that preserve or destroy the supermartingale property, with proofs and counterexamples.

Threshold and infinitely-armed bandits. Good-arm identification [15], thresholding bandits [16] and infinitely-armed pure exploration [17, 18] study finding arms above a threshold with bounded error; distributed exploration [19] and asynchronous successive halving [20] parallelise search. None targets the lexicographic *cheapest-level* objective with per-level non-discovery certificates, and parallel systems optimise throughput rather than error control under faulty delivery. Our matching lower bound uses the change-of-measure argument of [21].

Statistical assurance in testing. Residual-risk estimation in fuzzing [22, 23], statistical model checking [24, 25] and scenario optimisation [26] bound what was not found; recent LLM-evaluation work stresses error bars [27] and evidential limits of red teaming [28]. Our certificates are cost-indexed and anytime-valid but, as our experiments show, coarse at realistic budgets. Parallel fuzzing schedulers [29] remove redundancy for deterministic oracles; for stochastic confirmation, redundancy is a correctness issue.

Distributed systems. We reuse leases [30], escrow [31], monotone state and coordination-freedom [32, 33], causal ordering and snapshots [34, 35], and list-scheduling bounds [36]. The closest systems analogue is differential-privacy budget scheduling [37], which treats a non-replenishable statistical budget as a cluster resource; FRESCO's budget is a testing error budget spent at registration, validated by Ville and a union bound, and enforced alongside result deduplication and ordering, which DP budgeting does not need.

LLM agent security. Benchmarks cover indirect injection, tool use, long-horizon and multi-agent attacks [2, 3, 38–41]; counterfactual and causal analyses separate permission from apparent risk [42, 43]; defences enforce capabilities and provenance [44, 45]; best-of-N sampling shows that attack success grows with repeated stochastic trials [46], which is exactly why confirmation must be statistical. Authorization consistency across agents [47–49] is related but orthogonal: we evaluate agents, not authorization infrastructure.

4 Research questions and hypotheses

- **RQ1 (validity).** Does FRESCO keep false confirmation $\leq \varepsilon$ under faults, and do executor defaults break it? (H-valid-sim, H-rules, H-alg1)
- **RQ2 (scalability).** How does time-to-margin scale with workers, and what does coordination cost? (H-speed, H-overhead, H-recover)

Table 1: Novelty positioning: what is reused and what is new.

Component	Established	New here
Per-candidate e-process	betting e-processes, Ville [5, 8]	estimand is a lexicographic minimum over adaptively generated candidates; bets restricted to the committed prefix
Error spending	α-investing, weighted Bonferroni [13, 50]	spending at registration from ledger leases with a polynomial schedule that never exhausts
Seed-committed in-order slots	deterministic replay; in-order commit	proved to make validity independent of execution order and latency (Thm. 1(iii))
Crash imputation	worst-case imputation	direction-aware rule conservative for both confirmation and certification
Leased global budget	leases, escrow, DP budgets [30, 31, 37]	testing-error budget with incarnation fencing; necessity shown by counterexample
Necessity results	—	each executor default (duplicates, fresh retry, arrival order, local budget) breaks validity, some with error $\to 1$

- **RQ3 (cooperation).** Does a shared ledger beat independent runs and a centralized scheduler? (H-coop)
- **RQ4 (efficiency and certificates).** Is LEXIS at least as sample-efficient as a fixed design, and are certificates calibrated? (H-vs-Alg1, H-cert)

Decision criteria were fixed before the full runs (after a 3-seed pilot used only for sizing) and are listed with verdicts in Table 4.

5 Framework and model

Nodes and trust. A logically single, linearizable *ledger* holds all authoritative state; *workers* (honest, crash-stop, elastic) run generators and request slots; *executors* run one sandboxed agent episode per slot from an immutable snapshot and evaluate the oracle. The generator is untrusted with respect to the statistics: it may exploit any leakage, sees only committed outcomes, and never sees a slot's key before the slot is registered and leased. The network may delay, reorder, duplicate and drop messages and partition. Byzantine workers are out of scope: workers belong to the evaluator.

Assumption 1 (Fresh-key conditional Bernoulli)**.** *Slot (j,k) uses a key $u_{j,k}$; keys are i.i.d. and independent of the generator's randomness, and $Y_{j,k} = Y(\delta_j, u_{j,k})$. Executions share no hidden state.*

Assumption 2 (Registration before revelation)**.** *No party learns $u_{j,\cdot}$ before candidate j is registered with its error weight fixed.*

Assumption 3 (Crash independence)**.** *Whether slot (j,k) crashes may depend on its own key and trajectory and on infrastructure noise independent of all other keys. (Not needed in replay mode.)*

Assumption 4 (Oracle correctness)**.** *Y is the true committed-violation label; with false-positive rate ω all guarantees hold for $p + \omega(1-p)$.*

Under drift, all results hold for the null "$p_{j,k} \le \alpha$ at every slot"; a confirmation then means the violation probability exceeded α at some time during the run.

Targets. (G1) $\Pr(R > \hat{b}) \le \varepsilon$, implied by the no-false-witness property $\Pr(\exists j \text{ confirmed} : p(\delta_j) \le \alpha) \le \varepsilon$. (G2) For audit distributions D_k and $\mu_k = D_k\{p \ge \alpha_c\}$, certificates $\bar{\eta}_k$ with $\Pr(\exists k : \mu_k > \bar{\eta}_k) \le \varepsilon'$. No statement $R > b$ is ever produced.

6 LEXIS: anytime-valid margin confirmation

For candidate j with null $H_j : p(\delta_j) \le \alpha$ define

$$E_{j,n} = \prod_{i=1}^{n} (1 + \lambda_{j,i}(\tilde{Y}_{j,i} - \alpha)), \qquad \lambda_{j,i} = f_j(\mathcal{R}_j, \tilde{Y}_{j,1}, \ldots, \tilde{Y}_{j,i-1}) \in [0, 1/\alpha), \tag{3}$$

where $\mathcal{R}_j$ is the registration information (including the weight a_j) and $\tilde{Y}$ the recorded outcome. Candidate j is confirmed once $\sup_n E_{j,n} \ge 1/a_j$, and $\hat{b} = \min\{c(\delta_j) : j \text{ confirmed}\}$. Weights satisfy $\sum_j a_j \le \varepsilon$ almost surely; by default lease n receives $\varepsilon/(n(n+1))$, split evenly across R registrations, which never exhausts.

Theorem 1 (Schedule-oblivious validity)**.** *Under Assumptions 1–3, if $\tilde{Y} \le Y$ pointwise, bets depend only on registration information and the committed prefix, and the committed stream of each candidate is a prefix of its slot-indexed sequence, then for every generator, allocation and continuation policy, stopping rule and execution order, $\Pr(\exists j : H_j \text{ true}, \ j \text{ confirmed}) \le \varepsilon$, hence $\Pr(R > \hat{b}) \le \varepsilon$.*

Proof. Index candidates by registration and extend each slot sequence to infinity conceptually. Let $E^*_{j,n}$ be (3) on the full sequence and $\mathcal{G}_{j,n} = \sigma(\mathcal{R}_j, \tilde{Y}_{j,1..n}, \text{crash noise of slots } 1..n)$. (i) By Assumptions 1, 2 and 3, $u_{j,n+1}$ is independent of $\mathcal{G}_{j,n}$, so $\mathbb{E}[\tilde{Y}_{j,n+1} \mid \mathcal{G}_{j,n}] \le \mathbb{E}[Y_{j,n+1} \mid \mathcal{G}_{j,n}] = p(\delta_j) \le \alpha$ under H_j; with $\lambda \ge 0$ predictable and $1 - \lambda\alpha > 0$, E^*_j is a non-negative supermartingale with $E^*_{j,0} = 1$. (ii) Ville's inequality conditional on $\mathcal{R}_j$ gives $\Pr(\sup_n E^*_{j,n} \ge 1/a_j \mid \mathcal{R}_j) \le a_j$ on H_j. (iii) Whatever the schedule, the committed stream is a prefix of the full sequence, so confirmation implies $\sup_n E^*_{j,n} \ge 1/a_j$; abandonment, pruning, out-of-order execution and even clairvoyant stopping only shorten the prefix. (iv) Summing, the probability that some true null is confirmed is at most $\mathbb{E}\sum_j a_j \le \varepsilon$. If no null is confirmed, every confirmed δ has $p > \alpha$, so $R \le \hat{b}$. □

Proposition 2 (Anytime zero-failure certificate)**.** *For i.i.d. Bernoulli(q) draws and any random time N, $\Pr(S_N = 0 \text{ and } q > 1 - \beta^{1/N}) \le \beta$.*

Proof. With $n_0 = \lceil \log\beta / \log(1-q) \rceil$ the event requires the first n_0 draws to be zero, which has probability $(1-q)^{n_0} \le \beta$. □

Proposition 3 (Certificate from a betting upper confidence sequence)**.** *Test $H_g : q \ge g$ on a grid with $\prod(1 + \lambda_i(g - Z_i))$, λ_i predictable, and let U_n be the smallest grid value above which all grid values are rejected. Then $\Pr(\exists n : q > U_n) \le \beta$. For audits $Z = \mathbf{1}\{\ge t \text{ of } r \text{ runs violate}\}$ (crash $\Rightarrow Z = 1$), every draw with $p \ge \alpha_c$ has $\Pr(Z = 1) \ge h = \Pr(\mathrm{Bin}(r, \alpha_c) \ge t)$, so $\mu_k \le U_k/h =: \bar{\eta}_k$.*

Proof. If $q > U_n$ the largest grid value $g \le q$ is rejected although H_g holds; its e-process is a non-negative supermartingale, so Ville bounds this single event by β. Monotonicity of the binomial tail in p gives the mass bound. □

Proposition 4 (Confirmation cost)**.** *With a fixed bet λ and drift $g(\lambda, p) > 0$, $\mathbb{E}_p[\tau] \le (\log(1/a) + \log(1 + \lambda(1-\alpha)))/g(\lambda, p)$, and the Kelly bet for p_1 attains $g = \mathrm{KL}(p_1 \| \alpha)$. Any level-a test that stops almost surely under p has $\mathbb{E}_p[\tau] \ge \log(1/(2.4a))/\mathrm{KL}(p\|\alpha)$.*

Proof. Wald's identity with bounded overshoot gives the upper bound; the lower bound is the change-of-measure argument of [21] applied to $\tau \wedge n$. □




Figure 1: FRESCO architecture. All safety properties route through the ledger; the frontier broadcast and worker state are soft caches that affect only efficiency.

Per-level search with candidates drawn i.i.d. and violating mass $\pi_k(\Delta)$ costs $O\big(K(\log\frac{1}{\varepsilon} + \log J)/(\pi_k \,\mathrm{KL}(\alpha{+}\Delta\|\alpha))\big)$ slots under uniform level weights, which are minimax among fixed weightings (worst case $T/\min_k w_k \geq KT$). Finally, the aggregate discovered-compromise curve $\hat{F}(b) = \frac{1}{N}\sum_i \mathbf{1}\{\hat{b}_i \leq b\}$ satisfies $\hat{F}(b) - F(b) \leq \frac{1}{N}\sum_i \mathbf{1}\{\hat{b}_i < R_i\}$ uniformly in b, so it is a conservative lower estimate of the vulnerable fraction up to ε in expectation.

7 FRESCO: protocol and architecture

Rules. **R1** slot keys $u_{j,k} = \mathrm{PRF}_\kappa(\mathrm{run}, j, k)$ revealed only on lease; **R2** bets see only the committed prefix; **R3** each slot has at most one terminal value (first write wins, fenced by a lease token) and the e-process consumes only the contiguous terminal prefix; **R4** a crashed slot is recorded as $Y = 0$ for confirmation and $Z = 1$ for audits and is never re-run with a fresh key (re-running with the *same* key is allowed in replay mode); **R5** every weight is spent from a ledger lease bound to a worker incarnation and fenced on close; **R6** only the ledger confirms, by recomputing the e-process from stored slots.

State machine. The ledger state is (candidates, slots, leases, frontier, audits). Transitions are guarded commands applied atomically and journaled before execution: Grant, Register, Lease, Record, Expire, Advance, Prune/Abandon, Close, Audit. Requests carry (sender, request id) and responses are cached, so retransmissions are idempotent; slot results are additionally fenced by token. Invariants I1–I7 (budget conservation, per-lease spending, write-once slots, monotone commit pointer, deterministic e-process, confirmation soundness, monotone frontier) are checked after every transition in property-based tests.

Theorem 5 (Validity under asynchrony and faults)**.** *Under Assumptions 1–4 and rules R1–R6, G1 and G2 hold for every number of workers, membership history and interleaving, under message delay, reordering, duplication and loss, crash-stop failures of workers and executors, and network partitions.*

Proof sketch. Each hypothesis of Theorem 1 is supplied by a rule: I3–I4 (R3) make the committed stream a prefix of one sequence, and duplicates and late messages fail the token guard; R4 gives $\tilde{Y} \leq Y$ (a crash between execution and recording leaves the slot leased until expiry turns it into a recorded 0); R2 with R6 makes bets predictable; R1 gives Assumptions 1–2; I1–I2 with R5 give $\sum_j a_j \leq \varepsilon$, since registrations under closed leases are rejected by the ledger. Partitions only delay

Algorithm 1 FRESCO worker loop (any scheduling policy is valid by Theorem 1)

loop
  if no open lease **then**
    request GRANT
  end if
  $\hat{b}_{\text{view}} \leftarrow$ latest frontier (possibly stale)
  $a \leftarrow \text{SCHEDULE}(\hat{b}_{\text{view}}, \text{local state})$
  if $a = \text{AUDIT}(k)$ **then**
    lease audit (k, i) with seed; draw $\delta \sim D_k(\text{seed})$; run r episodes; RECORDAUDIT
  else if $a = \text{NEW}(k)$ **then**
    $\delta \leftarrow G_k.\text{PROPOSE}()$; REGISTER(lease, δ) ▷ a_j fixed here
  else if $a = \text{CONTINUE}(j, m)$ **then**
    for each $(k, u, \text{tok}) \in \text{LEASE}(j, m)$ **do**
      $y \leftarrow \text{EXECUTE}(\delta_j, u, \text{deadline})$; **if** no crash **then** $\text{RECORD}(j, k, y, \text{tok})$
    end for
  end if
end loop

transitions; the only timing-dependent transition (expiry) can only make recorded values more conservative. G2 follows from R4 and audit prefix commit with Propositions 2–3. In replay mode a re-run reproduces $Y(\delta_j, u_{j,k})$ exactly, so Assumption 3 is not needed. □

Theorem 6 (Necessity)**.** *For each of R2, R3 (deduplication or ordering), R4 and R5 there is an execution satisfying all other rules with false-confirmation probability exceeding ε; for R3-ordering, R4 and R5 it tends to one.*

Proof. Take $p = \alpha$. *No dedup:* applying every result twice yields $(E^*)^2$; since E^* is a martingale tending to zero, optional stopping gives error in $[\sqrt{\varepsilon}/(1 + \lambda(1 - \alpha)), \sqrt{\varepsilon}]$. *Fresh retry:* if benign episodes crash with probability c_0 and violating ones with $c_1 < c_0$, the recorded stream is Bernoulli$(p(1-c_1)/(p(1-c_1)+(1-p)(1-c_0))) > \alpha$ and any consistent test rejects almost surely. *Arrival order:* with m slots in flight and violations returning first, as $m \to \infty$ the consumed stream is $S \sim \text{Bin}(N, \alpha)$ ones followed by zeros, which crosses any threshold for large N. *Local budget:* W workers each spending ε give family-wise error $1 - (1 - \varepsilon_0)^W \to 1$. *Non-predictable bets:* betting with knowledge of the current outcome never loses wealth. □

Efficiency properties. Because $\hat{b}$ is a monotone min-register computed by the ledger, frontier staleness Δ costs at most $KW\theta\Delta$ wasted slots (θ slots per worker per unit time) and never correctness; m slots in flight per candidate waste at most $m-1$ per decision; and greedy scheduling gives $T_W \le Q_W \bar{t}/W + D\,T_{\max}$ with D the generator's sequential depth [36]. Coordination is one ledger write per slot plus one per registration; at agent-episode durations (5–60 s) and $W = 32$ this is under ten writes per second.

Component justification. A single logical ledger (PostgreSQL in production; schema in the artifact) is required because every safety property needs one serialisation point. Message brokers, caches and custom consensus are deliberately absent: a broker adds an at-least-once hop that must then be deduplicated, a cache reintroduces stale reads that R6 avoids, and the ledger's database replication suffices for availability, which safety never depends on. General-purpose task frameworks may place executors but their automatic retries must be disabled, since they implement the fresh-retry pattern of Theorem 6.

8 Experimental methodology

Why simulation. Coverage claims require ground truth (which candidates are null, the true margin k^*, the true masses μ_k), which real agents never provide. We therefore evaluate the implemented protocol—ledger, message layer, workers—in a deterministic discrete-event simulator with Bernoulli oracles of known p, injected network faults (loss, duplication, reordering, partitions), worker and executor crashes, ledger crash with journal recovery, and outcome-correlated latency (lognormal, mean 20 s benign / 30 s violating). Same configuration and seed reproduce the same event trace.

Workloads. S1-moderate: violating fractions $(0, 0, 0.05, 0.10)$ at levels 1–4 with $p = 0.6$; S2-sparse: $(0, 0, 0.01, 0.05)$; weak scaling: $0.16/W$ at level 3; boundary null: every candidate at $p = \alpha = 0.2$; certificate scenario: rare violators ($\mu = 0.003, 0.01$, $p = 0.3$). $\alpha = 0.2$, $\varepsilon = \varepsilon' = 0.05$, four executors per worker, horizon $H = 150{,}000$ s.

Baselines. B0a: MARGIN-Bench Algorithm 1 as specified (per-budget top-T confirmation, Wilson bound at ε/T); B0b: repaired (Clopper–Pearson at $\varepsilon/(KT)$); B1: W independent single-worker deployments with ε/W each; B2: FRESCO with one rule removed; B3: one centralized scheduler driving all $4W$ executors. All methods use the same total concurrency.

Statistics. Seeds are the unit of analysis. Time-to-margin is censored at H; we report restricted mean survival time (RMST) with percentile-bootstrap CIs, Kaplan–Meier curves [51], two-sided Mann–Whitney tests with Holm correction, rank-biserial correlations, and Wilson intervals for proportions. Validity is judged by the Wilson lower bound against ε. With 100 seeds per cell the study detects RMST ratios below about 0.65 with roughly 80% power.

9 Results

All results in this section are synthetic.

9.1 Validity (RQ1)

Every ledger-based method stayed valid at every W (Table 2, Fig. 2). Algorithm 1 as specified exceeded its nominal level five-fold: it tests $K = 4$ budget levels in sequence, each at ε/T, without correcting across levels, and its Wilson bound is anti-conservative at $n = 30$. The exact repair is valid and, as shown below, no less efficient. Rule ablations through the full system (400 seeds each) reproduced Theorem 6: removing deduplication, the fresh-retry ban or in-order commit gave 0.133 [0.103, 0.169], 0.102 [0.076, 0.136] and 0.083 [0.059, 0.114], against 0.003–0.018 for FRESCO under the same triggers and 0.003 [0.000, 0.014] under all faults combined. Removing the global budget at $W = 8$ gave 0.065 [0.045, 0.094]; its inflation is not established at this configuration.

9.2 Scalability (RQ2)

FRESCO's restricted mean time to the true margin fell from 27,955 s at $W = 1$ to 1,101 s at $W = 32$ on S1 (speedup 25.4×, efficiency 0.79; Fig. 3); on S2 the speedup was at least 21.4× (38% of single-worker runs were censored). Oracle calls to the margin stayed nearly flat (5.2k at $W = 1$, 6.6k at $W = 32$, overlapping CIs), messages per oracle call grew from 3.34 to 3.71, and the ledger processed about 10 operations per virtual second at $W = 32$. Weak-scaling efficiency was 0.81–0.97 up to $W = 16$ and 0.71 [0.53, 0.96] at $W = 32$. After a 60 s ledger crash, a 120 s crash of half the workers, or a 300 s partition of half the workers, throughput returned to 90%

Table 2: False-confirmation probability on the boundary null (every confirmation is false; nominal $\varepsilon = 0.05$; 95% Wilson intervals).

Method	False/runs	Pr(false confirmation)
FRESCO, $W = 1$ / 8 / 32	5, 2, 1 / 400	0.013, 0.005, 0.003 (all upper limits ≤ 0.029)
Independent ε/W, $W = 8$ / 32	2, 0 / 400	0.005, 0.000
Centralized scheduler, $W = 8$ / 32	9, 6 / 400	0.022 [0.012, 0.042], 0.015 [0.007, 0.032]
Algorithm 1 as specified (Wilson, ε/T)	513/2000	**0.257 [0.238, 0.276]**
Algorithm 1 repaired (Clopper–Pearson, ε/KT)	69/2000	0.035 [0.027, 0.043]
LEXIS (1,160 / 30,000-slot budget)	37, 21 / 2000	0.018 [0.013, 0.025], 0.011 [0.007, 0.016]




Figure 2: Validity of all methods at the boundary null. Only Algorithm 1 as specified is invalid.

of its pre-fault level within one 20 s measurement bucket; lost work matched the arithmetic loss (Fig. 4).

9.3 Does cooperation help? (RQ3)

No. In all 20 Holm-corrected comparisons (two scenarios, $W \in \{2, 4, 8, 16, 32\}$, against B1 and B3) we detected no difference: RMST ratios ranged from 0.77 to 1.14 against independent runs and 0.81 to 1.30 against the centralized scheduler, every 95% CI contained 1, and every adjusted $p \geq 0.94$ (Fig. 5). This agrees with the analysis that cooperation has no built-in statistical advantage—a shared budget spends over more registrations, roughly cancelling the union-bound saving—while frontier pruning saves only work at levels above the current margin. Effects smaller than a ratio of about 0.65 could not be detected.

9.4 Sample efficiency and certificates (RQ4)

At a matched budget of 1,160 oracle calls, repaired Algorithm 1 reached the true margin in 0.800 [0.782, 0.817] of S1 runs versus 0.246 [0.228, 0.266] for LEXIS, and 0.272 versus 0.043 on S2;




Figure 3: Strong scaling of time to the true margin for three methods (top; shaded: 95% bootstrap CI) and FRESCO speedup and weak-scaling efficiency (bottom).

LEXIS needed roughly 3–12× more calls (Table 3). A post-hoc, explicitly exploratory reduction of the per-candidate cap did not close the gap. The cause is structural: Algorithm 1 screens each candidate with five trials and confirms only the top three, whereas LEXIS runs every opened null candidate to its cap and spreads effort over empty levels. Certificates covered in every run (coverage 1.000 [0.981, 1.000], both audit rules) but were loose: median $\bar{\eta}_k$ of 0.73–0.75 with $(r, t) = (3, 1)$ and 0.39–0.40 with the gap rule $(10, 4, \alpha_c = 0.3)$, against true masses of 0–0.01. Ablations (Fig. 6) confirmed the lease-policy fix (the earlier fixed-fraction policy was 1.7× slower at $W = 32$), showed that cheap-first level weights cost 2.1× when cheap levels are barren, and that conservative crash imputation costs 1.7× under 20% crashes, mostly recovered by replay mode.

9.5 Real-agent experiments

These have *not* been run; Table 5 lists the required evidence. The protocol: (1) profile 2,000 episodes per open-weight model to estimate timeout and crash rates separately for violating and benign trajectories and measure redelivery rates of common queue configurations, then rerun the fault-injection study with the measured rates; (2) replay 200 completed slots to verify seeded determinism; (3) compare FRESCO with B0b, B1 and B3 on 20 MARGIN-Bench scenario families with cluster bootstrap over families; (4) report authorized-task completion on paired counterparts; (5) re-confirm witnesses across models with fresh keys.




Figure 4: Oracle-call throughput around injected faults ($W = 8$, mean of 30 seeds).




Figure 5: Kaplan–Meier curves of time to the true margin at $W = 8$. Curves overlap in both scenarios.

10 Discussion and failure analysis

What the evidence supports. The defensible contribution is *fault-tolerant validity*: an evaluation harness can be parallelised to tens of workers with near-linear speedup and negligible coordination while its reported margins keep their stated error level under faults that, with ordinary engineering defaults, inflate that error several-fold. The rules are cheap—one ledger write per episode and a write-once constraint—and they remove failure modes whose error is unbounded in the limit.

What it does not support. Cooperation did not help, and LEXIS was less sample-efficient than a repaired fixed design. The latter points to a concrete redesign: keep fixed-design screening (few trials per candidate, promote the best) and replace its one-shot confirmation by LEXIS e-processes with scouting-weighted spending, which preserves anytime validity and FRESCO compatibility. This hybrid is untested. The certificates are honest but coarse; informative statements at the 1–5% level need thousands of audits per level or a certified gap above α.

When FRESCO fails. Validity is lost if episodes share hidden state (e.g. memory not reset between slots), if the oracle has false positives (the guarantee then concerns the observed rate), or if keys leak to the generator. Efficiency collapses if violating episodes time out more often than benign ones, since conservative imputation then hides them; replay mode or longer deadlines are required, and deadlines must be preregistered as statistical parameters.

Table 3: Probability of reaching the true margin $k^* = 3$ (slot-level, single process; 2,000 runs each).

Instance	Method	Pr(reach k^*)	Median calls when reached
S1	Algorithm 1 repaired ($\leq$1,160 calls)	0.800 [0.782, 0.817]	810
S1	LEXIS, matched 1,160 calls	0.246 [0.228, 0.266]	552
S1	LEXIS, 30,000 calls	0.998 [0.994, 0.999]	2,993
S2	Algorithm 1 repaired	0.272 [0.252, 0.291]	810
S2	LEXIS, matched	0.043 [0.035, 0.053]	544
S2	LEXIS, 30,000 calls	0.782 [0.764, 0.800]	10,011

Table 4: Preregistered hypotheses and verdicts (synthetic evidence).

Hypothesis	Criterion	Verdict
H-valid-sim	Wilson lower bound $\leq \varepsilon$ in all FRESCO configurations	supported
H-rules	removed rule gives lower bound $> \varepsilon$	supported for 3 of 4 rules
H-alg1	specified Algorithm 1 exceeds ε, repaired does not	supported
H-vs-Alg1	LEXIS reaches k^* at least as often at matched budget	**refuted**
H-speed	speedup CI lower bound ≥ 16 at $W = 32$	supported (25.4×)
H-coop	cooperative FRESCO faster than B1 and B3	**not supported**
H-overhead	≤ 10 messages per call, ≤ 100 ledger ops/s	supported
H-recover	90% throughput within 2× outage	supported
H-cert	coverage ≥ 0.95	supported; certificates loose
H-valid-real	measured fault profiles imply inflation	[TO RUN]

Implications for MARGIN-Bench. Its Algorithm 1 should either adopt the exact $\varepsilon/(KT)$ repair, which costs no efficiency in our experiments, or the screening-plus-e-process hybrid; and any distributed harness used for it should implement at least deduplication, in-order consumption and the fresh-retry ban.

11 Threats to validity

Construct: synthetic oracles and latency/crash models are assumptions; effect sizes of rule violations in real harnesses may be smaller or larger. *Internal:* default parameters (cap, audit share, lease size) were not tuned and are not time-optimal; one post-hoc variant is labelled exploratory. *Statistical:* 100 seeds per cell bound detectable effects; censoring at a common horizon is handled by RMST; seeds share random streams across methods by design. *External:* the simulated generator is non-adaptive; adaptive attackers add sequential depth that may limit scaling. *Implementation:* the production database ledger is specified but not executed; coordination cost is measured in virtual time.

12 Limitations and negative results

(i) No real-agent results. (ii) No cooperative speed-up was detected. (iii) LEXIS is less sample-efficient than a repaired fixed design. (iv) Certificates are loose at realistic audit budgets. (v) The global-budget rule's necessity was not established at $W = 8$ in the system-level study, although it follows analytically for larger W. (vi) Byzantine executors are not covered; verifiable confirmation checks computation, not outcomes. (vii) Bit-reproducible epoch mode, an ASHA-style scheduler baseline and the database adapter are not yet implemented.




Figure 6: Component ablations at $W = 8$ on S1 (RMST ratio relative to the default; 95% CI).

13 Reproducibility and data availability

All code, configurations, raw results (JSON lines with configuration hashes and code revisions), analysis scripts and figures are in the project repository [INSERT PERMANENT ARCHIVE DOI]. `experiments/run_all.sh` regenerates every number and figure in about two hours on four cores; `python -m pytest tests` runs 42 unit, property-based and integration tests; the simulator is deterministic given configuration and seed. For real-agent runs, the run key is committed by hash before execution and revealed afterwards, so every slot key can be recomputed and checked against stored traces.

14 Future work

Execute the real-agent protocol; implement and evaluate the screening-plus-e-process hybrid; adaptive level scheduling that beats the factor-K price on structured instances; tighter certificates via adaptive audit allocation; Byzantine-tolerant executors with attestation for third-party compute; and extension of the evaluation to authorization-race scenarios in multi-agent delegation.

15 Conclusion

Statistical guarantees of LLM-agent security evaluation depend on how episodes are executed. We proved that six simple protocol rules make sequential margin confirmation valid independently of

Table 5: Real-agent result shells. No value may be filled except from executed runs.

Quantity	Model A	Model B
Timeout/crash rate by outcome (c_0, c_1)	[TO RUN]	[TO RUN]
Replay determinism (% trace-hash match)	[TO RUN]	[TO RUN]
Implied false-confirmation inflation per removed rule	[TO RUN]	[TO RUN]
RMST time to $\hat{b}$: FRESCO / B1 / B3	[TO RUN]	[TO RUN]
Per-surface $\hat{b}$ and censoring fraction	[TO RUN]	[TO RUN]
Authorized-task completion	[TO RUN]	[TO RUN]
Cross-model witness transfer rate	[TO RUN]	[TO RUN]

scheduling and faults, showed that each common executor default can break it, and demonstrated in simulation near-linear scaling at negligible coordination cost. Two hypotheses we expected to hold did not: cooperation brought no speed-up, and our sequential procedure was less sample-efficient than a repaired fixed design, which also exposed an error in the original benchmark's estimator. Real-agent validation remains to be done.

Declarations

Funding. [INSERT TRUE FUNDING INFORMATION OR "No funding was received".]
Competing interests. [AUTHORS TO DISCLOSE.]
Ethics approval. Not applicable to the simulation study; the real-agent protocol uses sandboxed mock tools and no human participants [CONFIRM BEFORE REAL-AGENT RUNS].
Data availability. Synthetic results are released with the code [ARCHIVE DOI]. No real-agent data exist yet.
Code availability. [REPOSITORY URL AND ARCHIVE DOI].
Author contributions. [CRediT STATEMENT].
Use of generative AI. [AUTHORS MUST DISCLOSE: substantial parts of the design, code, analysis and text of this working manuscript were drafted with an AI assistant and must be verified and declared according to the journal's policy.]

References

[1] Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection. In *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security (AISec)*, 2023. doi: 10.1145/3605764.3623985.

[2] Edoardo Debenedetti, Jie Zhang, Mislav Balunović, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents. In *NeurIPS Datasets and Benchmarks Track*, 2024. URL https://arxiv.org/abs/2406.13352. arXiv:2406.13352.

[3] Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. InjecAgent: Benchmarking indirect prompt injections in tool-integrated large language model agents. arXiv:2403.02691, 2024. URL https://arxiv.org/abs/2403.02691.

[4] MARGIN-Bench: Counterfactual safety margins for multi-turn and multi-agent large language model systems. Working manuscript v1.0, 18 October 2026 (unpublished), 2026.

[5] Aaditya Ramdas, Peter Grünwald, Vladimir Vovk, and Glenn Shafer. Game-theoretic statistics and safe anytime-valid inference. *Statistical Science*, 38(4), 2023. doi: 10.1214/23-STS894.

[6] Vladimir Vovk and Ruodu Wang. E-values: Calibration, combination and applications. *The Annals of Statistics*, 49(3), 2021. doi: 10.1214/20-AOS2020.

[7] Peter Grünwald, Rianne de Heide, and Wouter Koolen. Safe testing. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 2024. doi: 10.1093/jrsssb/qkae011.

[8] Ian Waudby-Smith and Aaditya Ramdas. Estimating means of bounded random variables by betting. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 86(1), 2024. doi: 10.1093/jrsssb/qkad009.

[9] Steven R. Howard, Aaditya Ramdas, Jon McAuliffe, and Jasjeet Sekhon. Time-uniform, nonparametric, nonasymptotic confidence sequences. *The Annals of Statistics*, 49(2), 2021. doi: 10.1214/20-AOS1991.

[10] Ramesh Johari, Pete Koomen, Leonid Pekelis, and David Walsh. Always valid inference: Continuous monitoring of A/B tests. *Operations Research*, 70(3), 2022. doi: 10.1287/opre.2021.2135.

[11] Ruodu Wang and Aaditya Ramdas. False discovery rate control with e-values. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 84(3), 2022. doi: 10.1111/rssb.12489.

[12] Ziyu Xu and Aaditya Ramdas. Online multiple testing with e-values. In *Proceedings of the 27th International Conference on Artificial Intelligence and Statistics (AISTATS)*, volume 238 of *Proceedings of Machine Learning Research*, pages 3997–4005, 2024. URL https://proceedings.mlr.press/v238/xu24a.html.

[13] Dean P. Foster and Robert A. Stine. α-investing: a procedure for sequential control of expected false discoveries. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 70(2), 2008. doi: 10.1111/j.1467-9868.2007.00643.x.

[14] Lisa V. Hampson and Christopher Jennison. Group sequential tests for delayed responses (with discussion). *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 75(1), 2013. doi: 10.1111/j.1467-9868.2012.01030.x.

[15] Hideaki Kano, Junya Honda, Kentaro Sakamaki, Kentaro Matsuura, Atsuyoshi Nakamura, and Masashi Sugiyama. Good arm identification via bandit feedback. *Machine Learning*, 2019. doi: 10.1007/s10994-019-05784-4.

[16] Andrea Locatelli, Maurilio Gutzeit, and Alexandra Carpentier. An optimal algorithm for the thresholding bandit problem. In *Proceedings of the 33rd International Conference on Machine Learning (ICML)*, volume 48 of *Proceedings of Machine Learning Research*, 2016. URL https://proceedings.mlr.press/v48/locatelli16.html.

[17] Maryam Aziz, Jesse Anderton, Emilie Kaufmann, and Javed Aslam. Pure exploration in infinitely-armed bandit models with fixed-confidence. In *Proceedings of Algorithmic Learning Theory (ALT)*, volume 83 of *Proceedings of Machine Learning Research*, pages 3–24, 2018. URL https://proceedings.mlr.press/v83/aziz18a.html.

[18] Arghya Roy Chaudhuri and Shivaram Kalyanakrishnan. PAC identification of a bandit arm relative to a reward quantile. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 31, 2017. URL https://ojs.aaai.org/index.php/AAAI/article/view/10802.

[19] Eshcar Hillel, Zohar Karnin, Tomer Koren, Ronny Lempel, and Oren Somekh. Distributed exploration in multi-armed bandits. In *Advances in Neural Information Processing Systems 26 (NeurIPS)*, 2013. URL https://papers.nips.cc/paper/2013/hash/598b3e71ec378bd83e0a727608b5db01-Abstract.html.

[20] Liam Li, Kevin Jamieson, Afshin Rostamizadeh, Ekaterina Gonina, Jonathan Ben-tzur, Moritz Hardt, Benjamin Recht, and Ameet Talwalkar. A system for massively parallel hyperparameter tuning. In *Proceedings of Machine Learning and Systems (MLSys)*, 2020. URL https://proceedings.mlsys.org/paper_files/paper/2020/hash/a06f20b349c6cf09a6b171c71b88bbfc-Abstract.html.

[21] Emilie Kaufmann, Olivier Cappé, and Aurélien Garivier. On the complexity of best-arm identification in multi-armed bandit models. *Journal of Machine Learning Research*, 17, 2016. URL https://jmlr.org/papers/v17/kaufman16a.html.

[22] Marcel Böhme. STADS: Software testing as species discovery. *ACM Transactions on Software Engineering and Methodology*, 27(2), 2018. doi: 10.1145/3210309.

[23] Marcel Böhme, Danushka Liyanage, and Valentin Wüstholz. Estimating residual risk in greybox fuzzing. In *Proceedings of the 29th ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering (ESEC/FSE)*, 2021. doi: 10.1145/3468264.3468570.

[24] Håkan L. S. Younes and Reid G. Simmons. Statistical probabilistic model checking with a focus on time-bounded properties. *Information and Computation*, 204(9), 2006. doi: 10.1016/j.ic.2006.05.002.

[25] Axel Legay, Benoît Delahaye, and Saddek Bensalem. Statistical model checking: An overview. In *Runtime Verification (RV 2010)*, volume 6418 of *Lecture Notes in Computer Science*. Springer, 2010. doi: 10.1007/978-3-642-16612-9_11.

[26] Marco C. Campi and Simone Garatti. The exact feasibility of randomized solutions of uncertain convex programs. *SIAM Journal on Optimization*, 19(3), 2008. doi: 10.1137/07069821X.

[27] Evan Miller. Adding error bars to evals: A statistical approach to language model evaluations. arXiv:2411.00640, 2024. URL https://arxiv.org/abs/2411.00640.

[28] Bandana Kaur. What AI red-team evaluations can and cannot prove. arXiv:2607.21735, 2026. URL https://arxiv.org/abs/2607.21735.

[29] DynamiQ: Unlocking the potential of dynamic task allocation in parallel fuzzing. arXiv:2510.04469, 2025. URL https://arxiv.org/abs/2510.04469.

[30] Cary G. Gray and David R. Cheriton. Leases: An efficient fault-tolerant mechanism for distributed file cache consistency. In *Proceedings of the 12th ACM Symposium on Operating Systems Principles (SOSP)*, 1989. doi: 10.1145/74850.74870.

[31] Patrick E. O'Neil. The escrow transactional method. *ACM Transactions on Database Systems*, 11(4), 1986. doi: 10.1145/7239.7265.

[32] Marc Shapiro, Nuno Preguiça, Carlos Baquero, and Marek Zawirski. Conflict-free replicated data types. In *Stabilization, Safety, and Security of Distributed Systems (SSS 2011)*, volume 6976 of *Lecture Notes in Computer Science*. Springer, 2011. doi: 10.1007/978-3-642-24550-3_29.

[33] Joseph M. Hellerstein and Peter Alvaro. Keeping CALM: When distributed consistency is easy. *Communications of the ACM*, 63(9), 2020. doi: 10.1145/3369736.

[34] Leslie Lamport. Time, clocks, and the ordering of events in a distributed system. *Communications of the ACM*, 21(7), 1978. doi: 10.1145/359545.359563.

[35] K. Mani Chandy and Leslie Lamport. Distributed snapshots: Determining global states of distributed systems. *ACM Transactions on Computer Systems*, 3(1), 1985. doi: 10.1145/214451.214456.

[36] Ronald L. Graham. Bounds on multiprocessing timing anomalies. *SIAM Journal on Applied Mathematics*, 17(2), 1969. doi: 10.1137/0117039.

[37] Tao Luo, Mingen Pan, Pierre Tholoniat, Asaf Cidon, Roxana Geambasu, and Mathias Lécuyer. Privacy budget scheduling. In *15th USENIX Symposium on Operating Systems Design and Implementation (OSDI)*, 2021. URL https://www.usenix.org/conference/osdi21/presentation/luo.

[38] Tanqiu Jiang, Yuhui Wang, Jiacheng Liang, and Ting Wang. AgentLAB: Benchmarking LLM agents against long-horizon attacks. In *Proceedings of the 43rd International Conference on Machine Learning (ICML)*, volume 306 of *Proceedings of Machine Learning Research*, 2026. URL https://proceedings.mlr.press/v306/jiang26as.html.

[39] TAMAS: Benchmarking adversarial risks in multi-agent LLM systems. arXiv:2511.05269, 2025. URL https://arxiv.org/abs/2511.05269.

[40] The dark side of LLMs: Agent-based attack vectors for system-level compromise. arXiv:2507.06850, 2025. URL https://arxiv.org/abs/2507.06850.

[41] Mantas Mazeika et al. HarmBench: A standardized evaluation framework for automated red teaming and robust refusal. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, volume 235 of *Proceedings of Machine Learning Research*, 2024. URL https://proceedings.mlr.press/v235/mazeika24a.html.

[42] Tianzhuo Yang et al. AgentBoundary: Counterfactual evaluation of safety in tool-using LLM agents. arXiv:2609.33658, 2026. URL https://arxiv.org/abs/2609.33658.

[43] Viraaji Mothukuri and Reza M. Parizi. Causal detection of multi-step LLM agent attacks. In *Proceedings of the 43rd International Conference on Machine Learning (ICML)*, volume 306 of *Proceedings of Machine Learning Research*, 2026. URL https://proceedings.mlr.press/v306/mothukuri26a.html.

[44] Edoardo Debenedetti et al. Defeating prompt injections by design. arXiv:2503.18813, 2025. URL https://arxiv.org/abs/2503.18813.

[45] Tobin South et al. Authenticated delegation and authorized AI agents. arXiv:2501.09674, 2025. URL https://arxiv.org/abs/2501.09674.

[46] John Hughes et al. Best-of-N jailbreaking. In *Advances in Neural Information Processing Systems 38 (NeurIPS)*, 2025. URL https://arxiv.org/abs/2412.03556. arXiv:2412.03556.

[47] Ruoming Pang et al. Zanzibar: Google's consistent, global authorization system. In *2019 USENIX Annual Technical Conference (USENIX ATC)*, 2019. URL https://www.usenix.org/conference/atc19/presentation/pang.

[48] Arnar Birgisson, Joe Gibbs Politz, Úlfar Erlingsson, Ankur Taly, Michael Vrable, and Mark Lentczner. Macaroons: Cookies with contextual caveats for decentralized authorization in the cloud. In *Network and Distributed System Security Symposium (NDSS)*, 2014. doi: 10.14722/ndss.2014.23212.

[49] Derek Lilienthal and Sanghyun Hong. Mind the gap: Time-of-check to time-of-use vulnerabilities in LLM-enabled agents. NeurIPS 2025; arXiv:2508.17155, 2025. URL https://arxiv.org/abs/2508.17155.

[50] Christopher R. Genovese, Kathryn Roeder, and Larry Wasserman. False discovery control with p-value weighting. *Biometrika*, 93(3), 2006. doi: 10.1093/biomet/93.3.509.

[51] Edward L. Kaplan and Paul Meier. Nonparametric estimation from incomplete observations. *Journal of the American Statistical Association*, 53(282), 1958. doi: 10.1080/01621459.1958.10501452.