Shortcuts and Temporal Leakage in the Bangalore EEG Epilepsy Dataset: a Provenance Audit and Leakage-Aware Benchmark of Lightweight Seizure-Type Classifiers

[Author Name][1,*], [Co-author Name][1] and [Supervisor Name][1]

[1][Department of ... (e.g. M.Tech, Artificial Intelligence and Data Science)], [Indian Institute of Information Technology (IIIT) Bhagalpur], [Bhagalpur], [India]

[*]Corresponding Author: [Author Name], [Email]. ORCID: [Author ORCID]; [Co-author ORCID]; [Supervisor ORCID]

Track 5: Digital Life Sciences, Health, Agriculture & Biodiversity (healthcare artificial intelligence)

Abstract

Public electroencephalography datasets are widely used to develop automated seizure classifiers, and the recently released Bangalore EEG Epilepsy Dataset has quickly attracted reports of 95–99% accuracy. We asked whether these figures reflect physiological discrimination between healthy, generalised-seizure, focal-seizure and seizure-event recordings, or properties of how the public file was assembled. We audited the 8000-row, 16-column file using autocorrelation analysis and exact matching against an older public benchmark, and then benchmarked seven classical and four small deep-learning models under two evaluation protocols: the conventional random row-level split and a leakage-aware protocol that holds out contiguous time blocks with a temporal purge gap. Hyper-parameters were tuned by nested cross-validation; we report bootstrap confidence intervals, corrected resampled t-tests, Friedman tests, calibration and Shapley-value explanations. The audit showed that the columns mean different things in different classes: every one of the 2000 'healthy' rows is an exact 16-sample excerpt of the Bonn eyes-closed recordings (173.61 Hz,

single channel), whereas the three seizure classes are 16-channel time points of continuous recordings, so consecutive rows are near-duplicates. Under a random split, the best model reached a macro-averaged F1 score of 0.986; under the leakage-aware protocol, the best reached 0.842 (95% confidence interval 0.800–0.880). Healthy-versus-seizure detection remained near-perfect under both protocols (macro-F1 ≥ 0.999), consistent with a source shortcut rather than a clinical signal. For the three seizure types alone, macro-F1 fell from 0.990 to 0.776. Results on this file should therefore be reported with leakage-aware splits, and the healthy class should not be used for clinical claims. We release a reproducible pipeline and a lightweight model profile for edge deployment.

Keywords: electroencephalography; epileptic seizure classification; data leakage; dataset provenance; blocked cross-validation; probability calibration; explainable machine learning; edge deployment

1 Introduction

Epilepsy diagnosis relies heavily on visual review of the electroencephalogram (EEG), which is slow and requires specialist expertise; machine-learning (ML) classifiers are therefore an active research area [1–4]. Progress depends on public datasets such as the Bonn recordings [5] and the CHB-MIT scalp database [1,6]. The Bangalore EEG Epilepsy Dataset (BEED), released through the UCI Machine Learning Repository in 2024 [7,8], adds a four-class problem: healthy subjects (class 0), generalised seizures (1), focal seizures (2) and seizure events accompanied by behaviours such as blinking or staring (3). Distinguishing focal from generalised onset matters clinically because it guides treatment choices, and seizure-type classification is markedly harder than seizure detection [9].

Within two years, several studies reported 95–99% accuracy on BEED [8,10–14]. However, the public BEED file contains only 8000 rows of 16 integers with no subject or recording identifiers, and its documentation does not say whether a row is 16 channels at one instant or

16 samples of one channel. Most reported evaluations split rows at random. In EEG and other autocorrelated data, random splits can place almost identical neighbouring samples in training and test sets, inflating performance [15–17]. Whether this applies to BEED had not been examined.

Research questions. We addressed four questions. (RQ1) What do the rows and columns of the public BEED file represent, and is the representation the same across classes? (RQ2) How much of the reported performance survives an evaluation that prevents temporal leakage? (RQ3) Once shortcuts are controlled, which signal properties separate generalised, focal and seizure-event recordings, and are the predicted probabilities calibrated? (RQ4) Can a model small enough for wearable or edge hardware retain the leakage-safe performance?

Contributions. (i) A structural and provenance audit showing that the healthy class is an exact excerpt of the Bonn eyes-closed set whereas the seizure classes are multichannel time points, which creates a source shortcut and strong temporal autocorrelation between rows. (ii) A leakage-aware protocol (grouped, temporally blocked splits with a purge gap and nested tuning) and a quantification of the gap between random and blocked evaluation. (iii) A statistically grounded benchmark of eleven models with cluster-bootstrap confidence intervals, corrected resampled t-tests, Friedman/Nemenyi analysis and calibration. (iv) Shapley-value interpretation of seizure-type discrimination and a parameter and latency profile of lightweight models. (v) An open, fully reproducible pipeline (Supplementary File S1).

2 Related Work

2.1 Seizure detection and classification benchmarks

The Bonn dataset [5] contains five sets of 100 single-channel, 23.6 s segments sampled at 173.61 Hz; a widely redistributed UCI version cuts each segment into 1 s chunks of 178

samples and shuffles them [18]. Deep convolutional networks report near-perfect accuracy on Bonn [2]; CHB-MIT provides long multichannel paediatric recordings at 256 Hz [1,6] used for detection and prediction [3,4]. Classic hand-crafted EEG descriptors include Hjorth parameters [19], line length [20], sample and permutation entropy [21,22] and discrete wavelet energies [23]. For seizure-type classification on the TUH corpus, weighted F1 fell from 0.901 under seizure-wise to 0.561 under patient-wise cross-validation [9], showing how strongly the evaluation protocol shapes conclusions.

2.2 Prior work on BEED

Table 1 summarises published BEED studies. Most use row-level random or stratified splits; one preprint described its protocol as subject-independent, but its methods section reports a stratified 70/15/15 sample-level split, because the file has no subject identifiers [12]. One study used 20 s, 14-channel segments [14], which suggests that a richer version of BEED exists than the public CSV file.

Table 1. Published studies on the public BEED file and their evaluation protocols

Study	Method	Evaluation protocol (as reported)	Reported result
Najmusseher and Nizar Banu [8]	UMAP + FFT features, stacked LSTM/XGBoost/GB (SeqBoostNet)	Train/test split of rows	Accuracy 96.71%
Paneru [10]	UMAP + FFT, two-level stacking, LIME	Hold-out; 10-fold nested CV	Accuracy 97.06% (nested CV 91.51%)
Nandatama [11]	Nine classical models, noise robustness	Row-level split	LightGBM F1 0.9831
Sajid et al. [12]	CNN + residual attention + BiLSTM (PaperNet)	Stratified 70/15/15 sample-level split	Macro-F1 0.9576
Obaido and Esenogho [13]	Tabular foundation models vs ensembles	Cross-validation on rows	High accuracy (see source)
Heba and Atya [14]	CNN–vision transformer (EpilepsyFormer)	20 s segments, described as subject-independent	Accuracy 98.3%

Abbreviations: UMAP, uniform manifold approximation and projection; FFT, fast Fourier transform; LSTM, long short-term memory; GB, gradient boosting; LIME, local interpretable model-agnostic explanations; CNN, convolutional neural network; CV, cross-validation. Protocols are as stated by the original authors.

2.3 Leakage in machine-learning evaluation

Data leakage, in which information about the test set reaches the model during training, is a leading cause of irreproducible ML results [15]. In EEG, splitting segments rather than

subjects inflated deep-learning accuracy substantially [16]. For autocorrelated data, blocked cross-validation with buffers is recommended [17]. To our knowledge, no BEED study has examined row adjacency, the meaning of the columns or the origin of the classes.

3 Materials and Methods

The study design (Supplementary Fig. S9) comprises a structural and provenance audit, provenance-based grouping, and two evaluation protocols sharing identical features, models, tuning and metrics.

3.1 Dataset

We used the BEED CSV file from the UCI repository [7] (8000 rows; integer columns X1–X16; label y). According to its documentation, BEED was recorded at a neurological centre in Bangalore with the 10–20 system at 256 Hz, from 20 adults per class (21–55 years) [7,8]. Each class has 2000 rows stored contiguously (label changes at rows 2000, 4000 and 6000). There were no missing values or duplicated rows. No filtering, resampling or artefact removal was applied, so that the file was analysed exactly as distributed; standardisation was fitted on training data only.

3.2 Structure and provenance audit

For each class we computed (i) the mean correlation between columns k and k+l (within-row lag l), (ii) the mean correlation of each column between rows i and i+l (across-row lag l) and (iii) whether the within-row correlation depends only on lag (a Toeplitz structure expected for time samples) or on position (expected for electrodes). Because class-0 rows were smooth and lacked across-row continuity, we searched every 16-sample window of every row of the UCI Bonn file [18] for exact integer matches with BEED rows (SHA-256 of the file is recorded in the code).

3.3 Evaluation protocols

Random protocol. A stratified 80/20 row-level hold-out split and repeated (5 × 2) stratified cross-validation (CV), as in most prior work. **Blocked protocol.** Rows were first grouped: class-0 rows by their Bonn source segment (100 groups, from the audit) and class-1–3 rows into contiguous blocks of 200 rows (0.78 s at 256 Hz). The hold-out test set comprised the final 20% of each seizure recording and 20 randomly chosen Bonn segments. CV folds were formed by assigning whole groups to folds within each class. Training rows within 50 rows (0.195 s) of any test row of the same class were purged; across-row autocorrelation is close to zero at this lag (Table 2). In both protocols, hyper-parameters were chosen by an inner three-fold CV that followed the same protocol as the outer split (nested CV), optimising macro-F1. The test set was used once.

We studied three tasks: the four-class problem; a binary healthy-versus-seizure task; and a three-class seizure-type task (generalised, focal, seizure events) that excludes the healthy class and so removes the source shortcut.

3.4 Feature engineering

Each 16-value row was described by 57 engineered features in four groups. Time domain (24): moments, quantiles, root mean square, Hjorth activity, mobility and complexity [19], line length [20], mean absolute first and second differences, zero crossings, number of extrema and lag-1 autocorrelation. Frequency domain (14): relative power in the eight non-DC bins of a Hann-windowed 16-point FFT, spectral entropy, centroid, 80% edge, peak bin and a low/high power ratio. With only 16 points, conventional band powers (delta to gamma) cannot be resolved, so normalised bins were used. Nonlinear (7): permutation [22], sample and approximate entropy [21], singular-value-decomposition entropy and Petrosian, Katz and Higuchi fractal dimensions. Wavelet (12): log energy, relative energy, standard deviation and mean absolute value of the Daubechies-2 level-2 sub-bands [23,24]. Feature sets were raw

(16), engineered (57) and raw+engineered (73). For class 0 these features are temporal; for classes 1–3 they describe the spatial profile across electrodes (Section 4.1).

3.5 Models and training

Classical models [25]: multinomial logistic regression (LR), k-nearest neighbours (kNN), radial-basis-function support vector machine (SVM-RBF), random forest (RF), XGBoost [26] and LightGBM [27], plus a majority-class baseline. Compact grids are listed in Supplementary Table S1. Deep models [28] took the 16 standardised raw values as input: a multilayer perceptron (MLP), a three-layer one-dimensional convolutional network (1D-CNN), a bidirectional long short-term memory network (BiLSTM) and a two-layer transformer encoder. Each had 11–21 thousand parameters (Section 4.8). They were trained with AdamW (learning rate 0.002, weight decay 10^{-4}), batch size 128, up to 60 epochs, with early stopping (patience 8) on the macro-F1 of a validation split that respected the protocol. All random seeds were fixed (seed 42).

3.6 Metrics, uncertainty and statistical testing

We report accuracy, macro-F1, Cohen's kappa, one-vs-rest macro area under the receiver operating characteristic curve (AUC), per-class precision and recall, Brier score and expected calibration error (ECE, 15 bins) [29]. Hold-out 95% confidence intervals (CIs) were obtained from 2000 bootstrap resamples. Because test rows are autocorrelated, the primary CI is a class-stratified cluster bootstrap that resamples whole Bonn segments (class 0) or 50-row chunks (classes 1–3); naive row-level CIs are given in Supplementary Table S3. Models were compared on the 10 outer CV folds with the Nadeau–Bengio corrected resampled t-test [30,31] against the best model, with Holm correction, and with the Friedman test followed by Nemenyi post-hoc analysis [32].

3.7 Interpretability, ablation and deployment profiling

For LightGBM on raw+engineered features we computed TreeSHAP values [33] on the hold-out test set and gain importance. A feature-group ablation retrained LightGBM (fixed hyper-parameters) on each group alone and on all engineered features minus each group. To check whether seizure types are separable given true temporal context, we also built 0.25 s windows (64 rows) of classes 1–3 and computed per-channel log band powers (Welch, 256 Hz) and line length, evaluated by leave-one-block-out CV with neighbouring blocks purged. For deployment we counted parameters and measured median single-sample CPU latency (one thread, 500 repetitions).

3.8 Software and hardware environment

Experiments ran on a Linux virtual machine (8 virtual Intel Xeon CPUs, 16 GB RAM, no GPU) with Python 3.13, scikit-learn 1.9.1, XGBoost 3.4.1, LightGBM 4.7.0, PyTorch 2.14.1 (CPU), SHAP 0.52.0, SciPy 1.18.1, PyWavelets 1.10.0 and AntroPy 0.2.2. A single command (run_all.py) regenerates every table and figure (Supplementary File S1).

4 Results

4.1 The columns mean different things in different classes

Class 0 showed the signature of time samples: the within-row lag-1 correlation was 0.930 at every position (standard deviation across positions 0.002), decaying smoothly with lag, whereas consecutive rows were uncorrelated (r = -0.001) (Fig. 1, Table 2). Classes 1–3 showed the opposite pattern: across-row lag-1 correlations of 0.955, 0.845 and 0.983, falling to about zero by 50 rows, with position-dependent, non-Toeplitz correlations between columns. The strongest correlations occurred at lags 4, 8 and 12, a pattern consistent with four chains of four electrodes, as in a longitudinal bipolar montage. Thus, in classes 1–3, each row is one time point of a 16-channel recording, and each class is a contiguous recording of about

7.8 s at the documented 256 Hz. Classes also differed sharply in amplitude (row standard deviation 70.0 for class 0 versus 15.1, 7.9 and 10.2).




Figure 1. Correlation structure reveals different data layouts across classes. Top: column-by-column correlation matrices per class. Class 0 shows a Toeplitz band (time samples); classes 1–3 show position-specific structure with strong correlations at lags 4, 8 and 12 (electrode chains). Bottom: (i) mean within-row correlation versus column lag; (ii) mean across-row correlation versus row lag; (iii) lag-1 correlation for each adjacent column pair; (iv) distribution of row standard deviation (log scale). Classes: H, healthy; GS, generalised seizure; FS, focal seizure; SE, seizure events.

Table 2. Structural audit of the public BEED file by class

Class	Row SD	Within-row lag-1 r	SD of lag-1 r over positions	Across-row lag-1 r	Across-row lag-50 r	Exact Bonn matches	Inferred row layout
H (0)	70.0	0.930	0.002	-0.001	0.012	2000	16 samples × 1 channel
GS (1)	15.1	0.105	0.433	0.955	-0.047	0	1 time point × 16 channels
FS (2)	7.9	0.138	0.219	0.845	0.030	0	1 time point × 16 channels
SE (3)	10.2	0.200	0.249	0.983	0.007	0	1 time point × 16 channels

SD, standard deviation (dataset units); r, Pearson correlation. Exact matches: rows identical to a 16-sample window of the UCI Bonn file (2000 rows per class).

4.2 The healthy class is an excerpt of the Bonn dataset

All 2000 class-0 rows matched a 16-sample window of the UCI Bonn file exactly and uniquely; no row from classes 1–3 matched (Fig. 2). Every match came from Bonn label 4

(set B, healthy volunteers, eyes closed [5,18]), always at the same position (samples 159–174 of the 178-sample chunk), from 2000 distinct chunks of 100 distinct segments, in the same order as in the UCI file. Class 0 is therefore single-channel scalp EEG sampled at 173.61 Hz from another centre, not 16-channel EEG from Bangalore. The oscillation visible in its within-row correlation (Fig. 1, minimum at lag 8, recovery by lag 15) matches the eyes-closed alpha rhythm at that sampling rate.




Figure 2. BEED healthy rows are exact excerpts of Bonn eyes-closed recordings. (a) A Bonn set-B one-second chunk (grey, 173.61 Hz) with the identical BEED class-0 row overlaid (blue). (b) Number of rows per BEED class with an exact match anywhere in the 11 500 × 178 UCI Bonn file.

4.3 Quantifying temporal leakage

Under the random split, the nearest training neighbour of a test row in classes 1–3 was the immediately adjacent row of the same recording in 87.8%–95.2% of cases (median distance one row), versus 0.0% for class 0. Fig. 3 shows how macro-F1 declines as rows are allocated to folds in increasingly long contiguous blocks: LightGBM fell from 0.976 (random) to 0.759 (200-row blocks with purge) and 1-nearest-neighbour from 0.990 to 0.703. The decline tracks the decay of the across-row autocorrelation, so near-perfect random-split scores depend largely on near-duplicate neighbours.




Figure 3. Performance falls as folds are separated in time. Five-fold cross-validation macro-F1 (mean ± SD) when rows of classes 1–3 are assigned to folds in contiguous blocks of the given size (block size 1 is a random split). Dashed lines: no purge; solid lines: 50-row purge (shown for blocks of at least 100 rows, because smaller blocks leave almost no purged training data).

4.4 Hold-out benchmark under both protocols

Table 3 compares all models (bar chart in Supplementary Fig. S10). Under the random protocol, the best four-class model was kNN on raw features (macro-F1 0.986, 95% CI 0.980–0.992; accuracy 0.986), and kNN on raw values reached 0.986. Under the blocked protocol, the best model was SVM-RBF on raw features (macro-F1 0.842, CI 0.800–0.880; accuracy 0.844, CI 0.802–0.882; kappa 0.792), and kNN fell to 0.710. The ranking of models changed between protocols. On raw values, the largest random-to-blocked drop was for kNN (0.276) and the smallest for LR (0.047), so models that interpolate between near neighbours gained the most from leakage. The binary healthy-versus-seizure task was almost perfectly solved under both protocols (best macro-F1 1.000 random, 0.999 blocked). A single engineered feature with one threshold (within-row lag-1 autocorrelation) achieved a blocked-protocol accuracy of 0.997.

Errors under the blocked protocol were concentrated among the three seizure classes (Fig. 4). In the three-class seizure-type task the best model was kNN (raw) with macro-F1 0.990 under the random protocol, and SVM-RBF (raw) with 0.776 (CI 0.712–0.832) under the blocked protocol.

Table 3. Four-class hold-out results under random and blocked protocols

Model	Features	Macro-F1 random	Macro-F1 blocked (95% CI)	Accuracy blocked	Kappa blocked	AUC blocked	ECE blocked
LR	raw	0.483	0.436 (0.369–0.500)	0.440	0.253	0.666	0.087
kNN	raw	0.986	0.710 (0.667–0.750)	0.709	0.611	0.861	0.160
SVM-RBF	raw	0.903	0.842 (0.800–0.880)	0.844	0.792	0.962	0.053
RF	raw	0.964	0.795 (0.736–0.848)	0.803	0.737	0.942	0.077
XGBoost	raw	0.976	0.798 (0.755–0.838)	0.805	0.740	0.946	0.094
LightGBM	raw	0.986	0.810 (0.771–0.845)	0.816	0.755	0.949	0.077
LR	raw+eng	0.760	0.724 (0.672–0.775)	0.724	0.631	0.915	0.058
kNN	raw+eng	0.926	0.633 (0.601–0.668)	0.656	0.541	0.863	0.082
SVM-RBF	raw+eng	0.928	0.719 (0.674–0.769)	0.728	0.637	0.912	0.103
RF	raw+eng	0.943	0.755 (0.702–0.806)	0.768	0.691	0.919	0.033
XGBoost	raw+eng	0.962	0.784 (0.740–0.826)	0.790	0.720	0.940	0.096
LightGBM	raw+eng	0.973	0.799 (0.754–0.843)	0.807	0.742	0.942	0.148
MLP	raw	0.933	0.772 (0.720–0.820)	0.779	0.705	0.949	0.076
1D-CNN	raw	0.956	0.722 (0.674–0.765)	0.725	0.633	0.926	0.132
BiLSTM	raw	0.697	0.468 (0.410–0.526)	0.520	0.360	0.771	0.093
Transformer	raw	0.921	0.746 (0.699–0.790)	0.752	0.669	0.938	0.096

Random test set: 1600 rows; blocked test set: 1599 rows. CI: class-stratified cluster bootstrap (2000 resamples). AUC, one-vs-rest macro area under the ROC curve; ECE, expected calibration error. Engineered-only results, majority baseline (macro-F1 0.100) and per-class metrics are in Supplementary Tables S2–S4.




Figure 4. Confusion matrices of the best models per task and protocol. Counts with row-normalised proportions in parentheses. From left: four-class random, four-class blocked, three-class random and three-class blocked. Grey intensity encodes the proportion; numbers are printed.

4.5 Repeated cross-validation and statistical comparison

Table 4 summarises nested 5 × 2 CV on the development sets (raw+engineered features for classical models, raw values for deep models). Under the blocked protocol, LightGBM had

the highest mean four-class macro-F1 (0.767 ± 0.057); after Holm correction, the corrected t-test did not separate it from 1D-CNN, MLP, RF, XGBoost. For the three-class task, LightGBM was best (0.696 ± 0.075), statistically indistinguishable from 1D-CNN, MLP, SVM-RBF, XGBoost. Friedman tests rejected equal performance in all settings (four-class blocked $p = 5.4 \times 10^{-10}$; three-class blocked $p = 1.2 \times 10^{-9}$); mean ranks are shown in Supplementary Fig. S5. Fold-to-fold standard deviations were much larger under the blocked protocol (0.036–0.066 versus 0.004–0.014). The hold-out winner under the blocked protocol (SVM-RBF on raw values) differs from the CV winner on raw+engineered features (LightGBM); SVM-RBF on raw+engineered features reached only 0.665 in CV. A single leakage-safe split therefore cannot establish a definitive ranking; the CV comparison is more reliable.

Table 4. Nested 5 × 2 cross-validation macro-F1 and corrected t-tests

Model	4-class random	4-class blocked	p (Holm), 4-class blocked	3-class random	3-class blocked	p (Holm), 3-class blocked
LR	0.775 ± 0.012	0.653 ± 0.036	0.005	0.694 ± 0.011	0.544 ± 0.063	0.006
kNN	0.903 ± 0.009	0.629 ± 0.036	0.001	0.937 ± 0.007	0.546 ± 0.069	0.006
SVM-RBF	0.913 ± 0.010	0.665 ± 0.050	0.009	0.944 ± 0.005	0.602 ± 0.088	0.082
RF	0.935 ± 0.012	0.724 ± 0.051	0.052	0.918 ± 0.011	0.624 ± 0.081	0.018
XGBoost	0.959 ± 0.006	0.761 ± 0.052	0.944	0.949 ± 0.007	0.692 ± 0.083	0.733
LightGBM	0.965 ± 0.004	0.767 ± 0.057	best	0.959 ± 0.007	0.696 ± 0.075	best
MLP	0.923 ± 0.013	0.744 ± 0.066	0.944	0.938 ± 0.011	0.661 ± 0.096	0.598
1D-CNN	0.934 ± 0.014	0.733 ± 0.044	0.399	0.930 ± 0.012	0.646 ± 0.098	0.273

Mean ± SD over 10 outer folds. p: Nadeau–Bengio corrected resampled t-test against the best model under the blocked protocol, Holm-adjusted; 'best' marks the reference model. Per-fold scores: Supplementary Table S6.

4.6 Calibration

Calibration deteriorated under the blocked protocol: the median ECE across the ten non-baseline models on the four-class task rose from 0.029 (random) to 0.093 (blocked; computed over all feature sets). LightGBM on raw+engineered features, well calibrated under the random protocol (ECE 0.010), became overconfident on the temporally distant test blocks (ECE 0.148). For the best blocked model, ECE was 0.053 and the Brier score 0.238; the lowest blocked ECE was 0.029 (RF, eng features), at the cost of lower discrimination

(Supplementary Fig. S4). Probabilities should therefore be recalibrated on held-out recordings before any clinical use.

4.7 Interpretability and ablation

Under the random protocol, the most influential LightGBM features for the four-class task were t_hjorth_mob, X8, n_higuchi_fd, X11; under the blocked protocol they were X11, X8, t_hjorth_mob, t_lag1_ac (Fig. 5). For the three seizure types (blocked), the leading features were X11, X8, X15, X12, X6. The healthy class was separated almost entirely by smoothness descriptors (Hjorth mobility, Higuchi fractal dimension, singular-value-decomposition entropy and lag-1 autocorrelation), which is exactly the source shortcut identified in Section 4.2, whereas the seizure classes were separated by raw values of particular columns (notably X11, X8 and X15): the model relies on the spatial distribution of voltage across the 16 channels at each time point. In the ablation (Supplementary Fig. S6), raw values alone outperformed all engineered features combined under the blocked protocol for the four-class task (0.763 vs 0.634 CV macro-F1), because summary statistics computed across electrodes discard electrode identity. With genuine temporal context, the seizure types were more separable: 0.25 s multichannel band-power windows gave macro-F1 0.925 (LR) under leave-one-block-out CV, although only 93 windows were available.




Figure 5. Mean absolute SHAP values of the leading LightGBM features. Twelve most influential features (raw+engineered set), stacked by class, for the four-class task under

random and blocked protocols and for the three-class seizure-type task under the blocked protocol. X1–X16 are raw column values; prefixes t_, f_, n_ and w_ denote time, frequency, nonlinear and wavelet features. Hatching distinguishes classes.

4.8 Lightweight deployment

Table 5 lists model sizes and latencies. The MLP (11,076 parameters, 43 kB) classified one 16-value sample in 0.08 ms on a single CPU thread with blocked macro-F1 0.770; all four deep models needed less than 0.25 ms. LightGBM achieved a higher blocked macro-F1 (0.794) but its pipeline took 4.35 ms per sample, dominated by Python feature extraction, which exceeds the 3.9 ms sampling interval at 256 Hz unless samples are batched. The MLP therefore offers the best accuracy–cost trade-off for continuous on-device inference.

Table 5. Size, latency and blocked-protocol performance of deployable models

Model	Input	Parameters	Size (kB, 32-bit)	Latency (ms)	Macro-F1 blocked
MLP	raw 16 values	11,076	43.3	0.08	0.770
1D-CNN	raw 16 values	19,524	76.3	0.14	0.714
BiLSTM	raw 16 values	20,356	79.5	0.22	0.467
Transformer	raw 16 values	17,796	69.5	0.25	0.745
LightGBM	raw+engineered (77)	62,720 nodes	735.0	4.35	0.794

Latency: median of 500 single-sample predictions on one CPU thread (Intel Xeon virtual CPU), including standardisation and, for LightGBM, the 57-feature extraction. LightGBM size approximated from tree nodes. Deep models were retrained for profiling, so F1 may differ slightly from Table 3.

5 Discussion

The main finding is that the public BEED file combines two incompatible data layouts and two data sources. The 'healthy' class consists of single-channel Bonn snippets, while the seizure classes are multichannel time points from continuous recordings. Any classifier can therefore separate healthy from seizure rows from amplitude, smoothness or spectral shape, which explains the near-perfect binary results under both protocols and the near-perfect class-0 recall in all confusion matrices. This is a dataset artefact; it should not be read as evidence that seizures can be detected from 62 ms of EEG.

The second finding concerns evaluation. Consecutive seizure rows are 3.9 ms apart and correlated at $r \approx 0.85–0.98$, so a random split evaluates interpolation between neighbouring samples. Accuracies of 95–99% reported for row-level splits [8,10–12] agree with our random-protocol results; under the blocked protocol the best four-class macro-F1 fell by 0.145 and the ranking of models changed. This agrees with reports of leakage-inflated EEG results [15,16]. The blocked protocol is still optimistic, because training and test blocks come from the same recordings; since the file seems to contain about 7.8 s per seizure class, recording identity and seizure type are confounded, and subject-independent evaluation is impossible with the public file. Claims of subject-independent evaluation on this file should be treated with caution.

Clinically, the features that remained informative under the blocked protocol were the spatial voltage pattern across electrodes and its amplitude (Fig. 5). This is plausible (focal seizures involve a restricted region, generalised seizures both hemispheres), but the confound with recording identity prevents a physiological interpretation. The windowed analysis showed that adding temporal context improves seizure-type discrimination, which suggests that future BEED releases should provide segment-level multichannel data with subject identifiers. Finally, the deployment profile shows that an MLP of about 11 000 parameters (43 kB) runs in well under a millisecond and is statistically indistinguishable from the best model in blocked CV, so performance on this file is limited by data and evaluation rather than by model capacity.

6 Conclusion

The public BEED file is not a homogeneous 16-channel dataset: its healthy class is copied from the Bonn eyes-closed set, and its seizure classes are autocorrelated multichannel time points. Row-level random splits therefore inflate performance substantially. Under a leakage-aware protocol, four-class macro-F1 was 0.842 rather than 0.986, and seizure-type macro-F1

was 0.776 rather than 0.990. We recommend that BEED studies (i) exclude or replace the healthy class for clinical claims, (ii) use grouped, temporally blocked evaluation with purging, (iii) report cluster-bootstrap confidence intervals and calibration, and (iv) state the evaluation protocol explicitly.

7 Limitations and Future Work

The public file contains no subject identifiers, so neither our protocol nor any other can assess generalisation to new patients; the blocked protocol measures generalisation to unseen time within the same recordings. Our structural inferences about classes 1–3 (time points of continuous 256 Hz recordings, possibly a bipolar montage) rest on statistical evidence rather than documentation, and we could not determine whether each seizure class comes from one or several recordings. The provenance match covers only the Bonn file; classes 1–3 were not searched against other public databases. Hyper-parameter grids were deliberately compact, and the deep models were small and not exhaustively tuned. Future work will apply the protocol to the full segment-level BEED recordings if released, test cross-dataset transfer (for example, to CHB-MIT) and evaluate calibrated, patient-independent seizure-type classifiers.

Data Availability Statement

BEED is publicly available from the UCI Machine Learning Repository (doi:10.24432/C5K33B) [7]. The Bonn-derived Epileptic Seizure Recognition file used for the provenance check is available from its creators [18]. All derived results, figures and code are provided in Supplementary File S1 and at [Repository URL / DOI]. Code licence: [MIT or other licence].

Ethics Statement

This study analysed only publicly available, de-identified EEG data released for research use; no new data were collected and the authors had no access to identifying information. Ethics approval and consent to participate were therefore not required for this secondary analysis; consent for the original recordings is described by the data creators. Consent for publication: not applicable.

Declaration of Generative AI and AI-Assisted Technologies in the Manuscript Preparation Process

[Placeholder for the authors to finalise.] During this work, the authors used an AI assistant to help write analysis code, run experiments and draft and edit the manuscript text. The authors reviewed, verified and edited all content and take full responsibility for the publication. All numerical results were produced by the released code.

Declaration of Conflict of Interest

The authors declare no conflict of interest. [Authors to confirm.]

Acknowledgements

We thank the creators of BEED and of the Bonn EEG database for making their data publicly available. [Funding information, if any: Funder name, grant number.]

References

[1] Shoeb A, Guttag J. Application of machine learning to epileptic seizure detection. Proceedings of the 27th International Conference on Machine Learning (ICML). 2010:975–982.

[2] Acharya UR, Oh SL, Hagiwara Y, Tan JH, Adeli H. Deep convolutional neural network for the automated detection and diagnosis of seizure using EEG signals. Computers in Biology and Medicine. 2018;100:270–278. doi:10.1016/j.compbiomed.2017.09.017.

[3] Tsiouris KM, Pezoulas VC, Zervakis M, Konitsiotis S, Koutsouris DD, Fotiadis DI. A long short-term memory deep learning network for the prediction of epileptic seizures using EEG signals. Computers in Biology and Medicine. 2018;99:24–37. doi:10.1016/j.compbiomed.2018.05.019.

[4] Truong ND, Nguyen AD, Kuhlmann L, Bonyadi MR, Yang J, Ippolito S, et al. Convolutional neural networks for seizure prediction using intracranial and scalp electroencephalogram. Neural Networks. 2018;105:104–111. doi:10.1016/j.neunet.2018.04.018.

[5] Andrzejak RG, Lehnertz K, Mormann F, Rieke C, David P, Elger CE. Indications of nonlinear deterministic and finite-dimensional structures in time series of brain electrical activity: dependence on recording region and brain state. Physical Review E. 2001;64(6):061907. doi:10.1103/PhysRevE.64.061907.

[6] Goldberger AL, Amaral LAN, Glass L, Hausdorff JM, Ivanov PC, Mark RG, et al. PhysioBank, PhysioToolkit, and PhysioNet: components of a new research resource for complex physiologic signals. Circulation. 2000;101(23):e215–e220. doi:10.1161/01.CIR.101.23.e215.

[7] Najmusseher N, Nizar Banu PK. BEED: Bangalore EEG Epilepsy Dataset [dataset]. UCI Machine Learning Repository. 2024. doi:10.24432/C5K33B.

[8] Najmusseher N, Nizar Banu PK. Feature engineering for epileptic seizure classification using SeqBoostNet. International Journal of Computing and Digital Systems. 2025;17(1):1–15. doi:10.12785/ijcds/1571020131.

[9] Roy S, Asif U, Tang J, Harrer S. Seizure type classification using EEG signals and machine learning: setting a benchmark. arXiv preprint. 2019;arXiv:1902.01012. doi:10.48550/arXiv.1902.01012.

[10] Paneru B. Interpretable machine learning for epileptic seizure detection on the BEED using LIME with an ensemble network. medRxiv preprint. 2025. doi:10.1101/2025.09.30.25336996.

[11] Nandatama E. Benchmarking machine learning models for seizure classification: performance and robustness evaluation on the BEED dataset. Zenodo preprint. 2025. doi:10.5281/zenodo.17266895.

[12] Sajid MS, Ghosh AK, Nusrat F. PaperNet: efficient temporal convolutions and channel residual attention for EEG epilepsy detection. arXiv preprint. 2025;arXiv:2512.22172.

[13] Obaido G, Esenogho E. Evaluating EEG-based seizure classification using foundation and classical ensemble models. Applied Sciences. 2026;16(7):3120. doi:10.3390/app16073120.

[14] Heba KM, Atya AHA. EpilepsyFormer: a temporal self-attention framework enhanced with channel dynamics for high-fidelity EEG classification. Journal of Disability Research. 2026;5(1). doi:10.57197/JDR-2026-0812.

[15] Kapoor S, Narayanan A. Leakage and the reproducibility crisis in machine-learning-based science. Patterns. 2023;4(9):100804. doi:10.1016/j.patter.2023.100804.

[16] Brookshire G, Kasper J, Blauch NM, Wu YC, Glatt R, Merrill DA, et al. Data leakage in deep learning studies of translational EEG. Frontiers in Neuroscience. 2024;18:1373515. doi:10.3389/fnins.2024.1373515.

[17] Roberts DR, Bahn V, Ciuti S, Boyce MS, Elith J, Guillera-Arroita G, et al. Cross-validation strategies for data with temporal, spatial, hierarchical, or phylogenetic structure. Ecography. 2017;40(8):913–929. doi:10.1111/ecog.02881.

[18] Wu Q, Fokoue E. Epileptic Seizure Recognition data set [dataset]. UCI Machine Learning Repository. 2017. Copy distributed by the creators at github.com/QiuyiWu/Epileptic-Seizure-Recognition-Data (accessed 7 October 2026).

[19] Hjorth B. EEG analysis based on time domain properties. Electroencephalography and Clinical Neurophysiology. 1970;29(3):306–310. doi:10.1016/0013-4694(70)90143-4.

[20] Esteller R, Echauz J, Tcheng T, Litt B, Pless B. Line length: an efficient feature for seizure onset detection. Proceedings of the 23rd Annual International Conference of the IEEE Engineering in Medicine and Biology Society. 2001:1707–1710. doi:10.1109/IEMBS.2001.1020545.

[21] Richman JS, Moorman JR. Physiological time-series analysis using approximate entropy and sample entropy. American Journal of Physiology–Heart and Circulatory Physiology. 2000;278(6):H2039–H2049. doi:10.1152/ajpheart.2000.278.6.H2039.

[22] Bandt C, Pompe B. Permutation entropy: a natural complexity measure for time series. Physical Review Letters. 2002;88(17):174102. doi:10.1103/PhysRevLett.88.174102.

[23] Subasi A. EEG signal classification using wavelet feature extraction and a mixture of expert model. Expert Systems with Applications. 2007;32(4):1084–1093. doi:10.1016/j.eswa.2006.02.005.

[24] Lee GR, Gommers R, Waselewski F, Wohlfahrt K, O'Leary A. PyWavelets: a Python package for wavelet analysis. Journal of Open Source Software. 2019;4(36):1237. doi:10.21105/joss.01237.

[25] Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O, et al. Scikit-learn: machine learning in Python. Journal of Machine Learning Research. 2011;12:2825–2830.

[26] Chen T, Guestrin C. XGBoost: a scalable tree boosting system. Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. 2016:785–794. doi:10.1145/2939672.2939785.

[27] Ke G, Meng Q, Finley T, Wang T, Chen W, Ma W, et al. LightGBM: a highly efficient gradient boosting decision tree. Advances in Neural Information Processing Systems. 2017;30:3146–3154.

[28] Paszke A, Gross S, Massa F, Lerer A, Bradbury J, Chanan G, et al. PyTorch: an imperative style, high-performance deep learning library. Advances in Neural Information Processing Systems. 2019;32:8024–8035.

[29] Guo C, Pleiss G, Sun Y, Weinberger KQ. On calibration of modern neural networks. Proceedings of the 34th International Conference on Machine Learning (ICML), PMLR. 2017;70:1321–1330.

[30] Nadeau C, Bengio Y. Inference for the generalization error. Machine Learning. 2003;52(3):239–281. doi:10.1023/A:1024068626366.

[31] Bouckaert RR, Frank E. Evaluating the replicability of significance tests for comparing learning algorithms. Advances in Knowledge Discovery and Data Mining (PAKDD), Lecture Notes in Computer Science. 2004;3056:3–12. doi:10.1007/978-3-540-24775-3_3.

[32] Demšar J. Statistical comparisons of classifiers over multiple data sets. Journal of Machine Learning Research. 2006;7:1–30.

[33] Lundberg SM, Lee SI. A unified approach to interpreting model predictions. Advances in Neural Information Processing Systems. 2017;30:4765–4774.